MARK SCHEME for the October/November 2013 series

0625 PHYSICS

0625/33

Paper 3 (Extended Theory), maximum raw mark 80

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.



Page 2	Mark Scheme	Syllabus	Paper
	IGCSE – October/November 2013	0625	33

NOTES ABOUT MARK SCHEME SYMBOLS & OTHER MATTERS

- M marks are method marks upon which further marks depend. For an M mark to be scored, the point to which it refers **must** be seen in a candidate's answer. If a candidate fails to score a particular M mark, then none of the dependent marks can be scored.
- B marks are independent marks, which do not depend on other marks. For a B mark to scored, the point to which it refers must be seen specifically in the candidate's answers.
- A marks In general A marks are awarded for final answers to numerical questions. If a final numerical answer, eligible for A marks, is correct, with the correct unit and an acceptable number of significant figures, all the marks for that question are normally awarded. It is very occasionally possible to arrive at a correct answer by an entirely wrong approach. In these rare circumstances, do not award the A marks, but award C marks on their merits. However, correct numerical answers with no working shown gain all the marks available.
- C marks are compensatory marks in general applicable to numerical questions. These can be scored even if the point to which they refer are not written down by the candidate, **provided subsequent working gives evidence that they must have known it.** For example, if an equation carries a C mark and the candidate does not write down the actual equation but does correct substitution **or** working which shows he knew the equation, then the C mark is scored. A C mark is not awarded if a candidate makes two points which contradict each other. Points which are wrong but irrelevant are ignored.
- Brackets () around words or units in the mark scheme are intended to indicate wording used to clarify the mark scheme, but the marks do not depend on seeing the words or units in brackets e.g. 10 (J) means that the mark is scored for 10, regardless of the unit given.
- <u>Underlining</u> indicates that this <u>must</u> be seen in the answer offered, or something very similar.
- OR/or indicates alternative answers, any one of which is satisfactory for scoring the marks.
- e.e.o.o. means "each error or omission".
- o.w.t.t.e. means "or words to that effect".
- c.a.o. correct answer only
- Spelling Be generous about spelling and use of English. However, do not allow ambiguities e.g. spelling which suggests confusion between reflection/refraction/diffraction or thermistor /transistor/transformer.
- Not/NOT indicates that an incorrect answer is not to be disregarded, but cancels another otherwise correct alternative offered by the candidate i.e. right plus wrong penalty applies.
- Ignore indicates that something which is not correct or irrelevant is to be disregarded and does not cause a right plus wrong penalty.

Page 3	Mark Scheme	Syllabus	Paper
	IGCSE – October/November 2013	0625	33

e.c.f. meaning "error carried forward" is mainly applicable to numerical questions, but may in particular circumstances be applied in non-numerical questions. This indicates that if a candidate has made an earlier mistake and has carried an incorrect value forward to subsequent stages of working, marks indicated by e.c.f. may be awarded, provided the subsequent working is correct, bearing in mind the earlier mistake. This prevents a candidate being penalised more than once for a particular mistake, but **only** applies to marks annotated e.c.f.

Significant figures

Answers are normally acceptable to any number of significant figures \geq 2. Any exceptions to this general rule will be specified in the mark scheme.

Units Deduct one mark for each incorrect or missing unit from an answer that would otherwise gain all the marks available for that answer: maximum 1 per question.

Arithmetic errors

Deduct one mark if the **only** error in arriving at a final answer is clearly an arithmetic one.

Transcription errors

Deduct one mark if the only error in arriving at a final answer is because given or previously calculated data has clearly been misread but used correctly.

Fractions Only accept these where specified in the mark scheme.

	Page 4			Mark Scheme Syllabus				
				IGCSE – October/November 2013	0625	33		
1	(a)	(i)	(met	tals/they are) (good) conductors (of heat)		B1	[1]	
		(ii)		ot end) molecules vibrate (more) lectrons identified as mechanism of conduction		B1		
				ecules collide with their neighbours lectrons move faster/have more energy		B1		
				rgy/vibration passed on lectrons pass on energy/reach far end/free to move		B1	[3]	
	(b)	imn det	nerse ermin	e mass of spoon (condone weigh provided word ma spoon in water/liquid ie increase in volume/overflow or density = mass/volume	ss is used in answe	r) B1 B1 B1 B1	[4]	
						[Tota	al: 8]	
2	(a)	(<i>W</i> 2.5	, -	g or 0.25 × 10 or 250 × 10 or 2500		C1 A1	[2]	
	(b)	(i)		of proportionality or (the point where) proportionality nsion stops or Hooke's Law no longer obeyed (conc		B1	[1]	
		(ii)		lient or numbers from graph divided e.g. $4.5 \div 10$ N/cm or 45 N/m		C1 A1	[2]	
	(c)	(i)	0 (N) or zero or no net force etc. (ignore absent unit; wro	ong unit loses mark)) B1	[1]	
		(ii)		0.9N (accept 0.8N < value < 1.0N)		B1	[1]	
				(a =) <i>F/m</i> or 0.90/0.12 (e.c.f. from 2(c)(i)) 7.5 m/s ² (e.c.f. from 2(c)(i))		C1 A1	[2]	
3	(a)	•	,	<i>F</i> × <i>d</i> or 640 × 3.5 o 2 or more sig. figs.		C1 A1	[2]	
	(b)	(i)	(<i>E</i> = 7500) <i>VIt</i> or 75 × 25 × 4.0 or 75 × 100 (accept (<i>E</i> =) <i>V</i> Q	and Q = It)	C1 A1	[2]	
		(ii)	(effic	ciency =) (useful)energy output energy input (× 100%) or 2240/7	7500			
			(acc	ept power for energy) (e.c.f. from 3(a)(i) or 3(b)(i)) or 0.30 or 0.299 or 30% or 29.9% (e.c.f. from 3(a)(i)		C1 A1		

	Pa	Page 5				Paper		
				IGCSE – October/November 2013	0625	33		
	(c)	any two from: electrical heating friction W.D. lifting supports sound					[2]	
						[Tota	ıl: 8]	
4	(a)	(i)	(GPI 34 J	E =) <i>mgh</i> or 0.40 × 10 × 8.5 (accept 9.8 for 10)		C1 A1	[2]	
		(ii)	or 2	= GPE in any form or ½ mv ² or 2 gh × 10 × 8.5 (e.c.f. from 4(a)(i))		C1		
				e) 170 or (<i>v</i> =)√170 f. from 4(a)(i))		C1		
				n/s e.c.f. from 4(a)(i)		A1	[3]	
	(b)		drag or air resistance or friction with air (ignore wind for air) WD or energy lost as heat or more KE needed to overcome drag etc.					
	(c)	transformed to thermal energy/heat or friction/air resistance slows parachutist dow						
		or lost to air particles (not KE (accept KE of air), not GPE \rightarrow KE \rightarrow heat; ignore sound)				B1	[1]	
5	(a)	(nu	clear)) fusion		B1	[1]	
	(b)	(i)		ller (surface) area ept thinner, narrower(at top), ignore reference to lid))	B1	[1]	
		(ii)		aratus: black object, white object, thermometer(s)/ba /level of water in vessel	III-bearing with	B1		
			sour	ce of heat e.g. Sun/radiant heater (condone light bu	lb/Bunsen burner)	B1		
				on: (fill cans with water and) measure temperature ris pare volumes of water	se or wax melts or	B1		
			incre	ervation: water in black can (better absorber) has gre ease / wax melts first / less water	eater temperature	54		
			note	emission experiment gains max. 2		B1	[4]	

PMT

	Pa	ge 6	;	Mark Scheme Syllabus			
		<u>J</u>		IGCSE – October/November 2013	0625	Paper 33	
6	(a)	(<i>Q</i> / <i>E</i> =) <i>Pt</i> or 2400 × 50 1.2 × 10 ⁵ (J) (<i>c</i> =) <i>Q</i> / <i>m</i> Δ <i>T</i> or 1.2 × 10 ⁵ /(1.5 × 32) (condone 2400/(1.5 × 32)) (allow e.c.f. from candidate's <i>Q</i> = 1.2 × 10 ⁵) 2.5 × 10 ³ J/(kg °C) or 2.5 J/(g °C) (condone missing brackets)					
				c.f. from candidate's $Q = 1.2 \times 10^5$)		A1	[4]
	(b)	(stu	ident'	s value) too large and heat lost to surroundings/kett	le/evaporation	B1 [Tota	[1] il: 5]
7	(a)	or 2 0.9	25° 641	sin <i>r</i> or <i>n</i> = sin <i>r</i> /sin <i>i</i> or (sin <i>i</i> =) 1.5 sin 40(°) i or (sin to 2 or more sig. figs.	n r =) 1.5 sin 40(°)	C1 C1 A1	[3]
	(b)		2.01) $f\lambda$ or 3.8 × 10 ¹⁴ × 5.3 × 10 ⁻⁷ × 10 ⁸ m/s to 2 or more sig. figs.		C1 A1	[2]
		(ii)		nv or 1.5 × 2.0/2.01/2.014 × 10 ⁸ (e.c.f. from 7(b)(i)) × × 10 ⁸ m/s (accept 3 or 3.0 × 10 ⁸ m/s only with worl f. from 7(b)(i))	king)	C1 A1	[2]
	(c)	aloı wav	ng`no /e(fro	nt) hits/enters the plastic at the same time or incide rmal/at 90° or $i = 0°$ (condone it doesn't hit at an an nt) all slows down at the same time or refracted ray = 0° by calculation	gle)	B1 al/at B1	[2]
						[Tota	ii: 9]
8	(a)	(i)		wave rectified trace (ignore horizontal lines) zontal lines and wavelength same and amplitude sa	me/slightly reduced	M1	
			(≥ ¾	A ₀ by eye)		A1	[2]
		(ii)		fier or suitable device or produce d.c. (from a.c. for done flashing lamp of some sort)	electronic circuits)	B1	[1]
	(b)			comes) dimmer/less bright/flashes on and off rmal)energy/heat/power or (thermal) energy etc. for	less time or current	B1	
			•	s zero		B1	[2]
						[Tota	l: 5]

	Page 7		/	Mark Scheme	Syllabus	Paper	
				IGCSE – October/November 2013	0625	33	
9	(a)	alte volt	ernatir tage/e	ing current causes alternating/changing) magnetic fien ng/changing magnetic field in secondary coil e.m.f. induced (in secondary coil) ns (on secondary) so greater output	eld (in core)	B1 B1 B1 B1	[4]
	(b)	(i)	(ene	stance increases (with/is proportional to length (of caergy losses) due to resistance (of cables)/heating in c ables)/ <i>I</i> ² <i>R</i>		B1 orking B1	[2]
		(ii)	 (ii) reduced resistance or less heat loss more metal or cables heavier or more pylons or more costly to construct 				[2]
						[Tota	l: 8]
10	(a)	 (i) at least two lines (one left, one right) outside the coil of correct shape or at least two vertical lines inside the coil or two diverging and one central line at top and bottom at least four lines (two left, two right) outside the coil of correct shape or at least two lines (one left, one right) outside the coil of correct shape) and at least two 				and C1 least	
				cal lines inside the coil ssing or complete loops outside coil gains maximum	of 1)	A1	[2]
		(ii)	lines	s closer where field is stronger o.w.t.t.e. or vice versa	a or spacing of line	s B1	[1]
	(b)			(strength of) field ng the resistance) reduces the current		B1 B1	[2]
	(c)	(i)	curv well-	ed path upwards (might curve back to the left) -drawn curved path (no straight section and circular l	by eye)	B1 B1	[2]
		(ii)		res in opposite direction to (c)(i) Inetic field reversed		B1 B1	[2]
						[Tota	l: 9]
11	(a)	12	count	rs/min		B1	[1]
	(b)	(i)	72 c	counts/min (e.c.f. from 11(a))		B1	
		(ii)		ounts/min (note: if background not subtracted, (i) 84 Impensatory mark)	and (ii) 21 gains	B1	[2]
	(c)	or ((e.c.f.	1/8 or 3 (half-lives)) 21/84 or 1/4 or 2 (half-lives) ites or 4.5 minutes (i.e. background not subtracted b	ut otherwise correc	C1 ct) A1	[2]
		[Tota					