

## PH1 Mark Scheme – January 2010

Question		Marking details	Marks Available
1.	(a)	Flow of charge [accept ....charge/ions] or $\frac{[\Delta]Q}{[\Delta]t}$ , if the symbols defined	1
	(b)	(i) Sum of areas of triangle and rectangle areas attempted [or reasonable attempt at area of trapezium] (1) $Q = 3.0 \text{ C ((unit))(1)}$	2
		(ii) No. of electrons = $\frac{3.0(\text{e.c.f.})}{1.6 \times 10^{-19}} = 1.9 \times 10^{19}$ (1) [1 <sup>st</sup> mark div by $e$ ]	2
		(iii) $I = 1.2(0) \text{ A}$ (from graph) (1); $v = \frac{I}{nAe}$ [manipulation shown – could be in following substitution – or by impl.](e.c.f. on $I$ )(1) $= 3.75 \times 10^{-5} \text{ m s}^{-1}$ [accept $3.8 \times 10^{-5} \text{ m s}^{-1}$ ] (e.c.f. on $I$ ) (1)	3
			<b>[8]</b>
2.	(a)	<u>Free</u> [or equiv, e.g. conducting / moving / delocalised] electrons (1) collide / interact / hindered [by] (1) with atoms / ions of metal conductor / lattice [“particles” b.o.d.](1)	3
	(b)	(i) I. [0 – 2 V]: Resistance constant / changes by v. small amount II. [2 – 8 V]: Resistance increases	1 1
		(ii) <b>Either</b> $R_{\text{bulb}} = \frac{6.0}{0.8(1)} = 7.5 \Omega$ (1) Total resistance = $5 \Omega$ (1) [ecf] $\left[ \text{Correct use of } \frac{1}{R} = \frac{1}{R_1} + \frac{1}{R_2} \right]$ $I = 1.2 \text{ A}$ (1) [ecf on $R$ ]	4
		<b>Or</b> $I$ through $15\Omega = \frac{6.0}{15}$ (1) = $0.4 \text{ A}$ (1) $I$ through bulb = $0.8 \text{ A}$ (1) $\therefore$ Total current = $1.2 \text{ A}$ (1)	
		(iii) Subst in $P = I^2R$ [ecf on $R$ and $I$ ] or in $P = \frac{V^2}{R}$ [ecf on $R$ only] or $P = IV$ [ecf on $I$ only] (1) $P = 7.2 \text{ W}$ (1)	2
			<b>[11]</b>

Question		Marking details	Marks Available
3.	(a)	The electrical (potential) <u>energy transferred</u> [or <u>work done</u> ] <i>per coulomb / unit charge passing through the cell</i> [ <u>Underlined</u> (1); <i>italic</i> (1)]	2
	(b)	Voltmeter shown in parallel with cell [outside the dotted line – accept inside the line if outside the cell/i.r combination] [Accept equivalent, e.g. connected in parallel with resistor]	1
	(c)	All points correctly plotted (2) [–1 per mistake, min 0] Line correctly drawn [with extrapolation just to $V$ axis] (1)	3
	(d)	(i) [e.m.f. =] 1.6 V	1
	(ii) gradient attempted [or by impl.](1); $r = 0.33 \Omega / 0.3 \Omega / \frac{1}{3}\Omega$ (1)	2	
			<b>[10]</b>
4.	(a)	(i) $\frac{\text{Total distance}}{\text{[Total] time}}$ [or equiv.] [ <b>Not</b> rate of change of distance]	1
		(ii) Time for the whole journey = 3 h + 4 h = 7 h (1) [or 25 200 s] Mean speed = $\frac{480(1)}{7} \left[ \frac{480000}{25200} \right] = 68.6 \text{ km h}^{-1}$ (1)[accept 69 – not 70]	3
	(b)	(i) Forward force labelled Driving / engine force <b>and</b> reverse force labelled Friction / drag / air resistance]	1
		(ii) Maximum at $t = 0$ (s) [accept: starts high at $t = 0$ ](1) Decreases (1) to zero [after 8 s] (1)	3
		(iii) $a = \frac{\Delta v(\text{from tangent})}{\Delta t (\text{from tangent})}$ (= 2.75 [accept 2.6 – 2.9] $\text{m s}^{-1}$ ) (1) $\Sigma F = ma / \Sigma F = 350 \times 2.75(\text{ecf})$ (1)= 962.5 [accept 910 – 1015] N (1)	3
	(c)	(i) Force $\times$ distance (moved) (1) in the direction of the force (1) [or equivalent, e.g. component of force in the direction of motion $\times$ distance moved, $Fd\cos\theta$ if symbols defined]	2
		(ii) Power $P = \frac{\text{work done}}{\text{time}}$ or $P = \frac{Fd}{t}$ (1) $d/t$ <u>identified</u> with $v$ (1) [by impl. if $F \times d / t$ used to define power]	2
		(iii) $F = \frac{40 \times 10^3}{18}$ [=2200 N]	1
	(d)	(i) Energy cannot be created or destroyed only changed from one form to another.	1
		(ii) Brake pads and wheel discs heat up (1) [accept k.e. $\rightarrow$ heat energy] Reference to particles' gaining energy (1)	2
			<b>[20]</b>

Question		Marking details	Marks Available
5.	(a)	(i) Wire with rule positioned (1) and <u>labelled</u> moving pointer / jockey / croc clip (1) <b>Either</b> correctly positioned ohm-meter with no power supply <b>or</b> correctly position ammeter and voltmeter with power supply (1)	3
		(ii) [Different] length[s] of wire (1) <b>Either</b> measure $V$ and $I$ <b>or</b> measure / read $R$ (1)	2
		(iii) Diameter of wire [not radius or csa by accept "thickness"] with micrometer / vernier calliper	1
		(iv) cross-sectional area fro $\pi r^2$ or $\pi(d/2)^2$ (1) graph of $R$ against $l$ [ <b>or</b> mean value of $R/l$ ] (1) $\rho = \text{gradient} \times [\text{cs}]a$ [ <b>or</b> mean value of $R/l \times \text{csa}$ ] (1) [NB $R = V/I$ given here can be used to credit 2 <sup>nd</sup> mark of (ii)] [NB Finding $R$ for a measured length and [cs] area and then $\rho$ calculated $\rightarrow$ 1 only]	3
	(b)	(i) $R \propto l$ (1) $\therefore R$ <u>increases</u> as strain gauge gets longer (1) $R \propto 1/A$ (1) $\therefore R$ <u>increases</u> as the strain gauge gets thinner (1) [ <b>or</b> $R = \frac{\rho l}{A}$ or $\rho = \frac{RA}{l}$ (1), $A$ increases & $l$ decreases (1) $\rho$ doesn't change /constant (1) so resistance increases (1)]	4
		(ii) [csa =] $0.2 \times 10^{-3} \times 0.0012 \times 10^{-3}$ [or equiv.] (1) $\rho = 4.9 \times 10^{-7} \Omega \text{ m}$ (( <b>unit</b> )) (1) [ecf from csa calculation] [ecf on powers of 10 in both $A$ and $l$ ]	2
		(iii) <b>Either</b> $1.6 = \frac{650}{650 + R} \times 6$ (1) Manipulation (1); $R = 1788 \Omega$ (1) <b>Or</b> $I = \frac{1.6}{650}$ ( $= 2.46 \times 10^{-3} \text{ A}$ ) (1) $R = \frac{(6 - 1.6)(1)}{2.46 \times 10^{-3}} = 1788 \Omega$ (1)	3
			<b>[18]</b>

Question		Marking details	Marks Available	
6.	(a)	(i) Horizontal arrow [by eye] to right, close to <b>A</b> , labelled <b>D</b> . (1)	2	
		(ii) Vertically downwards arrow at <b>A</b> labelled <b>F</b> . (1)[NB if other force(s) labelled, s.i.f. $\rightarrow 0$ ]		
	(b)	(i) $U_H = \frac{4.50}{1.50} (= 3.0 \text{ m s}^{-1})$	1	
		(ii) Use of relevant equation, e.g. $v = u + at$ or $v^2 = u^2 + 2ax$ (1) [or by impl.] Correct subst e.g. $0 = u - 9.81 \times 0.75$ or $0 = u^2 - 2 \times 9.81 \times 2.75$ (1) [or by impl.] Answer $U = 7.3 / 7.35 / 7.4 \text{ m s}^{-1}$ (1)	3	
		(iii) $U = \sqrt{3.0^2 + 7.4^2}$ [or $U^2 = 3^2 + 7.4^2$ ] (1) [e.c.f. on both velocities] $= 7.9 - 8.0 \text{ m s}^{-1}$ (1)	2	
	(c)	(i) $E_{\text{total}} = mgh + \frac{1}{2}mv_H^2$ [or by impl.] [Accept $E_{\text{total}} = \text{P.E.} + \text{K.E.}$ ] (1) $= 6.0 \times 9.81 \times 2.75 + \frac{1}{2} \times 6.0 \times 3.0^2$ [e.c.f. on $v_H$ ] (1) [subst] $= 189 \text{ J}$ (1) [NB If only PE considered then 0]	3	
		(ii) Extreme points of trajectory <b>both</b> marked with a <b>K</b> .	1	
		(iii) $\frac{1}{2}mU^2 = 189$ (1) [e.c.f.] [accept $\text{KE} = 189 \text{ J}$ ecf] $U = 7.9 \text{ m s}^{-1}$ (1)	2	
				[14]