



PH1

Question			Marking details	Marks Available
1	(a)	(i)	Horizontal velocity = $\frac{1.20}{0.60} = 2[.0 \text{ m s}^{-1}]$	1
		(ii)	$0 = u^2 - 2 \times 9.81 \times 0.44$ [correct substitution into $v^2 = u^2 + 2ax$] (1) $u = 2.94 [\text{m s}^{-1}]$ (1) or $0 = u - 9.81 \times 0.30$ [correct substitution into $v = u + at$] (1) $u = 2.94 [\text{m s}^{-1}]$ (1) [Other solutions possible]	2
	(b)	(i)	$R = (4 + 8.64)^{1/2}$ (1) [ecf from (a)(i) and/or (a)(ii)] $R = 3.56 [\text{m s}^{-1}]$ (1)	2
		(ii)	$\theta = 55.8^\circ$ ecf	1
	(c)	(i)	<u>Force of gravity on earth due to grasshopper</u>	1
(d)	(ii)	$F = 3 \times 10^{-5} \times 9.81 = 2.9 \times 10^{-4} [\text{N}]$ Accept 0.3 m[N]	1	
			1	
		Question 1 Total	[9]	
2	(a)	$V \text{ A}^{-1}$ and $W \text{ A}^{-2}$ 2 × (1)	2	
	(b)	(i)	$V = 0.01 \times 450 = 4.5 [\text{V}]$	1
		(ii)	$12 \text{ V} - 4.5 \text{ V}$ [ecf] = 7.5 [V]	1
	(iii)	$R = \frac{7.5}{0.01}$ (1 for correct use of 7.5 or ecf) = 750 [Ω] (1) or correct alternative	2	
(iv)	$\frac{1}{750} = \frac{1}{900} + \frac{1}{R}$ (1) (substitution) $R_{\text{variable resistor}} = 4500 [\Omega]$ (1) Alternative solution to (iii) and (iv) I through $900 \Omega = \frac{7.5}{900} = 0.0083 [\text{A}]$ (1) I through variable resistor = 0.0017 [A] (1) $R_{\text{variable resistor}} = \frac{7.5}{0.0017} = 4500 [\Omega]$ (1) Use of resistors in parallel formula to find total parallel resistance = 750 [Ω] (1)	2		

Question		Marking details	Marks Available
	(c)	<p>[No mark for stating circuit resistance decreases] Current in circuit increases (1) [accept explanation based on potential divider. Hence pd across $450\ \Omega$ increases (1) Hence pd across $900\ \Omega$ decreases (1) this mark can't be awarded unless it is correctly substantiated</p> <p>Alternative solutions: Resistance of parallel combination decreases (1) pd across parallel combination decreases (1) pd across $900\ \Omega$ decreases (1) OR current through the variable resistor increases (1) current through the $900\ \Omega$ decreases (1) pd across the $900\ \Omega$ decreases (1)</p> <p>Question 2 total</p>	<p>3</p> <p>[11]</p>

Question			Marking details	Marks Available
3	(a)	(i)	[Free] electrons forced to move by applied pd (Need a reference to drift velocity or electron flow but does not need to be explicitly stated) (1) They collide with atoms/nuclei/ions/lattice of the wire (1) don't accept particles or molecules	2
		(ii)	Power = $\frac{1.8}{60} = 0.03$ [W] (1) $R = \frac{0.03(\text{ecf})}{1.6^2} = 0.0117$ [Ω] (1) Alternative solution possible for the first 2 marks using $V = \frac{W}{Q}$ and $R = \frac{V}{I}$ $\rho = \frac{0.0117 \times 2 \times 10^{-6}}{0.4}$ (1) [ecf on R] $= 5.9 \times 10^{-8}$ [$\Omega \text{ m}$] (1)	4
	(b)	(i)	 [NB free electrons not required to be labelled] Number of free electrons = $nAvt$ [or nAl] (1) Total change = $nAvte$ [or $nAle$] (1) $I = \frac{nAvte}{t}$ with cancelling shown [or $\frac{nAle}{t}$, where $\frac{l}{t} = v$ shown] (1) Volume defined either from diagram [e.g. A and l labelled as shown] or in body of derivation [e.g. $\text{vol} = Al$] and n identified correctly – for the first mark	4
		(ii)	$1.6 = 6.4 \times 10^{28} \times 2 \times 10^{-6} \times v \times 1.6 \times 10^{-19}$ (1: substitution) $v = 7.8 \times 10^{-5}$ [m s^{-1}] (1)	2
		(iii)	(I) less than 1.6 A identified/circled (1) (II) the same as identified/circled (1) (III) half identified/circled (1)	3
	Question 3 Total			[15]

Question		Marking details	Marks Available
4	(a)	(i) Water bath or method of heating shown. Wire [coiled or uncoiled] shown (1). Voltmeter and ammeter and power supply correctly connected or ohmmeter only shown (1) Thermometer clearly identifiable. (1) Subtract 1 mark for poorly drawn diagrams. Method of cooling water to 0 °C not credited here.	3
		(ii) <u>Method</u> of cooling water to 0 °C (1) [Can be credited from (i)] Resistance values taken [or V and I values taken and R calculated](1) ..at different temperatures [minimum 5 implied or implication that a number of temperatures considered] (1) Method to reduce experimental error/ ensure accuracy e.g. water stirred/ resistance of leads/heat slowly/remove heat to allow temperature to settle (1) Accept repeat the experiment again or obtain readings whilst cooling down or using a digital thermometer. Don't accept just repeat readings. Graph of R vs θ drawn (1)	5
	(b)	(i) [-163 °C] is the temperature at which <u>a sudden decrease in resistance</u> occurs and the metal [alloy] (1) ...becomes a <u>superconductor</u> or resistance becomes zero (1)	2
		(ii) <u>Liquid nitrogen</u> [Accept liquid helium, liquid oxygen, liquid hydrogen]	1
	Question 4 Total		

Question			Marking details	Marks Available
5	(a)	(i)	power = $\frac{\text{work done or energy transferred}}{\text{time}}$ [Accept rate of doing work/ rate of energy transfer]	1
		(ii)	$\text{kg m s}^{-2} \times \text{m} \times \text{s}^{-1}$ (1) [Evidence of full correct methodology] $\text{kg m}^2 \text{s}^{-3}$ (1)	2
	(b)	(i)	$E_p = 70 \times 9.81 \times 215$ (1) [= 147 641 J] $E_k = \frac{1}{2} (70)(35)^2$ (1) [= 42 875 J] $E_{\text{lost}} = 147 641 - 42 875$ (1) [= 104 766] (ecf on both E_p and E_k) $F = \frac{104766}{1600} = 65.5$ [N] (1) (ecf on E_{lost})	4
		(ii)	Alternative solution: using $v^2 = u^2 + 2ax$ $P = \frac{104766}{46}$ ecf (1) = 2277 J s ⁻¹ or W (1) UNIT mark	2
			Question 5 total	[9]
6	(a)		 <p style="text-align: right;">(1)</p>	2
			Moment = Fd (1) [award only if clear diagram shown] / if no right angle in diagram then perpendicular must be included in definition	
	(b)	(i)	$(F \sin 40^\circ)(1) \times 0.4$ (1) = $((12 \times 0.9) + (22 \times 1.8))$ (1) $F = 196$ [N] shown	3
	(ii)	(I) Vertical component of force in strut = 126 [N] (1) Accept 128 [N] or 129 [N] if $F = 200$ N is used. (II) Vertical downward arrow shown at hinge. (1) (III) Vertical force on bar due to hinge = 92 [N] (1) ecf	3	
			Question 6 Total	[8]

Question			Marking details	Marks Available	
7	(a)	(i)	[Vector] distance between two locations measured along the shortest path joining them.	1	
		(ii)	(I)	Time for outward journey = 7.5 hrs and homeward journey = 5 hrs calculated (1) Speed = $\frac{600}{12.5}$ (1) = 48 [km h ⁻¹] (1)	3
			(II)	0 km h ⁻¹ (1) displacement = 0 stated (1)	2
		(b)	(i)	Suitable tangent drawn (1) = 0.15 (accept range 0.12 to 0.18) (1) $\Sigma F = 1.2 \times 10^6 \times 0.15 = 180$ [kN] (1) [ecf on gradient value] ΣF range = 144 kN to 216 kN	3
	(ii)		Line (or time axis) labelled at ≥ 92 or 94 seconds	1	
	(iii)		Constant speed (1) Driving force balanced [equal to] resistive forces (1) [Do not accept $\Sigma F = 0$]	2	
	(c)	(i)	(I)	$F = \frac{Wx}{t}$ and $\frac{x}{t}$ shown to be = v	1
			(II)	v (from graph) = 17.2 ms ⁻¹ (1) $F = \frac{4.5 \times 10^6}{17.2} = 262$ [kN] (1)	2
		(ii)	180 000 = 262 000 – F_{drag} (1) [ecf on both forces] $F_{\text{drag}} = 82$ [kN] (1)	2	
	Question 7 Total				[17]