



Cambridge International AS & A Level

COMPUTER SCIENCE**9618/23**

Paper 2 Fundamental Problem-solving and Programming Skills

May/June 2021

INSERT

2 hours

INFORMATION

- This insert contains all the resources referred to in the questions.
- You may annotate this insert and use the blank spaces for planning. **Do not write your answers** on the insert.



This document has **4** pages.

Note: An error occurs if a function call is not properly formed, or if the parameters are incorrect.

STRING Functions

LEFT(ThisString : STRING, x : INTEGER) RETURNS STRING
returns leftmost x characters from ThisString

Example: LEFT("ABCDEFGH", 3) returns "ABC"

RIGHT(ThisString : STRING, x : INTEGER) RETURNS STRING
returns rightmost x characters from ThisString

Example: RIGHT("ABCDEFGH", 3) returns "FGH"

MID(ThisString : STRING, x : INTEGER, y : INTEGER) RETURNS STRING
returns a string of length y starting at position x from ThisString

Example: MID("ABCDEFGH", 2, 3) returns "BCD"

LENGTH(ThisString : STRING) RETURNS INTEGER
returns the integer value representing the length of ThisString

Example: LENGTH("Happy Days") returns 10

LCASE(ThisChar : CHAR) RETURNS CHAR
returns the character value representing the lower case equivalent of ThisChar
Characters that are not upper case alphabetic are returned unchanged

Example: LCASE('W') returns 'w'

UCASE(ThisChar : CHAR) RETURNS CHAR
returns the character value representing the upper case equivalent of ThisChar
Characters that are not lower case alphabetic are returned unchanged

Example: UCASE('a') returns 'A'

TO_UPPER(ThisString : STRING) RETURNS STRING
returns a string formed by converting all characters of ThisString to upper case

Example: TO_UPPER("Error 803") returns "ERROR 803"

TO_LOWER(ThisString : STRING) RETURNS STRING
returns a string formed by converting all characters of ThisString to lower case

Example: TO_LOWER("JIM 803") returns "jim 803"

NUM_TO_STR(x : <data type>) RETURNS STRING
returns a string representation of a numeric value
Note: <data type> may be REAL or INTEGER

Example: NUM_TO_STR(87.5) returns "87.5"

STR_TO_NUM(x : <data type1>) RETURNS <data type2>

returns a numeric representation of a string

Note: <data type1> may be CHAR or STRING

Note: <data type2> may be REAL or INTEGER

Example: STR_TO_NUM("23.45") returns 23.45

IS_NUM(ThisString : STRING) RETURNS BOOLEAN

returns the value TRUE if ThisString represents a valid numeric value

Note: <data type> may be CHAR or STRING

Example: IS_NUM("12.36") returns TRUE

Example: IS_NUM("-12.36") returns TRUE

Example: IS_NUM("12.3a") returns FALSE

ASC(ThisChar : CHAR) RETURNS INTEGER

returns an integer value (the ASCII value) of ThisChar

Example: ASC('A') returns 65

CHR(x : INTEGER) RETURNS CHAR

returns the character whose integer value (the ASCII value) is x

Example: CHR(87) returns 'W'

NUMERIC Functions

INT(x : REAL) RETURNS INTEGER

returns the integer part of x

Example: INT(27.5415) returns 27

RAND(x : INTEGER) RETURNS REAL

returns a real number in the range 0 to x (**not** inclusive of x)

Example: RAND(87) could return 35.43

DATE Functions

Note: Date format is assumed to be DDMMYYYY unless otherwise stated.

DAY(ThisDate : DATE) RETURNS INTEGER

returns the current day number from ThisDate

Example: DAY(4/10/2003) returns 4

MONTH(ThisDate : DATE) RETURNS INTEGER

returns the current month number from ThisDate

Example: MONTH(4/10/2003) returns 10

`YEAR(ThisDate : DATE)` RETURNS INTEGER
returns the current year number from `ThisDate`

Example: `YEAR(4/10/2003)` returns 2003

`DAYINDEX(ThisDate : DATE)` RETURNS INTEGER
returns the current day index number from `ThisDate` where Sunday = 1, Monday = 2, Tuesday = 3 etc.

Example: `DAYINDEX(12/05/2020)` returns 3

`SETDATE(Day, Month, Year : INTEGER)` RETURNS DATE
returns a variable of type DATE

`NOW()` RETURNS DATE
returns the current date

OTHER Functions

`EOF(fileName : STRING)` RETURNS BOOLEAN
returns TRUE if there are no more lines to be read from file `fileName`

Note: This function will generate an ERROR if the file is not already open in READ mode

OPERATORS

&	Concatenates (joins) two strings Example: "Summer" & " " & "Pudding" evaluates to "Summer Pudding" Note: This operator may also be used to concatenate a character with a string
AND	Performs a logical AND on two Boolean values Example: TRUE AND FALSE evaluates to FALSE
OR	Performs a logical OR on two Boolean values Example: TRUE OR FALSE evaluates to TRUE
NOT	Performs a logical NOT on a Boolean value Example: NOT TRUE evaluates to FALSE
MOD	Finds the remainder when one number is divided by another Example: 10 MOD 3 evaluates to 1
DIV	Finds the quotient when one number is divided by another Example 10 DIV 3 evaluates to 3

Note: An error is generated if an operator is used with a value or values of an incorrect type.

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge Assessment International Education Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cambridgeinternational.org after the live examination series.

Cambridge Assessment International Education is part of the Cambridge Assessment Group. Cambridge Assessment is the brand name of the University of Cambridge Local Examinations Syndicate (UCLES), which itself is a department of the University of Cambridge.