



**General Certificate of Education**

**Mathematics 6360**

**MM1B      Mechanics 1B**

**Mark Scheme**

*2009 examination - January series*

*Final*

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation meeting attended by all examiners and is the scheme which was used by them in this examination. The standardisation meeting ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for the standardisation meeting each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed at the meeting and legislated for. If, after this meeting, examiners encounter unusual answers which have not been discussed at the meeting they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available to download from the AQA Website: [www.aqa.org.uk](http://www.aqa.org.uk)

Copyright © 2009 AQA and its licensors. All rights reserved.

#### COPYRIGHT

AQA retains the copyright on all its publications. However, registered centres for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to centres to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

### Key to mark scheme and abbreviations used in marking

M	mark is for method		
m or dM	mark is dependent on one or more M marks and is for method		
A	mark is dependent on M or m marks and is for accuracy		
B	mark is independent of M or m marks and is for method and accuracy		
E	mark is for explanation		
√ or ft or F	follow through from previous incorrect result	MC	mis-copy
CAO	correct answer only	MR	mis-read
CSO	correct solution only	RA	required accuracy
AWFW	anything which falls within	FW	further work
AWRT	anything which rounds to	ISW	ignore subsequent work
ACF	any correct form	FIW	from incorrect work
AG	answer given	BOD	given benefit of doubt
SC	special case	WR	work replaced by candidate
OE	or equivalent	FB	formulae book
A2,1	2 or 1 (or 0) accuracy marks	NOS	not on scheme
-x EE	deduct x marks for each error	G	graph
NMS	no method shown	c	candidate
PI	possibly implied	sf	significant figure(s)
SCA	substantially correct approach	dp	decimal place(s)

### No Method Shown

Where the question specifically requires a particular method to be used, we must usually see evidence of use of this method for any marks to be awarded. However, there are situations in some units where part marks would be appropriate, particularly when similar techniques are involved. Your Principal Examiner will alert you to these and details will be provided on the mark scheme.

Where the answer can be reasonably obtained without showing working and it is very unlikely that the correct answer can be obtained by using an incorrect method, we must award **full marks**. However, the obvious penalty to candidates showing no working is that incorrect answers, however close, earn **no marks**.

Where a question asks the candidate to state or write down a result, no method need be shown for full marks.

Where the permitted calculator has functions which reasonably allow the solution of the question directly, the correct answer without working earns **full marks**, unless it is given to less than the degree of accuracy accepted in the mark scheme, when it gains **no marks**.

**Otherwise we require evidence of a correct method for any marks to be awarded.**



## MM1B (cont)

Q	Solution	Marks	Total	Comments
3(a)	$4a = 4g \sin 40^\circ$	M1	3	M1: Resolving and application of Newton's second law. Allow $\cos 40^\circ$ . A1: Correct expression. A1: Correct result from correct working. Must see 6.30 not 6.3. Just seeing $g \sin 40^\circ = 6.30 \text{ ms}^{-2}$ scores full marks. Use of $g = 9.81$ gives 6.31, M1A1A0, but don't penalise again on the same script.
	$a = g \sin 40^\circ = 6.30 \text{ ms}^{-2}$ <b>AG</b>	A1 A1		
(b)	$0.9 = 0 + \frac{1}{2} \times a \times 0.6^2$	M1	3	M1: Use of a constant acceleration equation to find $a$ , with $s = 0.9$ , $u = 0$ and $t = 0.6$ . A1: Correct equation A1: Correct acceleration
	$a = \frac{0.9 \times 2}{0.6^2} = 5 \text{ ms}^{-2}$	A1 A1		
	<b>ALT Method</b> $0.9 = \frac{1}{2} (0 + v) \times 0.6$ $v = 3$ $3 = 0 + 0.6a$	(M1A1)		
	$a = 5 \text{ ms}^{-2}$	(A1)		
(c)	The acceleration is reduced because of air resistance or the fact that there is friction.	B1	1	No marks at this stage. M1: Constant acceleration equation with $u = 0$ and $t = 0.6$ . A1: Correct equation A1: Correct acceleration. B1: Must mention air resistance/resistive forces or friction. Do not allow air friction.
<b>Total</b>			<b>7</b>	

## MM1B (cont)

Q	Solution	Marks	Total	Comments
4(a)	Peg is smooth	B1	1	B1: Correct assumption
(b)	String is light	B1		B1: First correct assumption
	String is inextensible or inelastic	B1	2	B1: Second correct assumption
	Tension is the same throughout the string			Note: Ignore any additional assumptions.
(c)	$11g - T = 11a$	M1		M1: Equation of motion for A, containing T, 11g or 107.8 and 11a.
	$T - 9g = 9a$	A1		A1: Correct equation
		M1		M1: Equation of motion for B containing T, 9g or 88.2 and 9a.
		A1		A1: Correct equation
	$2g = 20a$			
	$a = 0.98 \text{ ms}^{-2}$ <b>AG</b>	A1	5	A1: Correct acceleration from correct working.
				Note: Do not penalise candidates who consistently use signs in the opposite direction throughout, provided they give their final answer as 0.98. If final answer is - 0.98 don't award final A1 mark.
				<b>Special Case:</b> Whole String Method $2g = 20a$ and $a = 2g / 20 = 0.98$ OE M1A1A1
				Use of $g = 9.81$ gives 0.981. If this is the first time award M1A1M1A1A0, but don't penalise again on the same script.

## MM1B (cont)

Q	Solution	Marks	Total	Comments
4(d)(i)	$v = 0 + 0.98 \times 0.5 = 0.49 \text{ ms}^{-1}$	M1 A1	2	M1: Use of constant acceleration equation to find $v$ with $u = 0$ , $a = 0.98$ and $t = 0.5$ . A1: Correct $v$
(d)(ii)	$s = 0 + \frac{1}{2} \times 0.98 \times 0.5^2 = 0.1225 \text{ m}$  <b>OR</b> $0.49^2 = 0^2 + 2 \times 0.98s$ $s = \frac{0.49^2}{2 \times 0.98} = 0.1225$  $d = 2 \times 0.1225$ $= 0.245 \text{ m}$	M1 A1  (M1) (A1)  M1 A1	4	M1: Finding distance travelled by each particle with $u = 0$ , $a = 0.98$ and $t = 0.5$ . A1: Correct distance. Accept 0.122 or 0.123  M1: Finding distance travelled by each particle with $u = 0$ , $a = 0.98$ and their $v$ . A1: Correct distance. Accept 0.122 or 0.123  M1: Doubling distance or use of $d/2$ in their original equation. A1: Correct final distance. Allow 0.244 or 0.246. (Use of $0.5 \times 0.49 = 0.245$ scores zero unless justified)
				<b>If candidates calculate the distance first award marks as above (see (d)(i)) or:</b> M1: Use of constant acceleration equation to find $v$ with $u = 0$ , $a = 0.98$ and $s = 0.1225$ . A1: Correct $v$ <b>Note: If parts (i) and (ii) are not separated or clearly labelled still award marks for both parts if justified.</b>
	<b>Total</b>		<b>14</b>	

## MM1B (cont)

Q	Solution	Marks	Total	Comments
5(a)	<p>OR</p>	B1	1	<p>B1: Diagram with four forces showing arrow heads and labelled.  Allow <math>mg</math> or <math>8g</math>.  Allow <math>T</math> or <math>40</math> or other reasonable notation.  Allow <math>\mu R</math>.  Direction of friction must be to the left.</p> <p>Any components must be shown in a different style.</p>
(b)	$8g + 40\sin 30^\circ (= R)$  $(R =)98.4 \text{ N AG}$	M1  A1		<p>M1: Expression for normal reaction, with <math>mg</math> or <math>8g</math> and <math>40\sin 30^\circ</math> or <math>40\cos 30^\circ</math>.  Allow incorrect signs.  A1: Correct expression with correct signs.</p>
(c)	$F = 40\cos 30^\circ = 34.6 \text{ N}$	M1  A1	3	<p>A1: Correct value from correct working.  Use of <math>g = 9.81</math> gives <math>98.5 \text{ N}</math>. Do not penalise if you have already done so earlier in the script. Otherwise penalise by 1 mark.</p>
(d)	$40\cos 30^\circ \leq \mu \times 98.4$  $\mu \geq \frac{40\cos 30^\circ}{98.4}$ $\mu \geq 0.352$	M1  A1F  A1F		<p>M1: Use of <math>F \leq \mu R</math> (or <math>F = \mu R</math>). Must use <math>R = 98.4</math> and a positive value for <math>F</math>.  A1F: Correct inequality or equation  Allow use of <math>F = \mu R</math> throughout.</p>
	<b>Total</b>		<b>9</b>	<p>A1F: Correct minimum value. For follow through must use <math>R = 98.4</math> and their value for <math>F</math> from part (c). For example use of <math>\sin 30^\circ</math> in part (c) gives <math>0.203</math>.</p>



## MM1B (cont)

Q	Solution	Marks	Total	Comments
6(a)	Resultant = $(6\mathbf{i} - 3\mathbf{j}) + (3\mathbf{i} + 15\mathbf{j})$ = $9\mathbf{i} + 12\mathbf{j}$	M1 A1	2	M1: Summing the two vectors A1: Correct resultant
(b)	Magnitude = $\sqrt{9^2 + 12^2}$ = 15 N	M1 A1F	2	M1: Finding magnitude with an addition sign. A1F: Correct magnitude based on their answer to part (a).
(c)	$1.5m = 9$ $2m = 12$ $m = 6 \text{ kg}$ or $m = 6 \text{ kg}$	M1 A1F	2	M1: Applying Newton's second law to one or both of the components. A1F: Correct mass, follow through their answer to part (a). Do not award this mark if vector division with 2 components has been used, eg $\frac{9\mathbf{i} + 12\mathbf{j}}{1.5\mathbf{i} + 2\mathbf{j}} = 6$ or $6\mathbf{i} + 6\mathbf{j}$ etc without a correct previous statement gives M0A0
(d)(i)	$\mathbf{r} = \frac{1}{2}(1.5\mathbf{i} + 2\mathbf{j})t^2$	M1 A1	2	M1: Using a constant acceleration equation to find the position vector with $\mathbf{u} = 0\mathbf{i} + 0\mathbf{j}$ A1: Correct position vector.
(d)(ii)	$\mathbf{r} = \frac{1}{2}(1.5\mathbf{i} + 2\mathbf{j}) \times 2^2 = 3\mathbf{i} + 4\mathbf{j}$ $d = \sqrt{(3)^2 + (4)^2}$ = $\sqrt{25} = 5$	M1 A1	2	M1: Finding the position vector when $t = 2$ . $(\mathbf{r} = (1.5\mathbf{i} + 2\mathbf{j}) \times 2 = 3\mathbf{i} + 4\mathbf{j})$ scores M0 unless it is clear how the 2 was obtained, possibly by a correct formula in (d) (i) A1: Correct distance
	<b>Total</b>		<b>10</b>	



## MM1B (cont)

Q	Solution	Marks	Total	Comments
7(b)	$\frac{\sin \theta}{2} = \frac{\sin 45^\circ}{3.855}$	M1		M1: Use of sine rule, with 2, 3.855 or 3.85 or awrt 3.85 and any angle.
	$\theta = 21.5^\circ$	A1		A1: Correct expression
	Bearing = $270 + 21.5 = 292^\circ$	A1		A1: Correct angle. Awrt $21^\circ$ or $22^\circ$
		A1		A1: Correct bearing. Do not penalise candidates who include decimals. Accept $291^\circ$
	<b>OR</b>			
	$\frac{\sin \theta}{5} = \frac{\sin 45^\circ}{3.855}$	(M1)		M1: Use of sine rule, with 5, 3.855 or 3.85 or awrt 3.85 and any angle.
	$\theta = 113^\circ$	(A1)		A1: Correct expression
		(A1)		A1: Correct angle. Allow awrt $113^\circ$ or $114^\circ$ .
				Also allow awrt $66^\circ$ or $67^\circ$ .
	Bearing = $360 - (113.3 - 45) = 292^\circ$	(A1)		A1: Correct bearing. Do not penalise candidates who include decimals. Accept $291^\circ$
	<b>OR</b>			
	$\tan \theta = \frac{2 \cos 45^\circ}{5 - 2 \cos 45^\circ}$	(M1)		M1: Consideration of perpendicular components using values from part (a).
	$\theta = 21.5^\circ$	(A1)		A1: Correct expression
	(A1)		A1: Correct positive angle. Awrt $21^\circ$ or $22^\circ$	
			Also allow method leading to awrt $68^\circ$ or $69^\circ$	
Bearing = $270 + 21.5 = 292^\circ$	(A1)		A1: Correct bearing. Do not penalise candidates who include decimals. Accept $291^\circ$	
<b>OR</b>				
$\cos \theta = \frac{3.855^2 + 5^2 - 2^2}{2 \times 5 \times 3.855}$	(M1)		M1: Use of cosine rule, with 2, 3.855 or 3.85 or awrt 3.85 and 5.	
$\theta = 21.5^\circ$	(A1)		A1: Correct expression	
	(A1)		A1: Correct angle. Awrt $21^\circ$ or $22^\circ$	
Bearing = $270 + 21.5 = 292^\circ$	(A1)	4	A1: Correct bearing. Do not penalise candidates who include decimals. Accept $291^\circ$	
	<b>Total</b>		<b>8</b>	

## MM1B (cont)

Q	Solution	Marks	Total	Comments
8				If candidates have already used $g = 9.81$ do not penalise again on this question.
(a)	$0^2 = (28 \sin 50^\circ)^2 + 2 \times (-9.8)s$ $s = \frac{(28 \sin 50^\circ)^2}{2 \times 9.8} = 23.5 \text{ m}$ <b>OR</b> $0 = 28 \sin 50^\circ - 9.8t$ $t = \frac{28 \sin 50^\circ}{9.8} = 2.1887$ $s = 28 \sin 50^\circ \times 2.1887 - 4.9 \times 2.1887^2 = 23.5$	M1 A1  dM1 A1  (M1) (A1) (dM1) (A1)	4	M1: Equation to find the max height, with $v = 0$ , $u = 28 \sin 50^\circ$ or $u = 28 \cos 50^\circ$ and $-9.8$ or $-g$ . A1: Correct equation dM1: Solving for the height A1: Correct height. Awrt 23.5 Note: If using a memorised formula, either 4 marks if final answer correct, 3 marks if substituted correctly but evaluated incorrectly, otherwise zero.  M1: Equation to find time to the max height, with $v = 0$ , $u = 28 \sin 50^\circ$ or $u = 28 \cos 50^\circ$ and $-9.8$ or $-g$ . A1: Correct time dM1: Finding the height with their time and $u = 28 \sin 50^\circ$ or $u = 28 \cos 50^\circ$ and $-4.9$ or $-g/2$ A1: Correct height. Awrt 23.5

## MM1B (cont)

Q	Solution	Marks	Total	Comments
8(b)	$2 = 28\sin 50^\circ t - 4.9t^2$	M1		M1: Quadratic equation in $t$ with a $\pm 2$ , $u = 28\sin 50^\circ$ or $u = 28\cos 50^\circ$ and $-4.9$ or $-g/2$ .
		A1		A1: Correct terms
		A1		A1: Correct signs for equation
	$0 = 4.9t^2 - 28\sin 50^\circ t + 2$	dM1		dM1: Solving the quadratic equation
	$t = 0.0953$ or $t = 4.282$	A1		A1: Correct larger time selected from two values.
	$t = 4.282 = 4.28$ s (to 3 sf) <b>AG</b>			
	OR	(M1)		M1: Calculation of two times, which sum or differ to give the time of flight.
	$0 = 28\sin 50^\circ - 9.8t$	(A1)		A1: Correct time by equation for zero vertical component of velocity or maximum height.
	$t = \frac{28\sin 50^\circ}{9.8} = 2.1887$			
	OR			
$23.5 = 28\sin 50^\circ t - 4.9t^2$	(dM1)		dM1: Correct expression for time to fall.	
$t = 2.1887$				
$21.5 = 4.9t^2$	(A1)		A1: Correct time.	
$t = \sqrt{\frac{21.5}{4.9}} = 2.0947$				
$2.1887 + 2.0947 = 4.2834 = 4.28$ (to 3sf) <b>AG</b>	(A1)	5	A1: Correct time. Accept 4.29 if their answer rounds to 4.29.	

## MM1B (cont)

Q	Solution	Marks	Total	Comments
8(c)	$v_x = 28 \cos 50^\circ (= 18.00 \text{ ms}^{-1})$ $v_y = 28 \sin 50^\circ - 9.8 \times 4.282 = -20.51 \text{ ms}^{-1}$ $v = \sqrt{18.00^2 + 20.51^2} = 27.3 \text{ ms}^{-1}$	B1 M1 A1 dM1 A1F	5	B1: Horizontal component, need not be evaluated. M1: Equation for vertical component with $28 \sin 50^\circ$ (or $28 \cos 50^\circ$ if $\sin 50^\circ$ used for horizontal component), $-9.8$ and awrt $4.28$ . A1: Correct vertical component. Awrt $\pm 20.5$ dM1: Finding speed with a + sign inside the square root. A1F: Correct speed. Awrt $27.3$ .  Intermediate values can be implied by final answer.
	<b>Total</b>		<b>14</b>	
	<b>TOTAL</b>		<b>75</b>	