

Version



**General Certificate of Education (A-level)
January 2013**

Mathematics

MM2B

(Specification 6360)

Mechanics 2B

Final

Mark Scheme

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all examiners participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for standardisation each examiner analyses a number of students' scripts: alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, examiners encounter unusual answers which have not been raised they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available from: aqa.org.uk

Copyright © 2013 AQA and its licensors. All rights reserved.

Copyright

AQA retains the copyright on all its publications. However, registered schools/colleges for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

Key to mark scheme abbreviations

M	mark is for method
m or dM	mark is dependent on one or more M marks and is for method
A	mark is dependent on M or m marks and is for accuracy
B	mark is independent of M or m marks and is for method and accuracy
E	mark is for explanation
✓ or ft or F	follow through from previous incorrect result
CAO	correct answer only
CSO	correct solution only
AWFW	anything which falls within
AWRT	anything which rounds to
ACF	any correct form
AG	answer given
SC	special case
OE	or equivalent
A2,1	2 or 1 (or 0) accuracy marks
-x EE	deduct x marks for each error
NMS	no method shown
PI	possibly implied
SCA	substantially correct approach
c	candidate
sf	significant figure(s)
dp	decimal place(s)

No Method Shown

Where the question specifically requires a particular method to be used, we must usually see evidence of use of this method for any marks to be awarded.

Where the answer can be reasonably obtained without showing working and it is very unlikely that the correct answer can be obtained by using an incorrect method, we must award **full marks**. However, the obvious penalty to candidates showing no working is that incorrect answers, however close, earn **no marks**.

Where a question asks the candidate to state or write down a result, no method need be shown for full marks.

Where the permitted calculator has functions which reasonably allow the solution of the question directly, the correct answer without working earns **full marks**, unless it is given to less than the degree of accuracy accepted in the mark scheme, when it gains **no marks**.

Otherwise we require evidence of a correct method for any marks to be awarded.


Q	Solution	Marks	Total	Comments	
1(a)	$KE = \frac{1}{2} \times 0.16 \times 11^2$ $= 9.68 \text{ J}$	M1	2		
		A1			
	(b)	Change in PE: $mgh = 0.16 \times 9.8 \times 5$ $= 7.84 \text{ J}$	M1		2
			A1		
(c)(i)	KE when reached point B $= 9.68 - 7.84 \text{ J}$ $= 1.84 \text{ J}$	M1	2	'(a)' - '(b)' cao	
		A1			
(ii)	Speed of ball is $\sqrt{\frac{1.84}{\frac{1}{2} \times 0.16}}$ $= 4.7958 \text{ m s}^{-1}$ $= 4.80 \text{ m s}^{-1}$	M1	2	If added in (c)(i) 0 marks for (c)(i) 14.8 M1A1 for (c)(ii)	
Total			8		
2(a)	$\mathbf{a} = \frac{d\mathbf{v}}{dt}$ $= -4\pi \sin\left(\frac{\pi}{3}t\right)\mathbf{i} - 18t\mathbf{j}$	M1	2	M1 for either term correct Accept $-12 \times \frac{\pi}{3} \sin\left(\frac{\pi}{3}t\right)\mathbf{i} - 18t\mathbf{j}$ condone no i in (a)	
		A1			
(b)(i)	Using $\mathbf{F} = m\mathbf{a}$: $\mathbf{F} = 4 \times \left[-4\pi \sin\left(\frac{\pi}{3}t\right)\mathbf{i} - 18t\mathbf{j}\right]$ $\mathbf{F} = -16\pi \sin\left(\frac{\pi}{3}t\right)\mathbf{i} - 72t\mathbf{j}$	M1	2	Or either term correct	
		A1			
(ii)	When $t = 3$, $\mathbf{F} = 4 \times [-4\pi \sin(\pi)\mathbf{i} - 54\mathbf{j}]$ $= -216\mathbf{j}$ Magnitude is 216	B1 B1ft	2	ft finding magnitude of their F	
(c)	$\mathbf{r} = \int \mathbf{v} dt$ $= \frac{36}{\pi} \sin\left(\frac{\pi}{3}t\right)\mathbf{i} - 3t^3\mathbf{j} + \mathbf{c}$ When $t = 3$, $\mathbf{r} = 4\mathbf{i} - 2\mathbf{j}$ $\rightarrow -81\mathbf{j} + \mathbf{c} = 4\mathbf{i} - 2\mathbf{j}$ $\mathbf{c} = 4\mathbf{i} + 79\mathbf{j}$ $\mathbf{r} = \left\{ \frac{36}{\pi} \sin\left(\frac{\pi}{3}t\right) + 4 \right\} \mathbf{i} + \{79 - 3t^3\} \mathbf{j}$	M1	5	either term correct No need for c (otherwise cao) Condone $\frac{12}{\left(\frac{\pi}{3}\right)}$	
		A1			
		M1			
		A1			
Total			11		

Q	Solution	Marks	Total	Comments
3	Force acting against gravity is $mg\sin\theta$ Force acting against gravity and resistance is $mg\sin\theta + 8000$ $= 1500 \times g \times \sin\theta + 8000$ $= 8588 \text{ N or } 8590 \text{ N}$ Using power = force \times velocity $= 8588 \times 22$ $= 188\,936 \text{ W}$ $= 189 \text{ kW}$	M1 A1 M1 dep A1 A1	5	Condone $\cos\theta$ or -1 for M marks Accept 188.9 or 188
Total			5	
4(a)	Symmetry	E1	1	
(b)	Moments about AB : $300\sigma \cdot 15 + 100\sigma \cdot 5 + 300\sigma \cdot 15 = 700\sigma \cdot x$ $x = \frac{9500}{700}$ $= \frac{95}{7} \text{ or } 13.6 \text{ cm}$	M1A1 A1	3	(condone lack of σ) M1 needs correct total marks
(c)	Distance from HG is 16.4 cm $\tan\theta = \frac{15}{16.42857}$ $= 0.913043$ $\theta = 42.3974^\circ$ $\theta = 42^\circ$	B1 M1 A1 A1	4	Seeing both 15,16.4 and tan [48° probably B1, M1] NB $\frac{13.6}{15}$ etc $\Rightarrow 42^\circ$ no marks
Total			8	

Q	Solution	Marks	Total	Comments
5(a)	Using $F = ma$: $-4v^{\frac{1}{3}} = 12 \frac{dv}{dt}$ $\therefore \frac{dv}{dt} = -\frac{1}{3}v^{\frac{1}{3}}$ $-3 \int \frac{dv}{v^{\frac{1}{3}}} = \int dt$ $-3 \times \frac{v^{\frac{2}{3}}}{\frac{2}{3}} = t + c$ $-\frac{9}{2}v^{\frac{2}{3}} = t + c$ When $t = 0, v = 8 \Rightarrow c = -18$ $-\frac{9}{2}v^{\frac{2}{3}} = t - 18$ $v^{\frac{2}{3}} = 4 - \frac{2}{9}t$ $v = \left(4 - \frac{2}{9}t\right)^{\frac{3}{2}}$	B1 M1 A1 M1A1 A1	 6	 condone -, 3 incorrect side condone lack of + c
(b)	Particle is at rest when $4 - \frac{2}{9}t = 0$ The value of t is 18	B1	1	
Total			7	
6(a)	Resolve vertically: $T \cos \theta = mg$ $34 \cos \theta = 2 \times 9.8$ $\cos \theta = \frac{19.6}{34}$ $\theta = 54.8^\circ$	M1 A1 A1	 3	M1 for $T \cos \theta$ or $T \sin \theta$ and mg
(b)	Resolve horizontally for particle: $\frac{mv^2}{r} = T \sin \theta$ $v^2 = \frac{34 \sin 54.8 \times 0.8}{2}$ $v^2 = 11.113$ Speed is 3.33 m s^{-1}	M1 A1 ft from (a) A1	 3	M1 for $T \cos \theta$ or $T \sin \theta$ Accept 3.34
(c)	Time taken is $2\pi r / v$ $= 1.51 \text{ sec}$	M1 A1ft	 2	Or find ω and use $\frac{2\pi}{\omega}$
Total			8	

Q	Solution	Marks	Total	Comments
7(a)	Using conservation of energy: $\frac{1}{2}mv^2 = \frac{1}{2}mu^2 - mgh$	M1	4	for 3 terms, 2 KE and 1 PE
	$\frac{1}{2} \times 3 \times v^2 = \frac{1}{2} \times 3 \times 4^2 - 3 \times g \times 1.2(1 - \cos 25)$	M1 A1		M1A1 for finding h [M1 for $1.2(1 - \cos 25$ or $\sin 25)$]
	$v^2 = 4^2 - 2.4 \times g(1 - \cos 25)$			
	$v^2 = 16 - 2.2036$ $v = 3.71 \text{ms}^{-1}$	A1		Accept 3.7, 3.70, 3.72
(b)	Resolving radially: $T = mg \cos 25 + \frac{mv^2}{a}$	M1A1	3	M1 accept $\cos 25$ or $\sin 25$, + or - sign and $\neq 2$
	$= 26.645 + 34.491$ $= 61.1 \text{ N}$	A1		A1 fully correct and substituted Accept 61.0 or 61
	Total		7	

Q	Solution	Marks	Total	Comments
8(a)	Work done = $\int_0^e \frac{\lambda x}{l} dx$	M1	3	SC1 $\int_0^e \frac{\lambda e}{l} de$
	= $\left[\frac{\lambda x^2}{2l} \right]_0^e$	A1		SC1 $\int \frac{\lambda x}{l} dx$ with no limits
	= $\frac{\lambda e^2}{2l}$	A1		
(b)(i)	Using $T = \frac{\lambda x}{l}$:			
	$5g = \frac{392x}{1.6}$ $x = \frac{5g \times 1.6}{392}$ = 0.2 Extension is 0.2 m	M1 A1	2	
(ii)	When extension is 0.6 m, $EPE = \frac{\lambda x^2}{2l}$	B1	3	B1 for 0.6
	= $\frac{392 \times (0.6)^2}{2 \times 1.6}$	M1		
	= 44.1 J	A1		
(iii)	Let y metres be distance particle is above A.			
	C of energy, when particle has speed 0.8 m s ⁻¹ , gives			
	$5 \times g \times y + \frac{392 \times (0.6 - y)^2}{2 \times 1.6} + \frac{1}{2} \times 5 \times 0.8^2$	M1A1		M1 4 terms, 2 correct M1A1 4 terms, 3 correct M1A2 4 terms correct Ft answer to (b)(ii)
	= $\frac{392 \times (0.6)^2}{2 \times 1.6}$	A1F		
	$49y + 122.5(0.6 - y)^2 + 1.6 = 122.5 \times 0.6^2$			
	$49y - 147y + 122.5y^2 + 1.6 = 0$			
	$122.5y^2 - 98y + 1.6 = 0$			
	$y = \frac{98 \pm \sqrt{98^2 - 4 \times 122.5 \times 1.6}}{2 \times 122.5}$			
	$y = \frac{98 \pm 93.9148}{245}$			
	= 0.016674 and 0.7833	A1		if x used instead of 0.6 - y, A1 here for x = 0.5833...
Speed first becomes 0.8 when y = 0.0167	E1	5		
	Total		13	

Q	Solution	Marks	Total	Comments
9(a)	Smooth, hence reaction is perpendicular to possible movement	E1	1	
(b)				
(c)	<p>Resolving along the rod:</p> $S \cos \theta = mg \sin \theta$ <p>Moment about C: $S 2a \cos \theta \cdot \sin \theta$</p> $= mg(2a \cos \theta - \frac{1}{2}l) \cos \theta$ $4a \cdot S \sin \theta = mg(4a \cos \theta - l)$ <p>Dividing: $4a \tan \theta = \frac{4a \cos \theta - l}{\sin \theta}$</p> $l = 4a \cos \theta - 4a \sin \theta \tan \theta$ $l = \frac{4a \cos 2\theta}{\cos \theta}$	<p>B2</p> <p>M1A1</p> <p>M1A1</p> <p>A1</p>	<p>2</p> <p>5</p>	<p>B1 for 2 forces correct</p> <p>Or geometrically:</p> <p>three forces act through a point B1</p> <p>M1 is for 2 or 3 terms; 1 term correct (could be horizontal force at C used) [forces act through point D]</p> $AD \cos 2\theta = \frac{l}{2} \cos \theta \quad \text{M1A1}$ $AD \cos \theta = 2a \cos \theta \quad \text{M1}$ $l = \frac{4a \cos 2\theta}{\cos \theta} \quad \text{A1}$

Q	Solution	Marks	Total	Comments
9 cont	<p>or</p> <p>Resolving perpendicular to S: $R \cos \theta = mg \cos 2\theta$</p> <p>Moments about A: $R 2a \cos \theta = mg \frac{1}{2} l \cos \theta$</p> <p>$4a R = mgl$ $4amg \cos 2\theta = mgl \cos \theta$ $l = \frac{4a \cos 2\theta}{\cos \theta}$</p> <p>or</p> <p>Resolving horizontally: $R \sin \theta = S \cos 2\theta$</p> <p>Resolving vertically: $R \cos \theta + S \sin 2\theta = mg$</p> <p>Moments about A: $R 2a \cos \theta = mg \frac{1}{2} l \cos \theta$</p> <p>$4a R = mgl$ $R \cos \theta + R \frac{\sin \theta}{\cos 2\theta} \sin 2\theta = 4a \frac{R}{l}$ $l = \frac{4a \cos 2\theta}{\cos \theta}$</p>	<p>(M1A1)</p> <p>(M1A1)</p> <p>(A1)</p> <p>(M1A1)</p> <p>(A1)</p>		<p>Both attempted for M1 Both correct for A1</p>
	Total		8	
	TOTAL		75	