

# EDEXCEL FOUNDATION

Stewart House 32 Russell Square London WC1B 5DN

January 2002

Advanced Supplementary/Advanced Level

General Certificate of Education

Subject MECHANICS 6679

\* indicates printed answer

Paper No. M3

Question number	Scheme	Marks
1.	$0.2a = \frac{5}{x+1}$ $0.2v \frac{dv}{dx} = \frac{5}{x+1}$ $\int v dv = \int \frac{25}{x+1} dx$ $\frac{1}{2}v^2 = 25 \ln(x+1) (+C)$ $x=0, v=5 \Rightarrow C = 12.5$ $\frac{25}{2} = 25 \ln(x+1) + 12.5$ $x = 53.6 \text{ (3SF)}$	M1 → M1 → M1 A1 A1 A1 M1 A1 (8)
2. (a)	PE Loss = $0.5g(2+x)$ ; EPE <sub>at C</sub> = $19.6x^2$ $0.5g(2+x) = \frac{19.6x^2}{4}$ $5(x^2 - x - 2) = 0$ Solving $AC = 4m$	B1; B1 M1 A1 M1 A1 ✓ (6)
(b)	$T_c = \frac{19.6 \times 2}{2} = 19.6$ $19.6 - 0.5g = 0.5a$ $a = 29.4 \text{ ms}^{-2}$	B1 ✓ M1 A1 (3) (9)
3. (a)	Line of action of weight must pass through C which is not above centre of rod (or equivalent)	B1 (1)
(b)	<u>Method A:</u> R (along AC) : $T_1 = 2mg \sin\alpha = \frac{6mg}{5}$ R (along BC) : $T_2 = 2mg \cos\alpha = \frac{8mg}{5}$ [ Equiv. to moments about A, B respectively ]	M1 M1 A1 M1 A1
OR	<u>Method B:</u> R(G), $T_1 \sin\alpha + T_2 \cos\alpha = 2mg$ $\leftarrow T_1 \cos\alpha = T_2 \sin\alpha$ Solving to find $T_1$ or $T_2$ $T_1 = \frac{6mg}{5}$ ; $T_2 = \frac{8mg}{5}$	→ M1 → M1 M1 A1; A1 (5)
(c)	$\frac{8mg}{5} = k \frac{BC - a}{a}$ $BC = 2a \sin\alpha$ $k = 8$	M1 A1 B1 A1 (4) (10)

# EDEXCEL FOUNDATION

Stewart House 32 Russell Square London WC1B 5DN




January 2002

Advanced Supplementary/Advanced Level

General Certificate of Education

Subject MECHANICS 6679

Paper No. M3

Question number	Scheme	Marks
4.(a)	$\int_0^r (\pi) y^2 \times dx = \frac{\pi}{2} \int_0^r (\pi) y^2 dx$ $\int_0^r rx^2 dx = \frac{\pi}{2} \int_0^r rx dx$ $[(r)x^3]_0^r = \frac{\pi}{2} [(rx)^2]_0^r$ $\bar{x} = \frac{2r/3}{*}$	<span style="border: 1px solid black; padding: 2px;">M1 A1</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">A1 A1</span> <span style="border: 1px solid black; padding: 2px;">A1</span> (6)
(b)	 <p>Vertical thro' CM and lowest point of plane face  <math>\tan \alpha = r/h</math>  <math>\alpha = 72^\circ</math> (nearest degree)</p>	<span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">M1 A1</span> <span style="border: 1px solid black; padding: 2px;">A1</span> (4)
5.	 <p> <math>R(↑)</math>, <math>R \cos 25^\circ - F \sin 25^\circ = mg</math>  <math>R(←)</math>, <math>R \sin 25^\circ + F \cos 25^\circ = \frac{mv^2}{R}</math>  <math>F = 0.6R</math> used          Eliminating R          Solving for v  <math>v = 24.1 \text{ ms}^{-1}, 24 \text{ ms}^{-1}</math> </p>	<span style="border: 1px solid black; padding: 2px;">M1 A2</span> <span style="border: 1px solid black; padding: 2px;">M1 A2</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">A1</span> (10)
6.(a)	 <p>If S.H.M., <math>a = \omega^2 r</math>          Using <math>v^2 = \omega^2 (a^2 - x^2)</math>  <math>0.27 = \omega^2 (1.2^2 - 0.6^2)</math> or <math>0.2 = \omega^2 (1.2^2 - 0.8^2)</math>          Solve for <math>\omega</math> (<math>= 0.5</math>) and use in other eqn          Shown to be correct</p>	<span style="border: 1px solid black; padding: 2px;">B1</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">A1</span> <span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">A1 c.s.o.</span> (5)
(b)	$v = \omega r = 1.2 \times 0.5 = 0.6 *$	<span style="border: 1px solid black; padding: 2px;">M1 A1</span> (2)
(c)	$ x  = \omega^2 \times 0.6 = 0.15 \text{ m}^{-2}$	<span style="border: 1px solid black; padding: 2px;">M1 A1 V</span> (2)
(d)	$0.6 = a \sin \omega t$ or $0.8 = a \sin \omega t$ $t = \frac{1}{\omega} \left( \sin^{-1} \frac{0.8}{a} - \sin^{-1} \frac{0.6}{a} \right)$ $= 0.412 \text{ s}$ (3SF)	<span style="border: 1px solid black; padding: 2px;">M1</span> <span style="border: 1px solid black; padding: 2px;">M1 A1 V</span> <span style="border: 1px solid black; padding: 2px;">A1</span> (4)

# EDEXCEL FOUNDATION

Stewart House 32 Russell Square London WC1B 5DN

January 2002

Advanced Supplementary/Advanced Level

General Certificate of Education

Subject MECHANICS 6679

Paper No. M3

Question number	Scheme	Marks
7. (a)	$\frac{1}{2}m \frac{7ag}{2} - \frac{1}{2}mv^2 = mga$ $(\leftrightarrow), R = \frac{mv^2}{a} = \frac{3mg}{2}$	M1 A1 M1 A1 (4)
(b)	$\frac{1}{2}m \frac{7ag}{2} - \frac{1}{2}mv^2 = mga(1 + \cos\theta)$ $(\leftrightarrow), mg\cos\theta = \frac{mv^2}{a}$ Eliminating $v^2$ Solving to give $\sin\theta = k$ , $\underline{\theta = 60^\circ}$ *	M1 A1 M1 A1 M1 M1 A1 (7)
(c)	$v \cos 60^\circ t = ag \sin 60^\circ$ $v^2 = ag \cos 60^\circ$ Making $t$ explicit $t = \sqrt{\frac{6a}{5}}$	M1 B1 M1 A1 (4) 15