

# Mark Scheme (Results)

Summer 2015

Pearson Edexcel GCE in Mechanics 3 (6679/01)

## Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at [www.edexcel.com](http://www.edexcel.com) or [www.btec.co.uk](http://www.btec.co.uk). Alternatively, you can get in touch with us using the details on our contact us page at [www.edexcel.com/contactus](http://www.edexcel.com/contactus).

## Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: [www.pearson.com/uk](http://www.pearson.com/uk)

Summer 2015

Publications Code UA042154

All the material in this publication is copyright

© Pearson Education Ltd 2015



## General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

## PEARSON EDEXCEL GCE MATHEMATICS

### General Instructions for Marking

1. The total number of marks for the paper is 75.
2. The Edexcel Mathematics mark schemes use the following types of marks:

#### 'M' marks

These are marks given for a correct method or an attempt at a correct method. In Mechanics they are usually awarded for the application of some mechanical principle to produce an equation.

e.g. resolving in a particular direction, taking moments about a point, applying a suvat equation, applying the conservation of momentum principle etc.

The following criteria are usually applied to the equation.

To earn the M mark, the equation

(i) should have the correct number of terms

(ii) be dimensionally correct i.e. all the terms need to be dimensionally correct

e.g. in a moments equation, every term must be a 'force x distance' term or 'mass x distance', if we allow them to cancel 'g' s.

For a resolution, all terms that need to be resolved (multiplied by sin or cos) must be resolved to earn the M mark.

M marks are sometimes dependent (DM) on previous M marks having been earned.

e.g. when two simultaneous equations have been set up by, for example, resolving in two directions and there is then an M mark for solving the equations to find a particular quantity – this M mark is often dependent on the two previous M marks having been earned.

#### 'A' marks

These are dependent accuracy (or sometimes answer) marks and can only be awarded if the previous M mark has been earned. E.g. M0 A1 is impossible.

#### 'B' marks

These are independent accuracy marks where there is no method (e.g. often given for a comment or for a graph)

A few of the A and B marks may be f.t. – follow through – marks.

### 3. General Abbreviations

These are some of the traditional marking abbreviations that will appear in the mark schemes.

- bod – benefit of doubt
  - ft – follow through
  - the symbol  $\surd$  will be used for correct ft
  - cao – correct answer only
  - cso - correct solution only. There must be no errors in this part of the question to obtain this mark
  - isw – ignore subsequent working
  - awrt – answers which round to
  - SC: special case
  - oe – or equivalent (and appropriate)
  - dep – dependent
  - indep – independent
  - dp decimal places
  - sf significant figures
  - \* The answer is printed on the paper
  - The second mark is dependent on gaining the first mark
4. All A marks are 'correct answer only' (cao.), unless shown, for example, as A1 ft to indicate that previous wrong working is to be followed through. After a misread however, the subsequent A marks affected are treated as A ft, but manifestly absurd answers should never be awarded A marks.
- 5 For misreading which does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, in that part of the question affected.
- 6 If a candidate makes more than one attempt at any question:
- a. If all but one attempt is crossed out, mark the attempt which is NOT crossed out.
  - b. If either all attempts are crossed out or none are crossed out, mark all the attempts and score the highest single attempt.
- 7 Ignore wrong working or incorrect statements following a correct answer.

## General Principles for Mechanics Marking

*(But note that specific mark schemes may sometimes override these general principles)*

- Rules for M marks: correct no. of terms; dimensionally correct; all terms that need resolving (i.e. multiplied by cos or sin) are resolved.
- Omission or extra  $g$  in a resolution is an accuracy error not method error.
- Omission of mass from a resolution is a method error.
- Omission of a length from a moments equation is a method error.
- Omission of units or incorrect units is not (usually) counted as an accuracy error.
- dM indicates a dependent method mark i.e. one that can only be awarded if a previous specified method mark has been awarded.
- Any numerical answer which comes from use of  $g = 9.8$  should be given to 2 or 3 SF.
- Use of  $g = 9.81$  should be penalised once per (complete) question.

N.B. Over-accuracy or under-accuracy of correct answers should only be penalised *once* per complete question. However, premature approximation should be penalised every time it occurs.

- Marks must be entered in the same order as they appear on the mark scheme.
- In all cases, if the candidate clearly labels their working under a particular part of a question i.e. (a) or (b) or (c),.....then that working can only score marks for that part of the question.
- Accept column vectors in all cases.
- Misreads – if a misread does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, bearing in mind that after a misread, the subsequent A marks affected are treated as A ft
- Mechanics Abbreviations

M(A) Taking moments about A.

N2L Newton's Second Law (Equation of Motion)

NEL Newton's Experimental Law (Newton's Law of Impact)

HL Hooke's Law

SHM Simple harmonic motion

PCLM Principle of conservation of linear momentum

RHS, LHS Right hand side, left hand side.

**June 2015**  
**6679 M3**  
**Mark Scheme**

Question Number	Scheme	Marks
<b>1</b>		
<b>(a)</b>	$0.5g = T = \frac{\lambda \times 0.3}{1.2}$ $\lambda = 2g = 19.6$	M1A1  A1 (3)
<b>(b)</b>	$\frac{1}{2} \times \frac{19.6 \times x^2}{1.2} - \frac{1}{2} \times \frac{19.6 \times 0.4^2}{1.2} = 0.5 \times g \times (x + 0.4)$ $5x^2 - 3x - 2 = 0$ <p style="text-align: center;">(5x + 2)(x - 1) = 0      or use of diff of 2 squares to obtain and then solve a linear equation</p> <p style="text-align: center;">x = 1 (x = -0.4 need not be seen)</p> $AC = 2.2 \text{ m}$	M1A1ftA1          A1 (4) [7]

**(a) M1** Use Hooke's law to obtain the tension and equate to the weight

**A1** Correct equation

**A1** Solve to get  $\lambda = 19.6$  Accept 20 or 2g

**(b) M1** Attempt an energy equation with the difference of 2 EPE terms and a loss of GPE

EPE formula must be of the form  $k \frac{\lambda x^2}{l}$

**A1ft** EPE terms correct follow through their  $\lambda$

**A1** GPE term correct, including all signs in the equation correct If x used for EPE and GPE A0 here

**A1** Correct length AC If  $\lambda = 20$  is used, this is p.a. and so scores A0

**ALT:** Find BC first:  $\frac{1}{2} \times \frac{19.6 \times (h - 0.4)^2}{1.2} - \frac{1}{2} \times \frac{19.6 \times 0.4^2}{1.2} = 0.5gh$       M1A1A1

$BC = 1.4$   $AC = 2.2$       A1

Methods depending on SHM must prove SHM first, but if correct answer only is given award B1 (M1 on e-PEN)

By integration: Integrating and substituting yields an equation equivalent to the one shown - mark from here      M1A1A1ft -1 each error ft on  $\lambda$



Question Number	Scheme	Marks
2 (a)	$\text{Vol} = \pi \int_0^1 4e^{2x} dx$ $= \pi [2e^{2x}]_0^1$ $= 2\pi(e^2 - 1) \quad *$	M1 DM1A1 A1cso (4)
(b)	$\pi \int_0^1 4xe^{2x} dx$ $= 4\pi \left\{ \left[ x \times \frac{1}{2} e^{2x} \right]_0^1 - \int_0^1 \frac{1}{2} e^{2x} dx \right\}$ $= 4\pi \left[ \frac{1}{2} e^2 - 0 \right] - 4\pi \left[ \frac{1}{4} e^{2x} \right]_0^1$ $= \pi(e^2 + 1)$ $x \text{ coord} = \frac{\pi(e^2 + 1)}{2\pi(e^2 - 1)}, = \frac{e^2 + 1}{2(e^2 - 1)} \quad \text{oe}$	M1 DM1 A1 A1 M1A1 (6) [10]

(a) **M1** Using  $\pi \int y^2 dx$  with the equation of the curve, no limits needed

**DM1** Integrating their expression for the volume

**A1** Correct integration inc limits now

**A1** Substituting the limits to obtain the GIVEN answer

(b) **M1** Using  $(\pi) \int xy^2 dx$  with the equation of the curve, no limits needed,  $\pi$  can be omitted

**DM1** Attempting to use integration by parts; allow  $\pm$  between the two parts. No limits needed

**A1** Correct integration, including limits; no substitution needed for this mark

**A1** Correct after limits substituted

**M1** Use of  $\frac{\pi \int xy^2 dx}{\pi \int y^2 dx}$  with their  $\pi \int xy^2 dx$ .  $\pi$  must be seen in both numerator and

denominator or in neither. This mark is not dependent on the previous M marks

**A1cao** Correct answer.

Question Number	Scheme	Marks
<b>3(a)</b>	R(↑) $T_A \cos 30 = mg + T_B \cos 30$	M1A1
	NL2 $T_A \cos 60 + T_B \cos 60 = mr\omega^2$	M1A1
	$= m \times 2l \cos 60 \omega^2$ or $ml\omega^2$	A1
	$T_A + T_B = 2ml\omega^2$	
	$T_A - T_B = \frac{2mg}{\sqrt{3}}$	
<b>(i)</b>	$T_A = \frac{m}{3}(3l\omega^2 + g\sqrt{3})$ oe	DM1A1
<b>(ii)</b>	$T_B = \frac{m}{3}(3l\omega^2 - g\sqrt{3})$ oe	A1 (8)
<b>(b)</b>	$T_B \geq 0 \Rightarrow 3l\omega^2 \geq g\sqrt{3}$	M1
	$\omega^2 \geq \frac{g\sqrt{3}}{3l}$ *	A1cso (2)
		[10]

- (a) M1** Resolving vertically  
**A1** Correct equation  
**M1** NL2 along radius, acceleration in either form  
**A1** LHS correct  
**A1** Correct radius substituted and accel in  $r\omega^2$ . Can be awarded later by implication if work implies correct radius used.  
**DM1** Solving the two equations to obtain an expression for either tension. Dependent on both previous M marks  
**A1** Tension in AP correct – simplified to two terms  
**A1** Tension in BP correct – simplified to two terms
- (b) M1** Using their tension in  $BP \geq 0$  **must be**  $\geq$  for this mark  
**A1cso** Obtaining the GIVEN answer. Only error allowed is the expression for the tension in AP

Question Number	Scheme	Marks												
<b>4(a)</b>	$\frac{63000}{kt^2} = 900 \frac{dv}{dt}$	M1												
	$-\frac{70}{kt} (+c) = v$	DM1A1ft												
	$t = 1 \quad v = 0 \Rightarrow c = \frac{70}{k}$	M1(either)												
	$t = 4 \quad v = 10.5 \Rightarrow -\frac{70}{4k} + c = 10.5$	A1(both)												
	$-\frac{70}{4k} + \frac{70}{k} = 10.5$													
	$k = 5, \quad c = 14$	A1												
	$v = 14 - \frac{14}{t} \quad *$	A1 cso (7)												
<b>(b)</b>	$\frac{14}{t} > 0 \Rightarrow v < 14$ or $v$ never reaches 14	B1 (1)												
<b>(c)</b>	$7 = 14 - \frac{14}{t}$													
	$\frac{14}{t} = 7 \quad t = 2$	B1												
	<table border="0"> <tr> <td><math>t</math></td> <td>1</td> <td>1.25</td> <td>1.5</td> <td>1.75</td> <td>(2)</td> </tr> <tr> <td><math>v</math></td> <td>0</td> <td>2.8</td> <td>4.666..</td> <td>6</td> <td>7</td> </tr> </table>	$t$	1	1.25	1.5	1.75	(2)	$v$	0	2.8	4.666..	6	7	
$t$	1	1.25	1.5	1.75	(2)									
$v$	0	2.8	4.666..	6	7									
	$x = \frac{0.25}{2}(0 + 2 \times 2.8 + 2 \times 4.666... + 2 \times 6 + 7)$	M1A1												
	$X = 4.24175 \quad \text{Accept 4.2 or 4.24}$	A1 (4) [12]												

**(a) M1** Forming an equation of motion with acceleration as  $\frac{dv}{dt} = 900$  or  $m$

**DM1** Attempting the integration

**A1** Correct equation. Constant of integration not needed

**M1** Substituting either pair of given values

**A1** Obtaining correct equations using each pair of values

**A1** Obtaining correct values for  $c$  **and**  $k$  or use  $k = 5, \quad c = \frac{70}{k}$

**A1** Substituting these values to obtain the GIVEN answer  
Misread eg 6300 for 63000: M1DM1A1M1A0A0A0

**(b) B1** Must be clear that  $v < 14$  not just never = 14  $\frac{14}{t} > 0$  essential

**(c) B1** Showing that  $t = 2$  when  $v = 7$  Award if seen as upper limit for  $t$  in trapezium rule or values 1.25, 1.5, 1.75 seen for  $t$

**M1** Using the trapezium rule. Must have 4 intervals and values of  $t$  shown in the table.

**A1** Correct numbers in the trapezium rule statement.

Values of  $v$  can be in the form  $14 - \frac{14}{1.25}$  etc

**A1** Correct final answer. It is an estimate, so 2 or 3 sf only.

Question Number	Scheme	Marks
<p><b>5</b></p>	<p>Dist of c of m from <math>O = r \tan 30 = \frac{r}{\sqrt{3}}</math></p> <p>Ratio of masses <math>\begin{matrix} M &amp; kM &amp; (1+k)M \\ 1 &amp; k &amp; 1+k \end{matrix}</math></p> <p>Dist from <math>O</math> <math>\begin{matrix} -\frac{1}{4}h &amp; \frac{kh}{4} &amp; \frac{r}{\sqrt{3}} \end{matrix}</math></p> <p><math>M(O) \quad -\frac{1}{4}h + \frac{k^2h}{4} = (1+k)\frac{r}{\sqrt{3}}</math></p> <p><math>\frac{h}{4}(k^2 - 1) = (k+1)\frac{r}{\sqrt{3}}</math></p> <p><math>k = \frac{4r}{h\sqrt{3}} + 1 \quad *</math></p>	<p>M1A1</p> <p>M1A1A1ft</p> <p>A1 [6]</p>
<p><b>Alt 1</b></p>	<p>By moments about A</p> <p><math>kMg \left( \frac{1}{4}kh \cos 30 - r \sin 30 \right), \quad Mg \left( \frac{1}{4}h \cos 30 + r \sin 30 \right)</math></p> <p><math>h \cos 30(k^2 - 1) = 4r \sin 30(k + 1)</math></p> <p><math>(k - 1) = \frac{4r}{h} \tan 30</math></p> <p><math>k = \frac{4r}{h\sqrt{3}} + 1 \quad *</math></p>	<p>M1A1,M1A1</p> <p>A1ft</p> <p>A1</p>

Question Number	Scheme	Marks
<b>Alt 2</b>	Find $\bar{x}$ first  $M(0) \quad -\frac{1}{4}h + \frac{k^2h}{4} = (1+k)\bar{x}$ $\bar{x} = \frac{h(k-1)}{4} \quad \text{oe}$ Then suspend: $\frac{\bar{x}}{r} = \tan 30$  $\frac{h(k-1)}{4r} = \frac{1}{\sqrt{3}} \quad (\text{or } \tan 30)$  $k = \frac{4r}{h\sqrt{3}} + 1 \quad *$	M1 A1  A1  M1  A1ft  A1

**M1** Finding the distance of the c of m from  $O$  by using the angle given. Must use tan.

**A1** Obtaining  $\frac{r}{\sqrt{3}}$  (no approx allowed)

**M1** Forming a moments equation using the three known distances; mass ratio only needed – do not penalise use of incorrect formulae

**A1** LHS correct

**A1ft** RHS correct for their distance

**A1cao** Obtaining the GIVEN answer

#### **ALT 1 Taking moments about A**

**M1** Attempting the LHS – must have two appropriate terms inc the necessary resolution

**A1** Correct LHS

**M1** Attempting the RHS – must have two appropriate terms inc the necessary resolution

**A1** Correct RHS

**A1ft** Collecting the terms and cancelling  $Mg$

**A1cao** Completing to the GIVEN answer

#### **ALT 2 Find $\bar{x}$ first**

**M1** First M mark on e-PEN: Attempting an equation to find  $\bar{x}$  in terms of  $h$  and  $k$  - mass ratio as above

**A1** First A mark on e-PEN: Correct equation

**A1** Second A mark on e-PEN: Correct expression for  $\bar{x}$  (as shown or equivalent)

**M1** Second M mark on e-PEN: Using  $\frac{\bar{x}}{r} = \tan 30$  (LHS either way up)

**A1ft** Third A mark on e-PEN: Substitute their  $\bar{x}$ ; LHS must be the correct way up

**A1cao** Final A mark on e-PEN: Obtaining the GIVEN answer

Question Number	Scheme	Marks
<b>6 (a)</b>	$T_A = \frac{20x}{2.5} (=8x) \quad T_B = \frac{18(2-x)}{1.5} (=12(2-x))$ $\frac{20x}{2.5} = \frac{18(2-x)}{1.5}$ $x = \frac{12}{10} = 1.2$ $AO = 3.7 \text{ m}$	M1A1 A1 A1ft (4)
<b>(b)</b>	$\frac{18(0.8-y)}{1.5} - \frac{20(1.2+y)}{2.5} = 0.5\ddot{y}$ $-40y = \ddot{y} \therefore \text{SHM (or } \ddot{y} = (-20/m)y$	M1A1A1 A1cso (4)
<b>(c)</b>	$(\text{Max}) \text{ speed} = \frac{6}{0.5} = 12 \text{ m s}^{-1}$ $\omega = \sqrt{40} = 2\sqrt{10}$ $12 = a \times 2\sqrt{10}$ $a = \frac{6}{\sqrt{10}} \text{ or } \frac{3\sqrt{10}}{5} \text{ m (accept 1.897... ie 1.9, 1.90 or better)}$	B1 B1ft M1 A1ft (4)
<b>(d)</b>	$1.2 = a \sin \omega t$ $t = \frac{1}{2\sqrt{10}} \sin^{-1} \left( \frac{1.2\sqrt{10}}{6} \right)$ $t = 0.1082... \text{ s (Accept 0.11 or better)}$	M1(their $a, \omega$ ) M1(must use radians) A1cso (3) [15]

- (a) M1** Using Hooke's law to find **both** tensions and equating them. The extension in *BP* can be used instead of the extension in *AP*. ALT: Use both extensions and use  $e_a + e_b = 2$  later
- A1** Correct equation
- A1** Correct value found for either extension
- A1ft** Correct length for *AO*; follow through their extension
- (b) M1** Forming an equation of motion at a general point. Difference of 2 tensions, both including the variable. Use of  $a$  instead of  $\ddot{x}$  can score M1A1A0A0 max (ie an A error)
- A1 A1** A1A1 fully correct; A1A0 one error May have  $m$  instead of 0.5 Extensions measured from *O*
- A1cso** A correct simplified equation. Any equivalent form, including having  $m$  instead of 0.5. There must be a concluding statement.
- (c) B1** Correct speed following impulse Can be awarded if seen in (b) or (d)
- B1ft** Correct value of  $\omega$ ; must be numerical. FT from (b) Can be awarded if seen in (b) or (d)
- M1** Using  $v_{\max} = a\omega$  (their values). By energy – equation must have all terms
- A1ft** Correct value of  $a$  any equivalent form including decimals. Follow through their  $\omega$
- (d) M1** Using  $y = a \sin \omega t$  with their  $a$  and  $\omega$  If  $y = a \cos \omega t$  is used there must be some indication of moving from the time obtained to the required time.
- M1** Solving their equation to find a time. **Must** use radians
- A1cso** Correct time, min 2 sf.  $\omega$  and  $a$  must have been obtained from correct work.

Question Number	Scheme	Marks
7 (a)	$\frac{1}{2}mv^2 - \frac{1}{2}m\frac{rg}{4} = mgr(1 - \cos\theta)$	M1A1A1
	$v^2 = \frac{rg}{4}(9 - 8\cos\theta) \quad *$	A1 (4)
(b)	$(R) + mg \cos\theta = \frac{mv^2}{r}$	M1A1
	$R = 0 \quad mg \cos\alpha = \frac{mg}{4}(9 - 8\cos\alpha)$	DM1
	$12\cos\alpha = 9$ $\cos\alpha = \frac{3}{4}$ or 0.75	A1 (4)
(c)	Initial vert comp of speed = $\sqrt{\frac{3g}{8}} \sin\alpha = \sqrt{\frac{3g}{8}} \times \frac{\sqrt{7}}{4}$ (=1.2679...)	M1A1
	$\frac{7}{8} = 1.2679...t + \frac{1}{2}gt^2$	M1
	$7 = 10.143...t + 39.2t^2$	
	$39.2t^2 + 10.143...t - 7 = 0$	
	$t = \frac{-10.143 \pm \sqrt{10.143^2 + 4 \times 7 \times 39.2}}{2 \times 39.2}$	DM1
$t = 0.3125...$	A1	
	Horiz speed = $\sqrt{\frac{3g}{8}} \cos\alpha = \frac{1}{4} \sqrt{\frac{27g}{8}}$	
	$AC = \frac{1}{4} \sqrt{\frac{27g}{8}} \times 0.3125 + r \sin\alpha = 0.4493 + 0.3307 = 0.78 \text{ m}$	M1A1cso (7) [15]

- (a) **M1** Attempting an energy equation. 2KE terms needed and a PE term.  
Award if mass missing throughout, but **not** for use of  $v^2 = u^2 + 2as$   
**A1** KE terms correct (and subtracted) Mass not needed if M mark earned  
**A1** PE correct Again, mass not needed if M mark earned  
**A1cso** Obtaining the GIVEN answer

- (b) **M1** Attempting an equation of motion along the radius. Accel in either form,  $(\pm)R$  may be included.  
**A1** Correct equation, with or without  $(\pm)R$   
**DM1** Set  $R = 0$  and substitute for  $v$   
**A1**  $\cos\alpha = 3/4$  obtained

- (c) **M1** Attempting the initial vertical component of the speed
- A1** Correct vertical component - decimal or exact
- M1** Using  $s = ut + \frac{1}{2}at^2$  to form a quadratic in  $t$ , with *their* vertical speed and attempt at the vertical distance **Must** satisfy  $0.5 < \text{distance} < 1$
- DM1** Solving their quadratic; formula must be shown (and correct) if answer is incorrect, but allow with  $+\sqrt{\dots}$  instead of  $\pm\sqrt{\dots}$
- A1** Correct  $t$ . Give by implication if stored on a calculator and final answer correct  
Second solution need not be shown; ignore any shown
- M1** Using the horizontal speed and completing to obtain the required distance.
- A1**  $AC = 0.78$  **must** be 2 sf.

**ALT for (c):**

- M1A1** As main method above
- M1** Use the horizontal speed and distance travelled as a projectile to get an expression for  $t$  and substitute in  $s = ut + \frac{1}{2}at^2$  Vertical distance must be between 0.5 and 1
- DM1** Solve their quadratic - see above
- A1** Correct (projectile) distance
- M1A1** As main method above

**7(c) Using energy etc:**

<b>M1</b>	Using energy to get the speed at the floor. Can be from the top or the point of leaving the surface
<b>A1</b>	Correct speed at floor
<b>M1</b>	Using the horizontal component of the speed and Pythagoras to obtain the vertical component at the floor
<b>M1</b>	Using $v = u + at$ vertically to get $t$
<b>A1</b>	Correct $t$
<b>M1A1</b>	Complete as main method



## Other alternative Methods

## Question 4(a) by definite integration

$900 \frac{dv}{dt} = \frac{63000}{kt^2}$	M1
$\int_0^{10.5} dv = \int_1^4 \frac{70}{kt^2} dt$	
$[v]_0^{10.5} = \left[ -\frac{70}{kt} \right]_1^4$	DM1A1 Integration, limits not needed
$10.5(-0) = -\frac{70}{4k} + \frac{70}{k}$	M1 Substitute limits
$k = 5$	A1 Correct value
$\int_0^v dv = \int_1^t \frac{14}{t^2} dt$	A1 Integrate again with limits as shown
$v = 14 - \frac{14}{t} \quad *$	A1 Obtain GIVEN answer

## OR:

$900 \frac{dv}{dt} = \frac{63000}{kt^2}$	M1
$\int_0^v dv = \int_1^t \frac{70}{kt^2} dt$	
$[v]_0^v = \left[ -\frac{70}{kt} \right]_1^t$	DM1A1 Integration, limits not needed
$v = \frac{70}{k} \left[ -\frac{1}{t} \right]_1^t = \frac{70}{k} \left( 1 - \frac{1}{t} \right)$	M1 Substitute limits and $v = 10.5, t = 4$
$k = 5$	A1 Correct value
$v = \frac{70}{5} \left( 1 - \frac{1}{t} \right)$	A1 substitute
$v = 14 - \frac{14}{t} \quad *$	A1 Obtain GIVEN answer

## Question 6(c) by reference circle

**M1** Finding the required angle in radians.

**M1** Using the period  $\left( \frac{2\pi}{\omega} \right)$  and their angle to find the required time.

**A1** Correct time.

