

GCE Examinations
Advanced Subsidiary / Advanced Level
Mechanics
Module M3

Paper F
MARKING GUIDE

This guide is intended to be as helpful as possible to teachers by providing concise solutions and indicating how marks should be awarded. There are obviously alternative methods that would also gain full marks.

Method marks (M) are awarded for knowing and using a method.

Accuracy marks (A) can only be awarded when a correct method has been used.

(B) marks are independent of method marks.



Written by Shaun Armstrong & Chris Huffer

© Solomon Press


These sheets may be copied for use solely by the purchaser's institute.

M3 Paper F – Marking Guide

1. (a) impulse = $\int_1^4 F \, dt = \int_1^4 (4t + 3) \, dt$ M1
 $= [2t^2 + 3t]_1^4 = (32 + 12) - (2 + 3) = 39 \text{ Ns}$ M1 A1

(b) $\int_0^T F \, dt = m(v - u)$ M1
 $\therefore [2t^2 + 3t]_0^T = 1.5(22 - 0)$ A1
giving $2T^2 + 3T - 33 = 0$ A1
quad. form. gives $T = -4.88, 3.38; T > 0 \therefore T = 3.38 \text{ s}$ (3sf) M1 A1 (8)


2. (a) con. of ME: $\frac{1}{2}mv^2 = mgh$ M1
giving $v^2 = 2g(r - r\cos\theta) = 2 \times 9.8 \times 1.25(1 - \cos\theta) = 24.5(1 - \cos\theta)$ M1 A1

(b) 
resolve \leftarrow : $mg \cos\theta - R = \frac{mv^2}{r} = \frac{mv^2}{1.25}$ M1 A1
leaves surface when $R = 0 \therefore v^2 = 1.25g \cos\theta$ M1
combining, $24.5(1 - \cos\theta) = 1.25g \cos\theta$ M1
 $\therefore 24.5 = \cos\theta(1.25 \times 9.8 + 24.5)$
giving $\cos\theta = \frac{24.5}{36.75} = \frac{2}{3}$ A1 (8)

3. (a) $a = v \frac{dv}{dx} = \frac{500-kx}{150}$ M1
 $\therefore \int 150v \, dv = \int 500 - kx \, dx$ M1
 $75v^2 = 500x - \frac{1}{2}kx^2 + c$ A1
 $x = 0, v = 0 \therefore c = 0$ M1
 $x = 40, v = 16 \therefore 19200 = 20000 - 800k$ giving $k = 1$ M1 A1

(b) v_{\max} when $a = 0 \therefore \frac{500-x}{150} = 0$ so $x = 500$ M1
 $75v_{\max}^2 = 250000 - 125000$ giving $v_{\max} = 41 \text{ ms}^{-1}$ (2sf) M1 A1

(c) when $v = 0, 500x - \frac{1}{2}x^2 = 0$ M1
 $\therefore \frac{1}{2}x(1000 - x) = 0$ so $x = 0$ (at O) or $1000 \therefore OA = 1000 \text{ m}$ M1 A1 (12)

4. (a) 
resolve \nwarrow : $R - 2g \cos 30 = 0 \therefore R = \sqrt{3}g$ M1 A1
friction = $\mu R = \frac{1}{6}\sqrt{3} \times \sqrt{3}g = \frac{1}{2}g$ A1
work done = $Fs = \frac{1}{2} \times 9.8 \times 2.2 = 10.78 \text{ J}$ M1 A1

(b) change in GPE = $mgh = 2 \times 9.8 \times 2.2 \sin 30 = 21.56 \text{ J}$ (loss) M1 A1

(c) work done = loss of GPE – gain of EPE M1
 $\therefore 10.78 = 21.56 - \frac{\lambda x^2}{2l}$ M1 A1
giving $\frac{\lambda \times 0.7^2}{2 \times 1.5} = 10.78$ so $\lambda = 66 \text{ N}$ M1 A1 (12)

5. (a)

portion	mass	y	my
large cylinder	$\rho \times \pi (\frac{4}{3} r)^2 \times \frac{3}{2} h = \frac{8}{3} \rho \pi r^2 h$	$\frac{3}{4} h$	$2\rho \pi r^2 h^2$
small cylinder	$\rho \pi r^2 h$	$\frac{1}{2} h$	$\frac{1}{2} \rho \pi r^2 h^2$
flask	$\frac{5}{3} \rho \pi r^2 h$	\bar{y}	$\frac{3}{2} \rho \pi r^2 h^2$

$$\rho = \text{mass per unit volume} \quad y \text{ coords. taken vert. from open face} \quad \text{M2 A3}$$

$$\frac{5}{3} \rho \pi r^2 h \times \bar{y} = \frac{3}{2} \rho \pi r^2 h^2 \therefore \bar{y} = \frac{3}{2} h \div \frac{5}{3} = \frac{9}{10} h \quad \text{M1 A1}$$

(b)

portion	mass	y	my
flask	$\frac{5}{3} \rho \pi r^2 h$	$\frac{9}{10} h$	$\frac{3}{2} \rho \pi r^2 h^2$
liquid	$k \rho \pi r^2 h$	$\frac{1}{2} h$	$\frac{1}{2} k \rho \pi r^2 h^2$
full flask	$(\frac{5}{3} + k) \rho \pi r^2 h$	$\frac{15}{22} h$	$(\frac{3}{2} + \frac{1}{2} k) \rho \pi r^2 h^2$

$$\rho = \text{mass per unit volume} \quad y \text{ coords. taken vert. from open face} \quad \text{M2 A2}$$

$$(\frac{5}{3} + k) \rho \pi r^2 h \times \frac{15}{22} h = (\frac{3}{2} + \frac{1}{2} k) \rho \pi r^2 h^2 \quad \text{M1}$$

$$\therefore 15(\frac{5}{3} + k) = 22(\frac{3}{2} + \frac{1}{2} k), 25 + 15k = 33 + 11k, k = 2 \quad \text{M1 A1}$$

(c) e.g. when full the centre of mass is in top half so easily knocked over B2 (16)

6. (a)

$$v^2 = \omega^2(a^2 - x^2)$$

$$x = \pm 3, v = \pm 6 \therefore 36 = \omega^2(a^2 - 9) \text{ giving } \omega^2 = \frac{36}{a^2 - 9} \quad \text{M1 A1}$$

$$x = \pm 2.25, v = \pm 8 \therefore 64 = \omega^2(a^2 - \frac{81}{16}) \quad \text{M1}$$

$$\text{combining, } 64 = \frac{36}{a^2 - 9} (a^2 - \frac{81}{16}) \quad \text{M1}$$

$$\text{giving } 16(a^2 - 9) = 9(a^2 - \frac{81}{16}) \quad \text{A1}$$

$$256a^2 - 2304 = 144a^2 - 729$$

$$\text{so } a^2 = \frac{1575}{112} = \frac{225}{16}, a = \frac{15}{4} \therefore AB = 7.5 \text{ m} \quad \text{M1 A1}$$

$$(b) a^2 = \frac{225}{16} \therefore 64 = \omega^2(\frac{225}{16} - \frac{81}{16}) \text{ so } \omega^2 = \frac{64}{9}, \omega = \frac{8}{3} \quad \text{M1 A1}$$

$$\text{period} = \frac{2\pi}{\omega} = 2\pi \div \frac{8}{3} = \frac{3}{4}\pi \text{ s} \quad \text{M1 A1}$$

$$(c) \text{ KE} = \frac{1}{2}mv^2 = \frac{1}{2} \times 2.5 \times \frac{64}{9} (\frac{225}{16} - 1.05^2) = 115.2 \text{ J} \quad \text{M1 A2}$$

$$(d) x = a \cos \omega t \therefore -\frac{3.75}{2} = 3.75 \cos \omega t \quad \text{M1 A1}$$

$$\cos \omega t = -\frac{1}{2} \therefore \omega t = \frac{2\pi}{3} \quad \text{M1}$$

$$\therefore t = \frac{2\pi}{3} \div \frac{8}{3} = \frac{\pi}{4} \text{ s} \quad \text{A1} \quad (19)$$

Total (75)

Performance Record – M3 Paper F