UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the October/November 2010 question paper for the guidance of teachers

9709 MATHEMATICS

9709/42

Paper 4, maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2010 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE A/AS LEVEL – October/November 2010	9709	42

Mark Scheme Notes

Marks are of the following three types:

- M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.
- A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).
- B Mark for a correct result or statement independent of method marks.
- When a part of a question has two or more "method" steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.
- The symbol √ implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0. B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking *g* equal to 9.8 or 9.81 instead of 10.

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE A/AS LEVEL – October/November 2010	9709	42

The following abbreviations may be used in a mark scheme or used on the scripts:

AEF	Any Equivalent Form (of answer is equally acceptable)
AG	Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)
BOD	Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear)
CAO	Correct Answer Only (emphasising that no "follow through" from a previous error is allowed)
CWO	Correct Working Only – often written by a 'fortuitous' answer
ISW	Ignore Subsequent Working
MR	Misread
PA	Premature Approximation (resulting in basically correct work that is insufficiently accurate)
sos	See Other Solution (the candidate makes a better attempt at the same question)
SR	Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance)

Penalties

- MR –1 A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become "follow through √" marks. MR is not applied when the candidate misreads his own figures this is regarded as an error in accuracy. An MR –2 penalty may be applied in particular cases if agreed at the coordination meeting.
- PA –1 This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting.

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2010	9709	42

$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$					
$F = 2000\sin 15^{\circ} = \mu (400 \text{g} - 2000\cos 15^{\circ})] \qquad \text{M1} \qquad \text{For using F} = \mu R$ $Coefficient is 0.25 \qquad \qquad \text{A1} \qquad \textbf{[5]}$ $SR(\max. 4/5) \text{ for candidates who either:}$ $\text{have sin and cos interchanged or have angle } 15^{\circ} \text{ above the horizontal}$ $R + 2000\sin 15^{\circ} = 400 \text{ g and } F = 2000\cos 15^{\circ} \qquad \text{A1}$ $[2000\cos 15^{\circ} = \mu (400 \text{ g} - 2000\sin 15^{\circ})] \qquad \text{M1} \qquad \text{For using F} = \mu R$ $Coefficient is 0.55 \qquad \qquad \text{A1}$ $Coefficient is 0.55 \qquad \qquad \text{A1}$ $DF - 80 \text{ g sin2}^{\circ} = 80 \text{ a (i) or}$ $DF + 80 \text{ g sin2}^{\circ} = 80 \text{ a (i) or}$ $Acceleration is 0.9 \text{ ms}^{-2} \text{ (i) or}$ $Acceleration is 1.6 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (i)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 0.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.6 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 1.9 \text{ ms}^{-2} \text{ (ii)}$ $Acceleration is 0.9 \text{ ms}^{-2} \text{ (ii)}$ $Acce$	1		M1		• ` `
[2000sin15° = μ (400 g – 2000cos15°)] M1 For using F = μ R Coefficient is 0.25 A1 [5] SR(max. 4/5) for candidates who either: have sin and cos interchanged or have angle 15° above the horizontal R + 2000sin15° = 400 g and F = 2000cos15° A1 [2000cos15° = μ (400 g – 2000sin15°)] M1 For using F = μ R Coefficient is 0.55 A1 Coefficient is 0.55 A1 Driving force = 400/4 B1 DF - 80 g sin2° = 80a (i) or DF + 80 g sin2° = 80a (ii) or DF + 80 g sin2° = 80a (ii) or Acceleration is 0.9 ms² (i) or Acceleration is 1.6 ms² (ii) Acceleration is 0.9 ms² (i) and Acceleration is 0.9 ms² (ii) All For using Newton's second law (either case) and the second interchanged Driving force = 400/4 B1 For using Newton's second law (either case) - 3 terms needed Acceleration is 0.9 ms² (ii) and Acceleration is 0.9 ms² (ii) and Acceleration is 0.9 ms² (ii) All For using Newton's second law (either case) - 3 terms needed Triving force = 400/4 B1 For using Newton's second law (either case) - 3 terms needed All For using Newton's second law (either case) - 3 terms needed The second is a fixed by the second law (either case) - 3 terms needed All For using Newton's second law (either case) - 3 terms needed For a termpting to solve for α °. The second is a fixed by the second is a fix		$R + 2000\cos 15^{\circ} = 400 \mathrm{g}$	A1		
Coefficient is 0.25 SR(max. 4/5) for candidates who either: have sin and cos interchanged or have angle 15° above the horizontal M1 For resolving forces vertically R + 2000sin15° = 400g and $F = 2000 \text{cos} 15^{\circ}$ A1 [2000cos15° = μ ($400 \text{g} - 2000 \text{sin} 15^{\circ}$)] M1 For using $F = \mu R$ Coefficient is 0.55 A1 2 Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed DF - $80 \text{g} \sin 2^{\circ} = 80 \text{a}$ (i) or DF + $80 \text{g} \sin 2^{\circ} = 80 \text{a}$ (ii) Acceleration is 1.6ms^2 (ii) Acceleration is 1.6ms^2 (ii) and Acceleration is 1.6ms^2 (ii) and Acceleration is 1.6ms^2 (iii) Acceleration is 0.9ms^2 (i) SR(max. $3/5$) for candidates who have sin and cos interchanged Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed 3 M1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For tesolving forces in I and J directions (3 terms in at least one of the equations) 6cos $\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F$ and 6sin $\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [6cos $\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [7cot attempting to solve for α° . Popendent on 1° M1 For substituting to find F; dependent on the 1° M1		$F = 2000 \sin 15^{\circ}$	B1		
SR(max. 4/5) for candidates who either: have sin and cos interchanged or have angle 15° above the horizontal M1 For resolving forces vertically R + 2000sin 15° = 400 g and F = 2000cos 15° A1 [2000cos 15° = μ (400 g – 2000sin 15°)] M1 For using F = μ R Coefficient is 0.55 A1 2 Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed DF - 80 g sin 2° = 80a (i) or DF + 80 g sin 2° = 80a (i) or Acceleration is 0.9 ms $^{\circ}$ (ii) Acceleration is 1.6 ms $^{\circ}$ (iii) Acceleration is 1.6 ms $^{\circ}$ (iii) Acceleration is 0.9 ms $^{\circ}$ (i) and Acceleration is 0.9 ms $^{\circ}$ (i) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed 3 M1 For using Newton's second law (either case) – 3 terms needed 3 M1 For using Newton's second law (either case) – 3 terms needed 4 a - 8.74 (i) and a = 11.2 (ii) A1 3 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) 6 cos α° + 5 cos (90° – α°) = F and 6 sin α° - 5 cos (90° – α°) = F A1 [6 cos α° + 5 cos (90° – α°) = F A1 [6 cos α° + 5 cos (90° – α°) = F A1 [6 cos α° + 5 cos (90° – α°) = F A1 [6 cos α° + 5 cos (90° – α°) = F A1 [6 cos α° + 5 cos (90° – α°) = F A1 [7 cos (3 terms in at least one of the equations) A1 [8 cos (3 terms in at least one of the equations) A1 [9 cos (3 terms in at least one of the equations) A2 A3 [7 cos (3 terms in at least one of the equations) A4 [8 cos (3 terms in at least one of the equations) A3 A4 [9 cos (4 terms in a terms		$[2000\sin 15^{\circ} = \mu (400 \mathrm{g} - 2000\cos 15^{\circ})]$	M1		For using $F = \mu R$
have sin and cos interchanged or have angle 15° above the horizontal $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		Coefficient is 0.25	A1	[5]	
$R + 2000\sin 15^{\circ} = 400 \ \underline{a} \ \underline{and} \ F = 2000\cos 15^{\circ} \qquad A1$ $[2000\cos 15^{\circ} = \mu \ (400 \ \underline{g} - 2000\sin 15^{\circ})] \qquad M1 \qquad For using \ F = \mu \ R$ $Coefficient is 0.55 \qquad A1$ $DF - 80 \ \underline{g} \sin 2^{\circ} = 80 \ \underline{a} \ \underline{(i)} \text{or} \qquad A1$ $DF - 80 \ \underline{g} \sin 2^{\circ} = 80 \ \underline{a} \ \underline{(i)} \text{or} \qquad A1$ $DF + 80 \ \underline{g} \sin 2^{\circ} = 80 \ \underline{a} \ \underline{(i)} \text{or} \qquad A1$ $Acceleration is 0.9 \ \mathrm{ms}^2 \underline{(i)} \text{or} \qquad A1 Acceleration is 1.6 \ \mathrm{ms}^2 \underline{(ii)} \text{and} \qquad Acceleration is 1.6 \ \mathrm{ms}^2 \underline{(ii)} \text{and} \qquad Acceleration is 0.9 \ \mathrm{ms}^2 \underline{(i)} \text{or} \qquad A1 Acceleration is 0.9 \ \mathrm{ms}^2 \underline{(i)} \text{and} \qquad Acceleration is 0.9 \ \mathrm{ms}^2 \underline{(i)} \underline{(i)}$		· · · · · · · · · · · · · · · · · · ·	° above th	e horiz	zontal
[2000cos15° = μ (400 g - 2000sin15°)] M1 For using F = μ R Coefficient is 0.55 A1 Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed DF - 80 g sin2° = 80a (i) or A1 DF + 80 g sin2° = 80a (ii) Acceleration is 0.9 ms² (i) or A1 Acceleration is 1.6 ms² (ii) and Acceleration is 1.6 ms² (ii) and Acceleration is 0.9 ms² (i) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed a = -8.74 (i) and a = 11.2 (ii) A1 M1 For using Newton's second law (either case) – 3 terms needed a = -8.74 (i) and a = 11.2 (ii) A1 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) 6cos α ° + 5cos(90° – α °) = F and 6sin α ° – 5sin(90° – α °) = F A1 [6cos α ° + 5sin α ° – 6sin α ° – 5cos α ° \rightarrow 11cos α ° = sin α °] DM1 Dependent on 1st M1 α = 84.8 [F = 6cos84.8° + 5sin84.8°; F = 6sin84.8° – DM1 For substituting to find F; dependent on the 1st M1			M1		For resolving forces vertically
Coefficient is 0.55 A1 B1 M1 For using Newton's second law (either case) – 3 terms needed DF - 80 g sin2° = 80a (i) or DF + 80 g sin2° = 80a (ii) Acceleration is 0.9 ms² (i) or Acceleration is 1.6 ms² (ii) Acceleration is 1.6 ms² (ii) Acceleration is 0.9 ms² (i) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F$ and $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90$		$R + 2000\sin 15^{\circ} = 400 \text{ g} \text{ and } F = 2000\cos 15^{\circ}$	A1		
Coefficient is 0.55 A1 B1 M1 For using Newton's second law (either case) – 3 terms needed DF - 80 g sin2° = 80a (i) or DF + 80 g sin2° = 80a (ii) Acceleration is 0.9 ms² (i) or Acceleration is 1.6 ms² (ii) Acceleration is 1.6 ms² (ii) Acceleration is 0.9 ms² (i) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = 400/4 B1 M1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For using Newton's second law (either case) – 3 terms needed A1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F$ and $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 [$6\cos\alpha^{\circ} + 5\sin(90$		$[2000\cos 15^{\circ} = \mu (400 \text{ g} - 2000\sin 15^{\circ})]$	M1		For using $F = \mu R$
		, , ,	A1		ξ ,
		D:: C 400/4	D.1		
$ \text{case}) - 3 \text{ terms needed} $ $ \text{DF} - 80 \text{ g sin2}^{\circ} = 80 \text{ a (i)} \text{ or } $ $ \text{DF} + 80 \text{ g sin2}^{\circ} = 80 \text{ a (ii)} $ $ \text{Acceleration is } 0.9 \text{ ms}^{-2} \text{ (i)} \text{ or } $ $ \text{Acceleration is } 1.6 \text{ ms}^{-2} \text{ (ii)} $ $ \text{Acceleration is } 1.6 \text{ ms}^{-2} \text{ (ii)} $ $ \text{Acceleration is } 1.6 \text{ ms}^{-2} \text{ (ii)} $ $ \text{Acceleration is } 0.9 \text{ ms}^{-2} \text{ (i)} $ $ \text{Blft} $	2	Driving force = 400/4			Farming Nameton 2 and 1 lane (cither
DF + 80 g sin2° = 80a (ii) Acceleration is 0.9ms^{-2} (i) or A1 Accept $0.90 \text{or} 0.901$ and 1.60 Acceleration is 1.6ms^{-2} (ii) Acceleration is 1.6ms^{-2} (ii) and Acceleration is 0.9ms^{-2} (ii) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed 3 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F \text{and}$ $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{and}$ $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{A1}$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ} \text{For attempting to solve for } \alpha^{\circ}.$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}] \text{DM1} \text{Dependent on } 1^{\text{st}} \text{M1}$ $\alpha = 84.8 \text{A1}$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - \text{DM1} \text{For substituting to find } F;$ $5\cos84.8^{\circ}] \text{for attempting to find } F;$ $dependent \text{ on the } 1^{\text{st}} \text{M1}$			IVI I		
Acceleration is 0.9ms^{-2} (i) or Acceleration is 1.6ms^{-2} (ii) and Acceleration is 1.6ms^{-2} (ii) and Acceleration is 0.9ms^{-2} (ii) and Acceleration is 0.9ms^{-2} (ii) B1ft [5] ft Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed 3 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F$ and $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ}$ For attempting to solve for α° . $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}]$ DM1 Dependent on 1^{st} M1 $\alpha = 84.8$ A1 $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - DM1$ For substituting to find F; dependent on the 1^{st} M1			A1		
Acceleration is $0.9\mathrm{ms}^{-2}$ (i) B1ft [5] if Ans (i) + (ii) = 2.5 SR(max. 3/5) for candidates who have sin and cos interchanged Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed $a = -8.74$ (i) and $a = 11.2$ (ii) A1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^\circ + 5\cos(90^\circ - \alpha^\circ) = F$ and $6\sin\alpha^\circ - 5\sin(90^\circ - \alpha^\circ) = F$ A1 $[6\cos\alpha^\circ + 5\sin\alpha^\circ = 6\sin\alpha^\circ - 5\cos\alpha^\circ$ For attempting to solve for α° . $\rightarrow 11\cos\alpha^\circ = \sin\alpha^\circ]$ DM1 $\alpha = 84.8$ A1 $For substituting to find F; dependent on the 1st M1 For substituting to find F; dependent on the 1st M1$		Acceleration is $0.9 \mathrm{ms}^{-2}$ (i) or	A1		Accept 0.90 or 0.901 and 1.60
Driving force = $400/4$ B1 M1 For using Newton's second law (either case) – 3 terms needed $a = -8.74$ (i) and $a = 11.2$ (ii) A1 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos \alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F$ and $6\sin \alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ A1 $[6\cos \alpha^{\circ} + 5\sin \alpha^{\circ} = 6\sin \alpha^{\circ} - 5\cos \alpha^{\circ}]$ For attempting to solve for α° . DM1 $\alpha = 84.8$ A1 $[F = 6\cos 84.8^{\circ} + 5\sin 84.8^{\circ}; F = 6\sin 84.8^{\circ} - DM1$ For substituting to find F; dependent on the 1 st M1			B1ft	[5]	ft Ans (i) + (ii) = 2.5
$M1 \qquad \text{For using Newton's second law (either case)} - 3 \text{ terms needed}$ $3 \qquad \qquad M1 \qquad \text{For resolving forces in } \mathbf{i} \text{ and } \mathbf{j} \text{ directions}$ $6\cos\alpha^\circ + 5\cos(90^\circ - \alpha^\circ) = \mathbf{F} \qquad \text{and}$ $6\sin\alpha^\circ - 5\sin(90^\circ - \alpha^\circ) = \mathbf{F} \qquad \text{A1}$ $[6\cos\alpha^\circ + 5\sin\alpha^\circ - 6\sin\alpha^\circ - 5\cos\alpha^\circ \qquad \qquad \text{For attempting to solve for } \alpha^\circ.$ $\Rightarrow 11\cos\alpha^\circ = \sin\alpha^\circ] \qquad DM1 \qquad \text{Dependent on } 1^{\text{st}} M1$ $\alpha = 84.8 \qquad \text{A1}$ $[\mathbf{F} = 6\cos84.8^\circ + 5\sin84.8^\circ; \mathbf{F} = 6\sin84.8^\circ - DM1 \qquad \text{For substituting to find } \mathbf{F};$ $5\cos84.8^\circ] \qquad \text{Tor substituting to find } \mathbf{F};$ $\text{dependent on the } 1^{\text{st}} M1$		SR(max. 3/5) for candidates who have sin and of	cos intercl	nanged	1
3 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F \text{and} \\ 6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{A1}$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ} \text{For attempting to solve for } \alpha^{\circ}.$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}] \text{DM1} \text{Dependent on } 1^{\text{st}} \text{ M1}$ $\alpha = 84.8 \text{A1}$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - \text{DM1} \text{For substituting to find } F;$ $5\cos84.8^{\circ}] \text{DM1} \text{For substituting to find } F;$ $dependent \text{ on the } 1^{\text{st}} \text{ M1}$		Driving force = $400/4$	B1		
3 M1 For resolving forces in i and j directions (3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F \text{and}$ $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{A1}$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ} \text{For attempting to solve for } \alpha^{\circ}.$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}] \text{DM1} \text{Dependent on } 1^{\text{st}} \text{ M1}$ $\alpha = 84.8 \text{A1}$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - \text{DM1} \text{For substituting to find } F;$ $5\cos84.8^{\circ}] \text{dependent on the } 1^{\text{st}} \text{ M1}$			M1		
(3 terms in at least one of the equations) $6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F \text{and}$ $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{A1}$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ} \text{For attempting to solve for } \alpha^{\circ}.$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}] \text{DM1} \text{Dependent on } 1^{\text{st}} \text{ M1}$ $\alpha = 84.8 \text{A1}$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - \text{DM1} \text{For substituting to find } F;$ $5\cos84.8^{\circ}] \text{dependent on the } 1^{\text{st}} \text{ M1}$		a = -8.74 (i) and $a = 11.2$ (ii)	A1		
$6\cos\alpha^{\circ} + 5\cos(90^{\circ} - \alpha^{\circ}) = F \text{and} $ $6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F \text{A1}$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ} \text{For attempting to solve for } \alpha^{\circ}.$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}] \text{DM1} \text{Dependent on } 1^{\text{st}} \text{ M1}$ $\alpha = 84.8 \text{A1}$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - \text{DM1} \text{For substituting to find } F;$ $5\cos84.8^{\circ}] \text{dependent on the } 1^{\text{st}} \text{ M1}$	3		M1		
$6\sin\alpha^{\circ} - 5\sin(90^{\circ} - \alpha^{\circ}) = F$ $[6\cos\alpha^{\circ} + 5\sin\alpha^{\circ} = 6\sin\alpha^{\circ} - 5\cos\alpha^{\circ}$ $\rightarrow 11\cos\alpha^{\circ} = \sin\alpha^{\circ}]$ $11\cos\alpha^{\circ} = \sin\alpha^{\circ}]$ $[F = 6\cos84.8^{\circ} + 5\sin84.8^{\circ}; F = 6\sin84.8^{\circ} - DM1$ $5\cos84.8^{\circ}]$ For attempting to solve for α° . Dependent on 1^{st} M1 For substituting to find F; dependent on the 1^{st} M1					(3 terms in at least one of the equations)
		,	A1		
$[F = 6\cos 84.8^{\circ} + 5\sin 84.8^{\circ}; F = 6\sin 84.8^{\circ} - DM1$ For substituting to find F; dependent on the 1 st M1		<u>-</u>	DM1		
5cos84.8°] dependent on the 1 st M1		$\alpha = 84.8$	A1		
F = 5.52 A1 [6]			DM1		
		F = 5.52	A1	[6]	

Page 5	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2010	9709	42

First alternative sc	heme			
$[2F^2 = 25 + 3]$	6]	M1		For using '(resultant of forces of magnitude F) ² = (resultant of forces of magnitudes 5 and 6) ² '
F = 5.52		A 1		
		M1		For using 'resultant of forces of magnitudes 5 and 6 makes angle 45° with x-axis'
		M1		For using relevant trigonometry
` ′	= 5/6 or $\tan(135^{\circ} - \alpha^{\circ}) = 6/5$ or $\sin(135^{\circ} - \alpha^{\circ}) = 6/\sqrt{61}$ or			
$\sin(\alpha^{\circ}-45^{\circ})$	or $\cos(135^{\circ} - \alpha^{\circ}) = 5/\sqrt{61}$	A1		
α = 84.8		A1		
Second alternative	scheme			
$[6\cos\alpha^{\circ} + 5\cos\alpha^{\circ}]$,			
$=6\sin\alpha^{\circ}$	$-5\sin(90^{\circ}-\alpha^{\circ})]$	M1		For using $Rx = Ry$
$[11\cos\alpha^{\circ} - \sin\alpha]$	$n\alpha^{\circ} = 0$	M1		For attempting to solve for α°
$\alpha = 84.8$		A1		
	$\alpha^{o} + 5\cos(90^{o} - \alpha^{o})$ or			
$F = 6\sin\alpha^{\circ} - 1$	$5\sin(90^{\circ}-\alpha^{\circ})$	B1		
		M1		For substituting for α
F = 5.52		A1		
4 (i) [½ 20(2.	$5^2 - 1.5^2$), $20 \times 10 \times 10 \sin 4.5^\circ$]			For using KE loss = $\frac{1}{2}$ m($u^2 - v^2$)
		M1		or PE gain = $mg(L\sin\alpha)$
KE loss =	= 40 J or PE gain = 157 J	A1		
PE gain =	= 157 J or KE loss = 40 J	B1	[3]	
(ii) [WD = 1	57 – 40 + 50]	M1		For using WD by pulling force = PE gain – KE loss + WD against resistance
Work do	ne is 167 J	A1ft	[2]	ft incorrect PE gain + 10, even if -ve
(iii) [167 = F	x10cos15°]	M1		For using WD = FLcos 15°
Magnitue	le is 17.3 N	A1ft	[2]	
	for candidates who (implicitly) apply Newton's second law	make the u	ınjustif	fiable assumption that acceleration is
•	e is 17.3 N from $gsin 4.5^{\circ} - 50/10 = 20 \times (-0.2)$	B1		

Page 6	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2010	9709	42

_	(:)	$515 - 204 54^2 \rightarrow 5(4^2 44 + 2) = 0$	N/1		Equation $f(t) = \frac{1}{2}$
5		$[15 = 20t - 5t^2 \rightarrow 5(t^2 - 4t + 3) = 0]$	M1		For use of $h = ut - \frac{1}{2}gt^2$
		t = 1, 3	A1		
		Duration is 2 s (accept $1 < t < 3$)	B1ft	[3]	ft $t_2 - t_1$
	(ii)		M1		For using $h_P = h_Q$ at time t after P's (or Q's) projection
		$20t - 5t^2 = 25(t - 0.4) - 5(t - 0.4)^2$ (or $20(t + 0.4) - 5(t + 4)^2 = 25t - 5t^2$ or $(20 \times 0.4 - 5 \times 0.4^2) + 16t - 5t^2 = 25t - 5t^2$)	A1		
		t = 1.2 (or $t = 0.8$)	A1		
		$[v_P = 20 - 10x1.2; v_Q = 25 - 10x(1.2 - 0.4)]$ (or	M1		For using $v = u - gt$ for both v_P and v_Q
		$v_P = 20 - 10x(0.8 + 0.4); v_Q = 25 - 10x0.8)$			
		Velocities are 8 ms ⁻¹ and 17 ms ⁻¹	A1	[5]	
6	(i)	$[\frac{1}{2} 2.5(\text{speed}_{\text{max}}) = 4]$	M1		For using area property for distance
		Greatest speed is 3.2 ms ⁻¹	A1	[2]	
		SR (max. 1/2) for candidates who (implicitly) make the unjustifiable assumption that speed _{max} occurs when $t = 1.25$			justifiable assumption that speed _{max}
		Greatest speed is 3.2 ms^{-1} from $2 \text{ x } \frac{1}{2} 1.25 \text{ (speed}_{\text{max}}) \text{ v} = 4$	B1		
	(ii)	[V = 3x2]	M1		For using $a = (V - 0)/(4.5 - 2.5)$ or $V = 0 + at$
		V = 6	A1	[2]	
	(iii)		M1		For using area property for distance from $t = 2.5$ to $t = 14.5$
		$\frac{1}{2} 6(12 + T) = 48$ or			
		$\frac{1}{2} 6x^2 + 6T + \frac{1}{2} 6(10 - T) = 48$ or			
		$\frac{1}{2} 6x^2 + 6(10 - \tau) + \frac{1}{2} 6\tau = 48$	A1ft		
		t = 8.5	A1	[3]	from $4.5 + T$ or $14.5 - \tau$
	(iv)		M1		For using $a = (0 - V)/(14.5 - 8.5)$ or $0 = V + a(14.5 - 8.5)$
		Deceleration is 1 ms ⁻²	A1ft	[2]	

Page 7	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2010	9709	42

7	(i)	$a(t) = 0.006t^2 - 0.24t + 1.8$	B1		
		$[0.006(t^2 - 40t + 300) = 0]$	M1		For solving $a(t) = 0$
		$T_1 = 10, T_2 = 30$	A1		
			M1		For integrating $v(t)$
		$s(t) = 0.0005t^4 - 0.04t^3 + 0.9t^2 + 5t + (C)$	A1		
		[405 - 1080 + 810 + 150]	M1		For using limits 0 to T ₂ or equivalent
		Distance is 285 m	A1	[7]	
	(ii)	Velocity is 5 ms ⁻¹	B1		
		For curve with v increasing from a +ve value at $t=0$ to a maximum	B1		
		Then decreases to a +ve minimum and thereafter increases	B1	[3]	