



GCE

Further Mathematics B (MEI)

Y421/01: Mechanics major

Advanced GCE

Mark Scheme for June 2019

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

© OCR 2019

Y421/01

Mark Scheme

June 2019

Text Instructions

Annotations and abbreviations

Annotation in scoris	Meaning
✓ and ✕	
BOD	Benefit of doubt
FT	Follow through
ISW	Ignore subsequent working
M0, M1	Method mark awarded 0, 1
A0, A1	Accuracy mark awarded 0, 1
B0, B1	Independent mark awarded 0, 1
SC	Special case
^	Omission sign
MR	Misread
Highlighting	
Other abbreviations in mark scheme	Meaning
E1	Mark for explaining a result or establishing a given result
dep*	Mark dependent on a previous mark, indicated by *
cao	Correct answer only
oe	Or equivalent
rot	Rounded or truncated
soi	Seen or implied
www	Without wrong working
AG	Answer given
awrt	Anything which rounds to
BC	By Calculator
DR	This indicates that the instruction In this question you must show detailed reasoning appears in the question.

Subject-specific Marking Instructions for A Level Mathematics B (MEI)

- a Annotations should be used whenever appropriate during your marking. The A, M and B annotations must be used on your standardisation scripts for responses that are not awarded either 0 or full marks. It is vital that you annotate standardisation scripts fully to show how the marks have been awarded. For subsequent marking you must make it clear how you have arrived at the mark you have awarded.
- b An element of professional judgement is required in the marking of any written paper. Remember that the mark scheme is designed to assist in marking incorrect solutions. Correct solutions leading to correct answers are awarded full marks but work must not be judged on the answer alone, and answers that are given in the question, especially, must be validly obtained; key steps in the working must always be looked at and anything unfamiliar must be investigated thoroughly. Correct but unfamiliar or unexpected methods are often signalled by a correct result following an apparently incorrect method. Such work must be carefully assessed. When a candidate adopts a method which does not correspond to the mark scheme, escalate the question to your Team Leader who will decide on a course of action with the Principal Examiner. If you are in any doubt whatsoever you should contact your Team Leader.
- c The following types of marks are available.

M

A suitable method has been selected and *applied* in a manner which shows that the method is essentially understood. Method marks are not usually lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. In some cases the nature of the errors allowed for the award of an M mark may be specified.

A

Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated Method mark is earned (or implied). Therefore M0 A1 cannot ever be awarded.

B

Mark for a correct result or statement independent of Method marks.

E

A given result is to be established or a result has to be explained. This usually requires more working or explanation than the establishment of an unknown result.

Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored. Sometimes this is reinforced in the mark scheme by the abbreviation isw. However, this would not apply to a case where a candidate passes through the correct answer as part of a wrong argument.

Y421/01

Mark Scheme

June 2019

- d When a part of a question has two or more 'method' steps, the M marks are in principle independent unless the scheme specifically says otherwise; and similarly where there are several B marks allocated. (The notation 'dep*' is used to indicate that a particular mark is dependent on an earlier, asterisked, mark in the scheme.) Of course, in practice it may happen that when a candidate has once gone wrong in a part of a question, the work from there on is worthless so that no more marks can sensibly be given. On the other hand, when two or more steps are successfully run together by the candidate, the earlier marks are implied and full credit must be given.
- e The abbreviation FT implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A and B marks are given for correct work only – differences in notation are of course permitted. A (accuracy) marks are not given for answers obtained from incorrect working. When A or B marks are awarded for work at an intermediate stage of a solution, there may be various alternatives that are equally acceptable. In such cases, what is acceptable will be detailed in the mark scheme. If this is not the case please, escalate the question to your Team Leader who will decide on a course of action with the Principal Examiner.
Sometimes the answer to one part of a question is used in a later part of the same question. In this case, A marks will often be 'follow through'. In such cases you must ensure that you refer back to the answer of the previous part question even if this is not shown within the image zone. You may find it easier to mark follow through questions candidate-by-candidate rather than question-by-question.
- f Unless units are specifically requested, there is no penalty for wrong or missing units as long as the answer is numerically correct and expressed either in SI or in the units of the question. (e.g. lengths will be assumed to be in metres unless in a particular question all the lengths are in km, when this would be assumed to be the unspecified unit.) We are usually quite flexible about the accuracy to which the final answer is expressed; over-specification is usually only penalised where the scheme explicitly says so. When a value is given in the paper only accept an answer correct to at least as many significant figures as the given value. This rule should be applied to each case. When a value is not given in the paper accept any answer that agrees with the correct value to 3 s.f. Follow through should be used so that only one mark is lost for each distinct accuracy error, except for errors due to premature approximation which should be penalised only once in the examination. E marks will be lost except when results agree to the accuracy required in the question.
- g Rules for replaced work: if a candidate attempts a question more than once, and indicates which attempt he/she wishes to be marked, then examiners should do as the candidate requests; if there are two or more attempts at a question which have not been crossed out, examiners should mark what appears to be the last (complete) attempt and ignore the others. NB Follow these maths-specific instructions rather than those in the assessor handbook.
- h For a genuine misreading (of numbers or symbols) which is such that the object and the difficulty of the question remain unaltered, mark according to the scheme but following through from the candidate's data. A penalty is then applied; 1 mark is generally appropriate, though this may differ for some units. This is achieved by withholding one A mark in the question. Marks designated as cao may be awarded as long as there are no other errors. E marks are lost unless, by chance, the given results are established by equivalent working. 'Fresh starts' will not affect an earlier decision about a misread. Note that a miscopy of the candidate's own working is not a misread but an accuracy error.
- i If a graphical calculator is used, some answers may be obtained with little or no working visible. Allow full marks for correct answers (provided, of course, that there is nothing in the wording of the question specifying that analytical methods are required). Where an answer is wrong but there is some evidence of method, allow appropriate method marks. Wrong answers with no supporting method score zero. If in doubt, consult your Team Leader.
- j If in any case the scheme operates with considerable unfairness consult your Team Leader.

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
1	(a)	$-4+1+k=0$ $k=3$	M1 A1 [2]	1.1a 1.1	Consideration of i -component (allow sign errors) Sight of 3 scores both marks	$k=-3$ with no working scores no marks
1	(b)	e.g. taking moments about O: $4(k) - 3(2)$ 6 clockwise	M1 A1 B1 [3]	1.1a 1.1 2.5	Taking moments correctly about any point with correct number of terms oe (could be seen on a diagram)	
2		$[\rho]=ML^{-3}$ $[u]=LT^{-1}$ $[\mu]=[\rho ul]=(ML^{-3})(LT^{-1})L$ $[\mu]=ML^{-1}T^{-1}$	B1 B1 M1 A1 [4]	1.2 1.2 1.1 1.1	Rearrange correctly to make μ the subject and use the fact that R is dimensionless and substitute their $[\rho]$ and $[u]$ SC: B2 for $kg\ m^{-1}s^{-1}$	Condone lower case

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
3	(a)	$-8\mathbf{i} + 10\mathbf{j} = 2(\mathbf{v} - (3\mathbf{i} - 2\mathbf{j}))$ $\mathbf{v} = -\mathbf{i} + 3\mathbf{j}$ $(\mathbf{v} =) \sqrt{(-1)^2 + 3^2}$ $ \mathbf{v} = \sqrt{10}$	M1* A1 M1dep* A1 [4]	3.3 1.1 1.1 1.1	Use of impulse = change of momentum – must be using $m = 2$ oe (e.g. as a column vector) Correct method for either $ \mathbf{v} $ or $ \mathbf{v} ^2$ from their $ \mathbf{v} $ oe (awrt 3 sf)	Must be using subtraction 3.162277...
3	(b)	The ball is modelled as a particle	B1 [1]	3.5b	The impact of the ball and bat is instantaneous	
4	(a)	$(2.5a)(20a^2) + \left(5a + \frac{1}{3}a\right)\left(\frac{1}{2}(4a)(a)\right) = \dots$ $\bar{x}\left(20a^2 + \frac{1}{2}(4a)(a)\right)$ $\bar{x} = \frac{91}{33}a$	M1 A1 A1 A1 [4]	2.1 1.1 1.1 2.2a	Table of values idea – correct number of terms, dimensionally consistent Must be exact and must come from exact working	Allow one a slip – be on the look out for moments about F and C For reference only: 2.757575...
4	(b)	$\tan \theta = \frac{2a}{5a - \bar{x}}$ $\theta = 41.7^\circ$	M1 A1 [2]	1.1 1.1	Tan of a relevant angle; allow reciprocal oe (radians: 0.728317...) – answer correct to at least 3 sf	M0 for $\tan \theta = \frac{2a}{\bar{x}}$ 41.729512...

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
5	(a)	$\dot{\mathbf{r}}(t) = 3\mathbf{i} - 6e^{-3t}\mathbf{j}$ $\dot{\mathbf{r}}(0) = 3\mathbf{i} - 6\mathbf{j}$ $KE = \frac{1}{2}(4)(3^2 + 6^2)$ 90 (J)	M1* M1dep* M1dep* A1 [4]	3.1b 3.4 3.3 1.1	Attempt at differentiation – must be of the form $3\mathbf{i} + ke^{-3t}\mathbf{j}$ where $k \neq 0$ Substitute $t = 0$ into their $\dot{\mathbf{r}}(t)$ Correct method for finding KE with their $\dot{\mathbf{r}}(0)$	Dependent on first two M marks
5	(b)	$18e^{-3t} = 2$ $e^{-3t} = \frac{1}{9}$ $-3t = \ln\left(\frac{1}{9}\right) \Rightarrow t = \dots$ $t = 0.732$	M1* M1dep* A1 [3]	3.4 1.1 1.1	Differentiating their $\dot{\mathbf{r}}(t)$ and equating to 2 Correct method (i.e. taking logs correctly) to find t oe e.g. $\frac{1}{3}\ln 9$ - if not given exact then must be given to at least 2 sf	Their acceleration must be of the form $k_1e^{-3t}\mathbf{j}$ 0.7324081...

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
6	$mga = \frac{1}{2}mv^2$ $v^2 = 2ga \text{ or } v = \sqrt{2ga}$ $\frac{1}{2}mv_Q + mv_P = m\sqrt{2ga}$ $v_Q - v_P = -e(0 - \sqrt{2ga})$ $v_Q = \sqrt{2ga} \text{ or } \frac{1}{2}\left(\frac{1}{2}m\right)v_Q^2 = \frac{1}{2}mga$ $\left(v_P = \frac{1}{2}\sqrt{2ga} \text{ or } v_P = \frac{\sqrt{2ga}}{3}(2-e)\right)$ $\sqrt{2ga} - \frac{1}{2}\sqrt{2ga} = e(\sqrt{2ga}) \text{ or}$ $\frac{1}{2}\left(\frac{1}{2}m\right)\left(\frac{2}{3}\sqrt{2ga}(1+e)\right)^2 = \frac{1}{2}mga$ $e = \frac{1}{2}$	<p>M1*</p> <p>A1</p> <p>M1*</p> <p>M1*</p> <p>B1</p> <p>M1dep*</p> <p>A1</p> <p>[7]</p>	<p>3.3</p> <p>1.1</p> <p>3.3</p> <p>3.3</p> <p>3.3</p> <p>2.1</p> <p>2.2a</p>	<p>Equating KE gained for P with the PE lost</p> <p>v or v^2 of P before impact</p> <p>Attempt at conservation of momentum – correct number of terms – must be using their speed of P before impact in terms of g and a</p> <p>Attempt at Newton’s experimental law – correct number of terms and consistent with CLM – must be using their speed of P before impact in terms of g and a</p> <p>www where v_Q is the speed of Q after impact – for reference</p> <p>$v_Q = \frac{2}{3}\sqrt{2ga}(1+e)$</p> <p>Where first v_P expression comes from</p> <p>$\frac{1}{2}mv_Q + mv_P = m\sqrt{2ga}$ and $v_Q = \sqrt{2ga}$</p> <p>Setting up an equation involving g, a and e – dependent on all previous M marks only and must have found v_P and/or v_Q from a correct method</p>	<p>v is the speed of P before impact</p> <p>Correct masses for P and Q – note that v_Q may already have been substituted</p> <p>This mark may be earned later after v_Q and v_P have been found</p> <p>Condone $\frac{1}{2}mv_Q^2 = mga$</p> <p>No marks for these</p> <p>Either substituting into NEL or considering energy of Q after collision</p>

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
NOTE THAT THERE ARE TWO PAGES FOR THIS QUESTION – PLEASE ENSURE BOTH ARE CHECKED					
7	<p>DR</p> $V = \pi \int_0^{\ln 2} \left(e^{\frac{3}{2}y} \right)^2 dy$ $= \pi \left[\frac{1}{3} e^{3y} \right]_0^{\ln 2}$ $= \frac{1}{3} \pi (e^{3 \ln 2} - e^0) = \frac{7}{3} \pi$ $V\bar{y} = \pi \int_0^{\ln 2} y \left(e^{\frac{3}{2}y} \right)^2 dy$ $= \pi \left\{ \left[\frac{1}{3} y e^{3y} \right]_0^{\ln 2} - \frac{1}{3} \int_0^{\ln 2} e^{3y} dy \right\}$ $= \pi \left[\frac{1}{3} y e^{3y} - \frac{1}{9} e^{3y} \right]_0^{\ln 2}$ $\bar{y} = \frac{\frac{8}{3} \ln 2 - \frac{7}{9}}{\frac{7}{3}}$ $\bar{y} = \frac{8}{7} \ln 2 - \frac{1}{3}$	<p>M1*</p> <p>A1</p> <p>A1</p> <p>M1*</p> <p>A2</p> <p>M1dep*</p> <p>A1</p> <p>[8]</p>	<p>1.1</p> <p>1.1</p> <p>1.1</p> <p>2.1</p> <p>1.1</p> <p>1.1</p> <p>1.1</p> <p>2.2a</p>	<p>For $\int \left(e^{\frac{3}{2}y} \right)^2 dy$ or $\int \left(e^{\frac{3}{2}y} \right)^2 dy$</p> <p>For $\frac{1}{3} e^{3y}$</p> <p>For correct substitution of limits and removing of logs</p> <p>For $\int yx^2 dy$ leading to $= \pm \alpha y e^{3y} \pm \beta \int e^{3y} dy$ or consistent with their V if using $\int \left(e^{\frac{3}{2}y} \right)^2 dy$</p> <p>Both terms integrated correctly (A1 for one error)</p> <p>M1 for $\bar{y} = \frac{V\bar{y}}{V}$ - dependent on both previous M marks</p> <p>oe</p>	<p>Limits not required for M and first A mark</p> <p>Must see one line of working from integrated expression to answer</p> <p>Clear indication of integrating exponential term and differentiating y term</p> <p>Limits not required for M mark and both A marks</p> <p>Must have used correct limits correctly</p> <p>Allow absence of π throughout</p>

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance
8	(a)	Driving force = $\frac{25000}{v}$ or $\frac{25000}{7}$	B1	1.2	
		$800g \sin 5$	B1	1.1	Not for $mg \sin 5$ - award when value for m substituted
		$\frac{25000}{v} - 750 - 800g \sin 5 = 800a$	M1	3.3	N2L with either 3 or 4 terms – allow for the M mark $D - 750 - 800g \sin 5 = 800a$ or $D - 750 - 800g \sin 5 = 0$
		$v = 7 \Rightarrow a = 2.67 \text{ m s}^{-2}$	A1	1.1	Answer to least 3 sf
		$a = 0 \Rightarrow v = 17.4 \text{ m s}^{-1}$	A1	1.1	Answer to least 3 sf
			[5]		
8	(b)	WD by car = 25000(10.4)	B1	1.1	260000
		WD against resistance = 750(131)	B1	1.1	98250
		Change in PE = $800g(131 \sin 5)$	B1	1.1	89512.4340...
		Change in KE = $\pm \frac{1}{2}(800)(v^2 - 7^2)$	B1	1.1	Use of correct formula for KE
		$\frac{1}{2}(800)(v^2 - 7^2) + 800g(131 \sin 5)$	M1	3.3	Use of work-energy principle, all terms present – all values (condone g) substituted or implied by later working (so not in terms of m but award when m substituted or implied)
		$= (25000)(10.4) - 750(131)$			
		$v = 15.2 \text{ m s}^{-1}$	A1	2.2a	Answer to least 3 sf
			[6]		

Or implied by their answer
Condone sign errors and sin/cos confusion – lhs must be a weight component and the rhs must be mass only
2.67265943...
17.442253...

Not for $mg(131 \sin 5)$ - however, can be awarded if m implied or substituted later
As above - must use value for m at some pt.
Allow sign errors but must be a change in KE (so must imply subtraction of the two KE terms)
15.1523567...

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
8	(b)	<p>ALT</p> $x = \int \frac{800v}{\frac{25000}{v} - 750 - 800g \sin 5} dv \text{ or}$ $t = \int \frac{800}{\frac{25000}{v} - 750 - 800g \sin 5} dv$			<p>Using diff. equations</p> <p>Award B1 for either of these two integrals (allow numerical equivalents)</p> <p>Then the remaining 5 marks are for the correct answer of 15.2 (no interim marks after the first B mark)</p>	<p>So may have attempted to simplify the constant terms</p>
9	(a)	Initial PE = $-mgl \cos \alpha$, KE = 0	B1	1.1	<p>oe – other reference levels for GPE = 0 (e.g. $mgl(1 - \cos \alpha)$ using a reference level of l below 0)</p>	KE = 0 can be implied

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
		<p>At angle θ, PE = $-mgl \cos \theta$, KE = $\frac{1}{2}mv^2$</p> $\frac{1}{2}ml^2 \left(\frac{d\theta}{dt} \right)^2 = mgl(\cos \theta - \cos \alpha)$ $\left(\frac{d\theta}{dt} \right)^2 = \frac{2g}{l} \cos \theta - \frac{2g}{l} \cos \alpha$	<p>B1</p> <p>M1</p> <p>A1</p> <p>[4]</p>	<p>1.1</p> <p>3.3</p> <p>1.1</p>	<p>Or B1 for KE = $\frac{1}{2}mv^2$ and B1 for PE = $\pm mgl(\cos \theta - \cos \alpha)$</p> <p>Note that $\frac{1}{2}mv^2 = \pm mgl(\cos \theta - \cos \alpha)$ implies both B marks</p> <p>Conservation of energy and use of $v = l \frac{d\theta}{dt}$</p> $k_1 = -\frac{2g}{l} \cos \alpha$	<p>Must be three terms but allow sign errors and sin/cos confusion</p>
9	(b)	$T - mg \cos \theta = ml\omega^2$ $T - mg \cos \theta = ml \left[\frac{2g}{l} (\cos \theta - \cos \alpha) \right]$ $T = 3mg \cos \theta - 2mg \cos \alpha$	<p>M1*</p> <p>M1dep*</p> <p>A1</p> <p>[3]</p>	<p>3.3</p> <p>3.4</p> <p>1.1</p>	<p>Applying N2L radially – correct number of terms – allow r for l</p> <p>M1 for substituting their v^2 or ω^2 consistently – must be using l not r</p> $k_2 = -2mg \cos \alpha$	<p>For acceleration allow $\frac{v^2}{l}$ or a</p> <p>But M0 if in terms of k_1</p>
9	(c)	$\cos \alpha \approx \cos \theta \approx 1$ $T \approx mg$	<p>M1</p> <p>A1</p> <p>[2]</p>	<p>3.1a</p> <p>2.2b</p>	<p>Setting $\cos \alpha$ and $\cos \theta$ equal to 1 in their expression for T</p>	

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
9 (d)	$2\left(\frac{d\theta}{dt}\right)\left(\frac{d^2\theta}{dt^2}\right) = \frac{2g}{l}(-\sin\theta)\left(\frac{d\theta}{dt}\right)$ $2\frac{d^2\theta}{dt^2} \approx -2\frac{g}{l}\theta$ $\frac{d^2\theta}{dt^2} \approx -\omega^2\theta \text{ where } \omega^2 = gl^{-1} \text{ so motion is}$ <p>approximately simple harmonic</p>	<p>M1*</p> <p>M1dep*</p> <p>A1</p> <p>[3]</p>	<p>3.4</p> <p>2.3</p> <p>2.4</p>	<p>Differentiate ω^2 with respect to t $\frac{d\theta}{dt}$ or $\dot{\omega}$ must appear on both sides before cancelling</p> <p>Cancel $\dot{\theta}$ terms and use small angle approximation for sin</p> <p>Must state that this is simple harmonic</p>	<p>Or use N2L tangentially (correct number of terms) e.g.</p> $-mg \sin \theta = ml \frac{d^2\theta}{dt^2} -$ <p>must be using θ</p>

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
10 (a)	$m\ddot{x} = -\frac{kmg}{x^2} - F$ $m\ddot{x} = -\frac{kmg}{x^2} - \mu mg$ $v \frac{dv}{dx} + \frac{kg}{x^2} + \mu g = 0 \Rightarrow \frac{1}{2} \frac{d}{dx}(v^2) + \frac{kg}{x^2} + \mu g = 0$ $\Rightarrow \frac{d}{dx}(v^2) + \frac{2kg}{x^2} + 2\mu g = 0$	<p>M1*</p> <p>M1dep*</p> <p>A1</p> <p>[3]</p>	<p>3.3</p> <p>3.4</p> <p>2.2a</p>	<p>N2L with correct number of terms – accept any form for a – M0 if $\frac{1}{2}m\ddot{x} = -\frac{kmg}{x^2} - F$ seen</p> <p>Use of $F = \mu R$ and substitute in their application of N2L</p> <p>Use of $a = v \frac{dv}{dx}$ to get to AG</p> <p>Note that $\frac{d}{dx}\left(\frac{1}{2}mv^2\right) = -\frac{kmg}{x^2} - F$ is equivalent to the first M mark (work-energy principle for a variable force)</p>	<p>Allow $a = \frac{1}{2} \frac{d}{dx}(v^2)$ or for acceleration allow any of $a = \frac{dv}{dt} = v \frac{dv}{dx} = \frac{d^2x}{dt^2}$ but not if circular motion implied</p> <p>Allow any correct form for a</p> <p>Must see the $\frac{1}{2} \frac{d}{dx}(v^2)$ term before AG</p>
10 (b)	<p>When $x = a, v^2 = 2gk\left(\frac{1}{a} - \frac{1}{a}\right) + 2\mu g(a - a) = 0$</p> <p>therefore $v = 0$ at $x = a$</p> $\frac{d}{dx}\left[2gk\left(\frac{1}{x} - \frac{1}{a}\right) + 2\mu g(a - x)\right] = -\frac{2gk}{x^2} - 2\mu g$ $\frac{d}{dx}(v^2) + \frac{2kg}{x^2} + 2\mu g$ $= -\frac{2gk}{x^2} - 2\mu g + \frac{2kg}{x^2} + 2\mu g = 0$	<p>B1</p> <p>M1</p> <p>A1</p> <p>[3]</p>	<p>3.5a</p> <p>2.1</p> <p>2.2a</p>	<p>Must explicitly show that when $x = a, v = 0$</p> <p>Differentiate v^2 to get two terms of the form $\pm \frac{\alpha}{x^2} \pm \beta$</p> <p>Correctly shown – could re-arrange their derivative for v^2 to the AG e.g. $\frac{d}{dx}(v^2) = -\frac{2gk}{x^2} - 2\mu g$ therefore $\frac{d}{dx}(v^2) + \frac{2gk}{x^2} + 2\mu g = 0$</p>	<p>Allow $v^2 = 0$</p> <p>Allow for differentiating v</p> <p>Must be = 0</p>

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
10	(b)	ALT			Solving differential equation	
		$v^2 = -\int \frac{2kg}{x^2} + 2\mu g dx \Rightarrow v^2 = \frac{2kg}{x} - 2\mu gx + c$	M1*		Separating and integrating to the form $v^2 = \pm \frac{\alpha kg}{x} \pm \beta \mu gx$	+c not required
		$v = 0$ at $x = a \Rightarrow c = 2\mu ga - \frac{2kg}{a}$	M1dep*		Using given conditions to find c	
		$v^2 = \frac{2kg}{x} - 2\mu gx + 2\mu ga - \frac{2kg}{a}$ $\Rightarrow v^2 = 2gk\left(\frac{1}{x} - \frac{1}{a}\right) + 2\mu g(a - x)$	A1		AG – so sufficient working must be shown	
10	(c)	Remain at A if $\frac{kmg}{a^2} \leq \mu mg$ $\mu \geq \frac{k}{a^2}$	M1 A1 [2]	3.1b 1.1	Considering relationship between attractive force and friction (accept any inequality or equals) cao	Allow x for a for the M mark

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
11	(a)	$0.2u_A + 0.6u_B = 0.2(-4) + 0.6(2)$ $-4 - 2 = -0.5(u_A - u_B)$ $\mathbf{u}_A = 9.5\mathbf{i} + 2\mathbf{j}$ $\mathbf{u}_B = -2.5\mathbf{i} + 3\mathbf{j}$	M1* A1 M1* A1 M1dep* A1 A1 [7]	3.3 1.1 3.3 1.1 2.1 2.2a 1.1	Attempt at conservation of linear momentum – correct number of terms Attempt at NLR – correct number of terms and speed of approach must be multiplied by coefficient of restitution oe $4 + 2 = 0.5(u_A - u_B)$. Must be consistent with CLM e.g. $0.2u_A - 0.6u_B = 0.2(-4) + 0.6(2)$ and $-4 - 2 = -0.5(u_A + u_B)$ would score the first 4 marks Solving simultaneous equations and correct j components (\mathbf{u}_A and \mathbf{u}_B must be of the form $\alpha\mathbf{i} + \beta\mathbf{j}$) ISW if speeds found after correct velocities	Let $\mathbf{u}_A = u_A\mathbf{i} + v_A\mathbf{j}$ and $\mathbf{u}_B = u_B\mathbf{i} + v_B\mathbf{j}$ No components of u_A and u_B for this mark (unless done correctly)

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
11 (b)	Velocity of B after impact is $-2e\mathbf{i} + 3\mathbf{j}$ $\frac{1}{2}(0.6)\left[(2^2 + 3^2) - ((\pm 2e)^2 + 3^2)\right] = 1.152$ $e = 0.2$	B1 M1 A1 [3]	3.1b 3.4 1.1	Condone $2e\mathbf{i} + 3\mathbf{j}$ (or for dividing their answer by 2 if using v for $2e$) Or for $\frac{1}{2}(0.6)\left[2^2 - (\pm 2e)^2\right] = 1.152$ or for $\frac{1}{2}(0.6)\left((\pm 2e)^2 + 3^2\right) = 2.748$ or for $\frac{1}{2}(0.6)(\pm 2e)^2 = 0.048$ - allow slip in one power only – must be using $2e$ (either seen or implied by dividing by 2)	May be seen in an equation for e Must be using speeds after collision (so must be using $2\mathbf{i} + 3\mathbf{j}$ or just $2\mathbf{i}$) and correct mass – if using say v for $2e$ then this mark can only be earned when dividing by 2
11 (c)	$\tan \alpha = \frac{2}{3}$ or $\tan \chi = \frac{3}{2}$ $\tan \beta = \frac{2e}{3}$ or $\tan \delta = \frac{3}{2e}$ Deflected angle = $\tan^{-1}\left(\frac{2}{3}\right) + \tan^{-1}\left(\frac{2e}{3}\right)$ 41.3°	B1 B1ft M1 A1 [4]	1.1 1.1 3.1b 1.1	In degrees: $\alpha = 33.6900675\dots$ With their e - if correct for reference $\beta = 7.59464336\dots$ or $180 - \left(\tan^{-1}\left(\frac{3}{2}\right) + \tan^{-1}\left(\frac{3}{2e}\right)\right)$ $41.284710\dots$ (correct to 1 d.p.)	Radians: $\alpha = 0.5880026\dots$ $\beta = 0.1325515\dots$ $0.72055413\dots$

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
12	(a)	$T_{AP} \cos \theta = T_{BP} \sin \theta + mg$ $T_{AP} \sin \theta + T_{BP} \cos \theta = m r \omega^2$ $T_{BP} \sin^2 \theta + mg \sin \theta + T_{BP} \cos^2 \theta = m r \omega^2 \sin \theta$ $T_{BP} = m(r\omega^2 \cos \theta - g \sin \theta)$	M1*	3.3	Resolving vertically – correct number of terms but allow sin/cos confusion and sign errors	Must be mg for the weight – condone any clear notation (even AP, BP) for the tension in the two strings – no marks if T is used for both strings Or correct method for solving simultaneous equations for T_{BP} Must show sufficient working as AG
			A1	1.1	N2L horizontally – correct number of terms – accept a for acceleration – allow sin/cos confusion and sign errors	
			M1*	3.3		
			A1	1.1	Correctly eliminating T_{AP} from their two equations	
			A1	2.2a	AG	
			[6]			
12	(b)	$T_{AP} \cos^2 \theta = m r \omega^2 \sin \theta - T_{AP} \sin^2 \theta + mg \cos \theta$ $T_{AP} = m(r\omega^2 \sin \theta + g \cos \theta)$	M1	1.1	Either substitutes given result into one of their two equation from (a) correctly to find T_{AP}	Or re-starts and eliminates T_{BP} using given answer in (a)
			A1	1.1	Correct answer with no working scores both marks	
			[2]			

Y421/01

Mark Scheme

June 2019

Question		Answer	Marks	AOs	Guidance	
12	(c)	$\sin \theta = \frac{3}{5}, \cos \theta = \frac{4}{5}, r = \frac{12}{5}a$ $T_{BP} > 0 \Rightarrow \left(\frac{12}{5}a\right)\left(\frac{4}{5}\right)\omega^2 - \frac{3}{5}g > 0$ $48a\omega^2 > 15g \Rightarrow 16a\omega^2 > 5g$	B1 M1 A1 [3]	1.1 3.1b 2.2a	Correct r and one of sin or cos correct Setting $T_{BP} > 0$ and substitute values AG	Allow = 0 Must show sufficient working as AG
12	(d)	$m(r\omega^2 \cos \theta - g \sin \theta) = m(r\omega^2 \sin \theta + g \cos \theta)$ $\frac{12}{5}a\Omega^2\left(\frac{4}{5}\right) - \frac{3}{5}g = \frac{12}{5}a\Omega^2\left(\frac{3}{5}\right) + \frac{4}{5}g$ $\Omega^2 = \frac{35g}{12a} \text{ or } \Omega = \sqrt{\frac{35g}{12a}}$ $\text{Period} = \frac{2\pi}{\Omega}$ $= 2\pi \sqrt{\frac{12a}{35g}}$	M1* M1dep* A1 M1dep* A1 [5]	3.1b 3.4 1.1 1.2 1.1	Setting $T_{AP} = T_{BP}$ Substituting values and obtain an equation in terms of a, g and Ω Could be implied in their working Dependent on both previous M marks oe	Condone use of ω for the angular speed

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
13 (a)	$4aR_C \sin \theta = aT \cos \theta$ $aT \cos \theta + 2aW \sin \theta + (4a - x)(4W \sin \theta) = 4aR_B \sin \theta$ $R_B + R_C = 4W + W$ $\frac{aT \cos \theta + 18aW \sin \theta - 4Wx \sin \theta}{4a \sin \theta} + \frac{T \cos \theta}{4 \sin \theta} = 5W$ $2aT \cos \theta = 2aW \sin \theta + 4Wx \sin \theta$ $\Rightarrow T = W \left(1 + \frac{2x}{a} \right) \tan \theta$	<p>M1*</p> <p>A1</p> <p>M1*</p> <p>A1</p> <p>B1</p> <p>M1dep*</p> <p>A1</p> <p>[7]</p>	<p>3.3</p> <p>1.1</p> <p>1.1</p> <p>3.3</p> <p>2.1</p> <p>2.2a</p>	<p>Moments about A for AC – correct number of terms – allow sin/cos confusion and sign errors</p> <p>Moments about A for AB – correct number of terms – allow sin/cos confusion and sign errors</p> <p>Resolving vertically</p> <p>Correct method to eliminate R_B and R_C to obtain a linear equation in T</p> <p>AG</p>	<p>R_C is the normal contact force at C</p> <p>R_B is the normal contact force at B</p> <p>Dependent on all previous M marks and B mark</p> <p>Sufficient working must be shown as AG</p>

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
13 (b)	$DE^2 = a^2 + a^2 - 2(a)(a)\cos 2\theta$ $T = \frac{W}{0.25a}(DE - 0.25a) \text{ or}$ $T = \frac{W}{0.125a}(0.5DE - 0.125a)$ $W\left(1 + \frac{2x}{a}\right)\tan \theta = \frac{4W}{a}\left(\sqrt{2a^2 - 2a^2 \cos 2\theta} - \frac{1}{4}a\right)$ $\left(1 + \frac{2x}{a}\right)\tan \theta = \frac{4}{a}\left(2a \sin \theta - \frac{1}{4}a\right)$ $x = \frac{1}{2}a(8\cos \theta - \cot \theta - 1)$	<p>B1</p> <p>M1</p> <p>A1</p> <p>M1</p> <p>A1</p> <p>[5]</p>	<p>3.1a</p> <p>3.3</p> <p>1.1</p> <p>3.1a</p> <p>2.2a</p>	<p>Correct application of cosine rule for triangle DAE</p> <p>Correct application of Hooke's law for their extension</p> <p>Or A2 (rather than the next M) for $W\left(1 + \frac{2x}{a}\right)\tan \theta = \frac{4W}{a}\left(2a \sin \theta - \frac{1}{4}a\right)$ or $W\left(1 + \frac{2x}{a}\right)\tan \theta = \frac{8W}{a}\left(a \sin \theta - \frac{1}{8}a\right)$</p> <p>Correct use of double-angle formula to give an equation in terms of x, a and θ</p> <p>AG</p>	<p>B1 for $DE = 2a \sin \theta$ or $\frac{1}{2}DE = a \sin \theta$</p> <p>Condone x or e for extension</p> <p>AG so sufficient working must be shown</p>
13 (c)	DR				

Y421/01

Mark Scheme

June 2019

Question	Answer	Marks	AOs	Guidance	
	$\frac{dx}{d\theta} = \frac{a}{2}(-8\sin\theta + \cos\theta \sec^2\theta) = 0$ $\sin^3\theta = \frac{1}{8} \Rightarrow \theta = \frac{\pi}{6}$ $x = \frac{1}{2}a \left(8\cos\left(\frac{\pi}{6}\right) - \cot\left(\frac{\pi}{6}\right) - 1 \right)$ $x = \frac{3\sqrt{3}-1}{2}a$ $\left. \frac{d^2x}{d\theta^2} \right _{\theta=\frac{\pi}{6}} = \frac{a}{2} \left(-8\cos\left(\frac{\pi}{6}\right) - 2 \left(\cos\theta \sec^2\left(\frac{\pi}{6}\right) \cot\left(\frac{\pi}{6}\right) \right) \right)$ $= -6a\sqrt{3} < 0 \text{ therefore maximum}$	<p>M1*</p> <p>A1</p> <p>M1dep*</p> <p>A1</p> <p>A1</p> <p>[5]</p>	<p>1.1</p> <p>1.1</p> <p>3.4</p> <p>1.1</p> <p>3.2a</p>	<p>Attempt differentiation and set equal to zero – must be of the form $\pm 8\sin\theta \pm \cos\theta \sec^2\theta$ with no extra terms www</p> <p>Substitute their value of θ and obtain a value for x</p> <p>2.10a (allow 2.1a)</p> <p>Correctly showing that value of x is a maximum (condone in terms of degrees) $= -10.39...a$</p>	<p>Allow in degrees throughout (30)</p> <p>For reference: 2.098076...a Or equivalent justification that this value is a maximum</p>

OCR (Oxford Cambridge and RSA Examinations)
The Triangle Building
Shaftesbury Road
Cambridge
CB2 8EA

OCR Customer Contact Centre

Education and Learning

Telephone: 01223 553998

Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

Oxford Cambridge and RSA Examinations
is a Company Limited by Guarantee
Registered in England
Registered Office; The Triangle Building, Shaftesbury Road, Cambridge, CB2 8EA
Registered Company Number: 3484466
OCR is an exempt Charity

OCR (Oxford Cambridge and RSA Examinations)
Head office
Telephone: 01223 552552
Facsimile: 01223 552553

© OCR 2019

