

General Certificate of Education (A-level)
June 2013

**Physics A** 

PHA<sub>5</sub>D

(Specification 2450)

Unit 5D: Nuclear and Thermal Physics

Turning Points in Physics

# **Final**

Mark Scheme

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all examiners participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for standardisation each examiner analyses a number of students' scripts: alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, examiners encounter unusual answers which have not been raised they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available from: aga.org.uk

Copyright © 2013 AQA and its licensors. All rights reserved.

#### Copyright

AQA retains the copyright on all its publications. However, registered schools/colleges for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

The Assessment and Qualifications Alliance (AQA) is a company limited by guarantee registered in England and Wales (company number 3644723) and a registered charity (registered charity number 1073334).

Registered address: AQA, Devas Street, Manchester M15 6EX.

# Section A – Nuclear and Thermal Physics

Question	Part	Sub Part	Marking Guidance	Mark	Comments
1	(a)	(i)	1/12 the mass of an (atom) of ${}^{12}_{6}\mathrm{C}$ / carbon-12 / C12 $\checkmark$	1	a reference to a nucleus loses the mark
1	(a)	(ii)	separated nucleons have a greater mass ✓ (than when inside a nucleus)  because of the (binding) energy <u>added</u> to <u>separate</u> the nucleons or energy is <u>released</u> when a nucleus is <u>formed</u> (owtte) ✓	2	an answer starting with 'its' implies the nucleus marks are independent direction of energy flow or work done must be explicit
1	(b)		nuclei need to be <u>close together</u> (owtte) for the Strong Nuclear Force to be involved or for fusion to take place ✓ but the electrostatic/electromagnetic force is repulsive (and tries to prevent this) ✓ (if the temperature is high then) the nuclei have (high) kinetic energy/speed (to overcome the repulsion) ✓	3	e.g. first mark – within the range of the SNF  3 <sup>rd</sup> mark is for a simple link between temperature and speed/KE
1	(c)	(i)	15 $\checkmark$ $e^{+} \checkmark (\text{or } \beta^{+}, {}_{1}^{0}\beta, {}_{1}^{0}e)$ 12 $\checkmark$	3	give the middle mark easily for any e or $\beta$ with a + in any position

1	(c)	(ii)	$\Delta$ mass = $4 \times 1.00728 - 4.00150 - (2 \times 9.11 \times 10^{-31}/1.661 \times 10^{-27})$ or $\Delta$ mass = $\{4 \times 1.00728 - 4.00150 - 2 \times 0.00055\}$ (u) $\checkmark$ $\Delta$ mass = $0.02652$ (u) $\checkmark$ $\Delta$ binding energy (= $0.02652 \times 931.5$ ) {allow 931.3} $\Delta$ binding energy = $24.7$ MeV $\checkmark$	3	$\begin{array}{l} (4\times1.00728=4.02912)\\ 1^{st} \ mark - correct \ subtractions \ in \ any\\ \ consistent \ unit. \ use \ of \ m_p = 1.67\times10^{-27} \ kg\\ \ will \ gain \ this \ mark \ but \ will \ not \ gain \ the \ 2^{nd}\\ \ as \ it \ will \ not \ produce \ an \ accurate \ enough\\ \ result\\ 2^{nd} \ mark - for \ calculated \ value\\ 0.02652u\\ 4.405\times10^{-29} \ kg\\ 3.364\times10^{-12} \ J\\ 3^{rd} \ mark - conversion \ to \ Mev\\ \ conversion \ mark \ stands \ alone\\ \ award \ 3 \ marks \ for \ answer \ provided \ some\\ \ working \ shown - no \ working \ gets \ 2 \ marks\\ \ (2sf \ expected) \end{array}$
2	(a)		insert control rods (further) into the nuclear core/reactor ✓ which will absorb (more) neutrons (reducing further fission reactions) ✓	2	a change must be implied for 2 marks marks by use of (further) or (more) allow answers that discuss shut down as well as power reduction  If a statement is made that is wrong but not asked for limit the score to 1 mark (e.g. wrong reference to moderator)
2	(b)		fission fragments/daughter products or spent/used fuel/uranium rods (allow) plutonium (produced from U-238) ✓	1	not uranium on its own
2	(c)	(i)	γ (electromagnetic radiation is emitted) ✓ as the energy gaps are large (in a nucleus) as the nucleus de-excites down discrete energy levels to allow the nucleus to get to the ground level/state ✓ mark for reason	2	A reference to $\alpha$ or $\beta$ loses this first mark $2^{\text{nd}}$ mark must imply energy levels or states

2	(c)	(ii)	momentum/kinetic energy is transferred (to the moderator atoms) or a neutron slows down/loses kinetic energy (with each collision) ✓ (eventually) reaching speeds associated with thermal random motion or reaches speeds which can cause fission (owtte)✓	2	
3		(i)	(heat supplied by glass = heat gained by cola) (use of $m_{\rm g} \ c_{\rm g} \ \Delta T_{\rm g} = m_{\rm c} \ c_{\rm c} \ \Delta T_{\rm c})$ 0.250 × 840 × (30.0 – $T_{\rm f}$ ) = 0.200 × 4190 × ( $T_{\rm f}$ – 3.0) $\checkmark$ (210 × 30 – 210 $t_{\rm f}$ = 838 $T_{\rm f}$ – 838 × 3) $T_{\rm f}$ = 8.4(1) (°C) $\checkmark$	2	1 <sup>st</sup> mark for RHS or LHS of substituted equation 2 <sup>nd</sup> mark for 8.4°C Alternatives: 8°C is substituted into equation (on either side shown will get mark) ✓ resulting in 4620J~4190J ✓ or 8°C substituted into LHS ✓ (produces $\Delta T$ = 5.5°C and hence) = 8.5°C ~ 8°C ✓ 8°C substituted into RHS ✓ (produces $\Delta T$ = 20°C and hence) = 10°C ~ 8°C ✓

3		(ii)	(heat gained by ice = heat lost by glass + heat lost by cola)  (heat gained by ice = $mc\Delta T + ml$ ) heat gained by ice = $m \times 4190 \times 3.0 + m \times 3.34 \times 10^5 \checkmark$ (heat gained by ice = $m \times 346600$ )  heat lost by glass + heat lost by cola = $0.250 \times 840 \times (8.41 - 3.0) + 0.200 \times 4190 \times (8.41 - 3.0) \checkmark$ (= $5670 \text{ J}$ ) $m = (-5670/346600) = 0.016 \text{ (kg)} \checkmark$ or (using cola returning to its original temperature) (heat supplied by glass = heat gained by ice) (heat gained by glass = $0.250 \times 840 \times (30.0 - 3.0)$ ) heat gained by glass = $5670 \text{ (J)} \checkmark$ (heat used by ice = $mc\Delta T + ml$ ) heat used by ice = $m(4190 \times 3.0 + 3.34 \times 10^5) \checkmark$ (= $m(346600)$ ) $m = (-5670/346600) = 0.016 \text{ (kg)} \checkmark$	3	NB correct answer does not necessarily get full marks $3^{rd}$ mark is only given if the previous 2 marks are awarded (especially look for $m \times 4190 \times 3.0$ ) the first two marks are given for the formation of the substituted equation not the calculated values if 8°C is used the final answer is 0.015 kg
4	(a)		molecules have negligible volume collisions are elastic the gas cannot be liquified there are no interactions between molecules (except during collisions) the gas obeys the (ideal) gas law / obeys Boyles law etc. at all temperatures/pressures any two lines 🗸 🗸	2	a gas laws may be given as a formula
4	(b)	(i)	$n (= PV/RT) = 1.60 \times 10^6 \times 0.200 / (8.31 \times (273 + 22)) \checkmark$ = 130 or 131 mol $\checkmark$ (130.5 mol)	2	

4	(b)	(ii)	mass = $130.5 \times 0.043 = 5.6$ (kg) $\checkmark$ (5.61kg) density (= mass/volume) = $5.61 / 0.200 = 28 \checkmark$ (28.1 kg m <sup>-3</sup> ) kg m <sup>-3</sup> $\checkmark$	3	allow ecf from bi a numerical answer without working can gain the first two marks
4	(b)	(iii)	$(V_2 = P_1 \ V_1 \ T_2 \ / \ P_2 \ T_1)$ $V_2 = 1.6 \times 10^6 \times .200 \times (273 - 50) \ / \ 3.6 \times 10^4 \times (273 + 22) \ \text{or} \ 6.7(2)$ $(m^3) \checkmark$ mass remaining = $5.61 \times 0.20 \ / \ 6.72 = 0.17 \ (kg) \checkmark \ (0.167 \ kg)$ or $n = (PV \ / \ RT = 3.6 \times 10^4 \times 0.200 \ / \ (8.31 \times (273 - 50)) = 3.88(5) \ (mol)$ $\checkmark$ mass remaining = $3.885 \times 4.3 \times 10^{-2} = 0.17 \ (kg) \checkmark$ $2 \ \text{sig figs} \checkmark$	3	allow ecf from bii  [reminder must see bii]  look out for  any 2 sf answer gets the mark

5		The mark scheme for this part of the question includes an overall assessment for the Quality of Written Communication (QWC).		
	QWC	Descriptor	Mark	
			range	
	High Level (Good to excellent)	The candidate refers to all the necessary apparatus and records the count-rate at various distances (or thicknesses of absorber). The background is accounted for and a safety precaution is taken. The presence of an $\alpha$ source is deduced from the rapid fall in the count rate at $2-5$ cm in air. The presence of a $\gamma$ source is deduced from the existence of a count-rate above background beyond 30 -50 cm in air (or a range in any absorber greater than that of beta particles, e.g. $3-6$ mm in Al) or from the intensity in air falling as an inverse square of distance or from an exponential fall with the thickness of a material e.g. lead. The information should be well organised using appropriate specialist vocabulary. There should only be one or two spelling or grammatical errors for this mark.	5-6	If more than one source is used or a different experiment than the question set is answered limit the mark to 4

Intermediate	The candidate refers to all the necessary apparatus and records the		
Level (Modest to adequate)	count-rate at different distances (or thicknesses of absorber). A safety precaution is stated. The presence of an $\alpha$ source is deduced from the rapid fall in the count rate at $2-5$ cm in air and the $\gamma$ source is deduced from the existence of a count-rate beyond 30 -50 cm in air (or appropriate range in any absorber, e.g. 3 -6 mm in Al). Some safety aspect is described. One other aspect of the experiment is given such as the background. <i>The grammar and spelling may have a few shortcomings but the ideas must be clear.</i>	3-4	To get an idea of where to place candidate look for 6 items:  1.Background which must be used in some way either for a comparison or subtracted appropriately  2.Recording some data with a named instrument
Low Level (Poor to limited)	The candidate describes recording some results at different distances (or thicknesses of absorber) and gives some indication of how the presence of $\alpha$ or $\gamma$ may be deduced from their range. Some attempt is made to cover another aspect of the experiment, which might be safety or background. There may be many grammatical and spelling errors and the information may be poorly organised.	1 - 2	3.Safety reference appropriate to a school setting – not lead lined gown for example 4.Record data with more than one absorber or distances 5.α source determined from results taken 6.γ source determined
	The description expected in a competent answer should include a coherent selection of the following points.   apparatus: source, lead screen, ruler, $\gamma$ ray and $\alpha$ particle detector such as a Geiger Muller tube, rate-meter or counter and stopwatch, named absorber of varying thicknesses may be used.   safety: examples include, do not have source out of storage longer than necessary, use long tongs, use a lead screen between source and experimenter.   measurements: with no source present switch on the counter for a fixed period measured by the stopwatch and record the number of counts or record the rate-meter reading   with the source present measure and record the distance between the source and detector (or thickness of absorber)   then switch on the counter for a fixed period measured by the stopwatch and record the number of counts or record the rate-meter reading   repeat the readings for different distances (or thicknesses of absorber).		from results taken this is a harder mark to achieve it may involve establishing an inverse square fall in intensity in air or an exponential fall using thicknesses of lead if a continuous distribution is not used an absorber or distance in air that would just eliminate $\beta$ (30-50cm air / 3-6mm Al) must be used with and without the source being present or compared to background

use of measurements:

for each count find the rate by dividing by the time if a rate-meter was not used

subtract the background count-rate from each measured count-rate to obtain the corrected count-rate

longer recording times may be used at longer distances (or thickness of absorber).

plot a graph of (corrected) count-rate against distance (or thickness of absorber) or refer to tabulated values

plot a graph of (corrected) count-rate against reciprocal of distance squared or equivalent linear graph to show inverse square relationship in air

analysis:

the presence of an  $\alpha$  source is shown by a rapid fall in the (corrected) count-rate when the source detector distance is between 2 – 5 cm in air

the presence of a  $\gamma$  source is shown if the <u>corrected</u> count-rate is still present when the source detector distance is greater than 30 cm in air (or at a range beyond that of beta particles in any other absorber, e.g. 3 mm in Al)

the presence of a  $\gamma$  source is best shown by the graph of (corrected) count-rate against reciprocal of distance squared being a straight line through the origin

# Section B – Turning Points in Physics

Question	Part	Sub- part	Marking guidance	Mark	Comment
	_			ı	
1	(a)	(i)	(at terminal velocity $v$ ), weight of droplet (or $mg$ ) = viscous drag (or $6\pi\eta r v$ ) $\checkmark$ mass ( $m$ ) of droplet = $(4\pi r^3/3) \times \rho$ , (where $r$ is the droplet radius) $\checkmark$ (therefore) $(4\pi r^3/3) \times \rho g = 6\pi\eta r v$ (or rearranged) $\checkmark$ (hence) $r = (9 \eta v /2 \rho g)^{1/2}$ = $\frac{9 \times 1.8 \times 10^{-5} \times 1.1 \times 10^{-4}}{2 \times 880 \times 9.8}$ ) gives $r = 1.0(3) \times 10^{-6}$ m $\checkmark$ note; some evidence of calculation needed to give final mark	4	Backward working 3 marks max; viscous force (= $6\pi\eta r  v$ ) = $6\pi \times 1.8 \times 10^{-5} \times 1.0 \times 10^{-6} \times 1.1 \times 10^{-4} = 3.7 \times 10^{-14}  \text{N}  \checkmark$ weight = mg = $\frac{4}{3}\pi  (1.0 \times 10^{-6})^3 \times 880 \times 9.8 = 3.6 \times 10^{-14}  \text{N}  \checkmark$ (allow 3.7) (therefore) viscous force = weight as required for constant velocity $\checkmark$ Allow final answer for $r$ in the range 1 to $1.05 \times 10^{-6}$ to any number of sig figs
1	(a)	(ii)	$m = ((4\pi r^3/3) \times \rho) = \frac{4}{3}\pi (1.0 \times 10^{-6})^3 \times 880) = 3.7 \times 10^{-15} \text{ kg} \checkmark$ ( or correct calculation of $6\pi \eta r v/g$ )	1	Allow ecf for <i>r</i> from a(i) in a correct calculation that gives <i>m</i> in the range 3.6 to 4.0 x 10 <sup>-15</sup> kg

			electric force ( or $QV/d$ ) = droplet weight ( or $mg$ ) $\checkmark$ $Q = \left(\frac{mgd}{V}\right) = \frac{3.7 \times 10^{-15} \times 9.8 \times 6.0 \times 10^{-3}}{680} \checkmark$ [or $Q$ (= viscous force $\times d/V$ $= 6\pi \times 1.8 \times 10^{-5} \times 1.0 \times 10^{-6} \times 1.1 \times 10^{-4} \times 6.0 \times 10^{-4} / 680 \checkmark$ ]		Allow ecf $m$ (or $r$ ) from a(ii) (or a(i)). Accept values in 1 <sup>st</sup> mark line Use of $e$ instead of $Q$ or $q = 2$ marks max For the 2nd mark, allow use of viscous force
1	(a)	(iii)	$Q = 3.2 \times 10^{-19} \text{C} \checkmark$	3	calculation. Use of viscous force method does not get 1st mark.
					If both methods are given and only one method gives $Q = ne$ (where $n = \text{integer } > 1$ ), ignore other method for 2nd mark and 3rd mark.
					For the final mark, Q must be within $n e \pm 0.2 \times 10^{-19}$ from a correct calculation.

1	(b)	The weight of the second droplet is greater than the maximum electric force on it $\checkmark$ Alternative for 1st mark; weight = drag force + elec force (owtte)  Scheme using V for next 5 marks; If $n = 1$ for the second droplet, pd to hold it = 1580 V (= $mgd/e$ ) $\checkmark$ which is not possible as $V \max = 1000 \ V \checkmark$ If $n = 2$ , it would be held at rest by a pd of 790 V (= 1580 /2 or $680 \times 4.3 / 3.7 \ V$ ) $\checkmark$ if $n > 2$ , it would be held at rest by a pd of less than 790 V (or $790 / n \ V$ ) $\checkmark$ So $n = 1(e)$ must be the droplet charge $\checkmark$	Max 4	Alternative schemes for last 5 marks  Q scheme Using QV/d = mg for a stationary droplet gives Q = mgd/V = 2.53 x 10 <sup>-19</sup> C ✓  which is not possible as Q = integer x e ✓  (so) Q (=ne) < 2.53 x 10 <sup>-19</sup> C ✓ owtte)  Calculation to show  Q= 1e fits above condition ✓  Q= 2e does not fit above condition ✓  F scheme;- Calc of mg to give 4.2 (±0.2)x10 <sup>-14</sup> N✓  Calc for Q = 1e of QV/d to give 2.6(±0.2) x 10 <sup>-14</sup> N✓  Calc for Q = 2e of QV/d to give 5.3 (±0.2)x 10 <sup>-14</sup> N ✓  mg> elec force for Q = 1e or <2e for Q=2e✓  So n = 1(e) must be the droplet charge ✓
2	(a)	(Matter) particles have wave-like properties (owtte) $\checkmark$ and an associated wavelength = $h/p$ where $p$ is the momentum of the particles $\checkmark$ .	2	Accept <i>mv</i> or mass x velocity in place of <i>p</i> Accept 'inversely proportional to momentum ( or <i>mv</i> )' after 'wavelength'

2	(b)	$E_{K} (= 0.021 \text{ eV}) = 0.021 \times 1.60 \times 10^{-19} \text{ or } 3.36 \times 10^{-21} \text{ J} \checkmark$ $(\text{Using } E_{K} = \frac{1}{2} \text{ m } v^{2} \text{ gives })$ $mv = (2 \text{ m } E_{K})^{1/2} = (2 \times 1.67(5) \times 10^{-27} \times 3.36 \times 10^{-21})^{1/2}$ $(= 3.35 \times 10^{-24} \text{ kg m s}^{-1}) \checkmark$ $[OR$ $v = (2 E_{K}/m)^{1/2} = (2 \times 3.36 \times 10^{-21}/\times 1.67(5) \times 10^{-27})^{1/2}$ $(= 2.0 \times 10^{3} \text{ m s}^{-1})$ $mv = (1.67(5) \times 10^{-27} \times 2.0 \times 10^{3} (= 3.35 \times 10^{-24} \text{ kg m s}^{-1})]$ $\lambda = \frac{h}{mv} (= \frac{6.63 \times 10^{-34}}{3.35 \times 10^{-24}}) = 1.88 \times 10^{-10} \text{ m} \checkmark$ $= 2.0 \times 10^{-10} \text{ m to 2 sf } \checkmark$	4	For 2nd mark, allow individual values of $e$ and $V$ in place of $E_{\rm K}$ value in data substitution  For 3rd mark, allow individual values of $e$ and $e$ in denominator  Alternative;  Correct use of 0.021 eV in $e$ = $e$
2	(c)	electron's momentum $(p)$ is the same (as that of the neutron) and its mass is (much) smaller than neutron mass $\checkmark$ kinetic energy = $p^2 / 2m$ so kinetic energy of electron is (much) greater $\checkmark$ $\frac{Alternative}{m}$ for $2^{nd}$ $\frac{m}{m}$ ; (so) electron's speed is (much) greater and as kinetic energy = $\frac{1}{2}$ $\frac{m}{v}$ , the electron's kinetic energy is (much) greater as $\frac{1}{2}$ is more significant than $m$ (here)(owtte)	2	$\frac{2^{nd} \ alternative}{\lambda = h / (2 \ mE_K)^{1/2}} \ so (same \ \lambda \ means) \ mE_K \ (in equation) is the same for electron as for the neutron) . So E_K is (much) greater as electron mass is (much) smaller than neutron mass (owtte) Note; allow use of eV in place of E_K if eV is identified as E_K.$

		Quality of written communication:  Good – Excellent	(5-6 marks)	
		The candidate provides a comprehensive, co logical explanation which recognises what a is and that the conditions for the formation of wave are present. They should know that no antinodes are formed at alternate positions a are equally spaced with nodes every half wa should know how the detector is used to loc of each node or antinode and how the wavel determined from the distance between two s They may know that the nodes can be located accurately than the antinodes and that their consitions should be as far apart as possible.	oherent and a stationary wave f a stationary des and along XY which velength. They ate the position ength is uch positions. ed more	For top band,  explanation = at least b and e  description = at least f, g,h   Explanation of stationary wave formation;  a. radio waves from the transmitter are reflected back towards the transmitter√  b. reflected and incident waves pass through each other √  c. both waves have same frequency (and speed) and amplitude√  d. superposition (of reflected and incident waves) occurs to form a stationary wave (as above) √
3	(a)	Their answer should be well-presented in ter punctuation and grammar.  Modest – Adequate  The candidate provides a logical explanation	(3-4 marks) 6	
		recognises what a stationary wave is and will conditions for the formation of a stationary with may know that nodes and antinodes are form positions along XY with nodes every half- was may know how the detector is used to locate each node or antinode and how the wavelend determined from the distance between two sometimes They may know that the nodes can be located accurately than the antinodes and that their opositions should be as far apart as possible. should be well-presented in terms of spelling and grammar.	ave are. They ned at alternate avelength. They the position of gth is uch positions. ed more chosen two Their answer	<ul> <li>e. (equally spaced) nodes and antinodes formed along XY√</li> <li>Description of measurement of wavelength;</li> <li>f. Detector signal is zero ( or least) along XY at nodes √</li> <li>g. distance between adjacent nodes is ½ λ √</li> <li>h. move detector along XY to measure distance between adjacent nodes and double to give the wavelength √</li> <li>i. measure distance over n nodes and divide</li> </ul>
		Poor to Limited	(1-2 marks)	by n-1 to give distance between adjacent nodes ✓
		The candidate may recognise that the reflect waves which then form a stationary wave pa		

incident waves. They may be unaware what the conditions for the formation of a stationary wave are and their understanding of nodes and antinodes may be poor. They may have some awareness that the stationary wave causes the detector signal to vary with position along XY and that the wavelength can be determined from this variation although they might not be able to link the wavelength to the changes of detector position correctly.

Their answer may lack coherence and may contain a significant number of errors in terms of spelling and punctuation.

# The explanations expected in a good answer should include most of the following physics ideas

#### Explanation of stationary wave formation ;-

- a. radio waves from the transmitter are reflected back towards the transmitter√
- reflected and incident waves pass through each other ✓
- c. both waves have same frequency (and speed) and amplitude√
- d. superposition (of reflected and incident waves) occurs to form a stationary wave (as above) ✓
- e. equally spaced nodes and antinodes formed along XY✓

## Description of measurement of wavelength;-

- f. Detector signal is zero ( or least) along XY at nodes
- g. distance between adjacent nodes is  $\frac{1}{2} \lambda \checkmark$
- h. move detector along XY to measure distance between adjacent nodes and double to give the wavelength ✓
- i. measure distance over n nodes and divide by n-1 to give distance between adjacent nodes ✓

#### For middle band,

explanation = at least any two of a-e description = at least any two of f-i

#### For lowest band,

Any 2 points , must be 1 of each for 2 marks

### Explanation of stationary wave formation ;-

- a. radio waves from the transmitter are reflected back towards the transmitter√
- b. reflected and incident waves pass through each other ✓
- c. both waves have same frequency (and speed) and amplitude√
- d. superposition (of reflected and incident waves) occurs to form a stationary wave (as above) ✓
- e. (equally spaced) nodes and antinodes formed along XY✓

# Description of measurement of wavelength;

- f. Detector signal is zero ( or least) along XY at nodes ✓
- g. distance between adjacent nodes is ½  $\lambda$  ✓
- h. move detector along XY to measure

			distance between adjacent nodes and double to give the wavelength ✓ i. measure distance over n nodes and by n-1 to give distance between adjacent nodes ✓	divide
3	(b)	Speed of radio waves (obtained by Hertz ) is the same as the speed of light ✓  Speed of electromagnetic waves (calculated or predicted by Maxwell) is the same as the speed of light ( or of radio waves) so radio waves are electromagnetic waves ✓	by 2	
4	(a)	(Using $m = \frac{m_o}{\sqrt{1 - \frac{v^2}{c^2}}}$ gives) $2 = \frac{1}{\sqrt{1 - \frac{v^2}{c^2}}}  \text{or } \sqrt{1 - \frac{v^2}{c^2}} = 0.5  \checkmark$ (Rearranging gives) $v \ (= \sqrt{1 - 0.5^2} \ c) = 0.866 \ c \text{ or } 2.6 \times 10^8 \ \text{m s}^{-1} \ \checkmark$	2 Accept either answer.	

4	(b)	curve starts at $v$ =0 , $m$ = $m$ 0 and rises smoothly $\checkmark$ curve passes through $2m$ 0 at $v$ = 0.87 $c$ ( $\pm$ 0.03 $c$ or in 2nd half of x-scale div containing 0.87c) $\checkmark$ curve is asymptotic at $v$ = $c$ (and does not cross or touch $v$ = $c$ or curve back) $\checkmark$	3	2nd mark ; ecf from 4a if plotted correctly 3rd mark ; There must be visible white space between the curve and the $v=c$ line; also, the curve must reach $7m_o$ at least.
4	(c)	Energy = $mc^2$ so (as $v \rightarrow c$ ) energy of particle increases as mass increases $\checkmark$ mass -> infinity as $v \rightarrow c$ so energy -> infinity which is (physically) impossible $\checkmark$ [OR for one mark only force = $ma$ so force increases as mass increases  Mass -> infinity as $v \rightarrow c$ so force -> infinity which is (physically) impossible $\checkmark$ ]	2	Alternative scheme for 1 mark only; mass infinite at $v = c$ which is (physically) impossible $\checkmark$