

Cambridge International AS & A Level

PHYSICS

Paper 3 Advanced Practical Skills 2 MARK SCHEME Maximum Mark: 40 9702/32 May/June 2023

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2023 series for most Cambridge IGCSE, Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

Cambridge International AS & A Level – Mark Scheme PUBLISHED

PMT

Generic Marking Principles

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always whole marks (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently, e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Cambridge International AS & A Level – Mark Scheme **PUBLISHED**

PMT

Science-Specific Marking Principles

- 1 Examiners should consider the context and scientific use of any keywords when awarding marks. Although keywords may be present, marks should not be awarded if the keywords are used incorrectly.
- 2 The examiner should not choose between contradictory statements given in the same question part, and credit should not be awarded for any correct statement that is contradicted within the same question part. Wrong science that is irrelevant to the question should be ignored.
- 3 Although spellings do not have to be correct, spellings of syllabus terms must allow for clear and unambiguous separation from other syllabus terms with which they may be confused (e.g. ethane / ethene, glucagon / glycogen, refraction / reflection).
- 4 The error carried forward (ecf) principle should be applied, where appropriate. If an incorrect answer is subsequently used in a scientifically correct way, the candidate should be awarded these subsequent marking points. Further guidance will be included in the mark scheme where necessary and any exceptions to this general principle will be noted.

5 <u>'List rule' guidance</u>

For questions that require *n* responses (e.g. State **two** reasons ...):

- The response should be read as continuous prose, even when numbered answer spaces are provided.
- Any response marked *ignore* in the mark scheme should not count towards **n**.
- Incorrect responses should not be awarded credit but will still count towards *n*.
- Read the entire response to check for any responses that contradict those that would otherwise be credited. Credit should **not** be awarded for any responses that are contradicted within the rest of the response. Where two responses contradict one another, this should be treated as a single incorrect response.
- Non-contradictory responses after the first *n* responses may be ignored even if they include incorrect science.

6 <u>Calculation specific guidance</u>

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g. $a \times 10^n$) in which the convention of restricting the value of the coefficient (a) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

7 <u>Guidance for chemical equations</u>

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

9702/32

May/June 2023	May/June 2	2023
---------------	------------	------

Question	Answer	Marks
1(a)	Final value of x with unit in range 29.0–31.0 cm.	1
	Value of θ to nearest degree and in the range 60–80°.	1
1(b)	Six sets of readings of x (different values) and θ with correct trend (as x increases θ increases) and without help from the Supervisor scores 4 marks, five sets scores 3 marks, etc.	4
	Range: $x_{\min} \leq 10.0 \text{ cm}$ and $x_{\max} \geq 55.0 \text{ cm}$.	1
	Column headings: Each column heading must contain a quantity and a unit where appropriate. The presentation of quantity and unit must conform to accepted scientific convention e.g. θ/\circ , x/cm . cos θ must not have a unit.	1
	Consistency: All values of <i>x</i> must be given to the nearest millimetre.	1
	Significant figures: Values of $\cos \theta$ given to 2 or 3 significant figures.	1
	Calculation: Values of cos θ calculated correctly.	1

Cambridge International AS & A Level – Mark Scheme PUBLISHED

May/June 2023

PMT

Question	Answer	Marks
1(c)(i)	Axes: Axes must be labelled with the correct quantities. Scales must be chosen so that the plotted points occupy at least half the graph grid in both <i>x</i> and <i>y</i> directions. Scale markings are no more than 2 cm apart (one large square). Sensible scales must be used. Scale must not be awkward (e.g. 3:10 or fractions).	1
	Plotting of points: All observations in the table must be plotted on the grid. Diameter of plotted points must be less than half a small square. Points must be plotted to an accuracy of half a small square in both <i>x</i> and <i>y</i> directions.	1
	Quality: Trend of points must be negative. All points in the table must be plotted on the grid. It must be possible to draw a straight line that is within ± 4.0 cm (to scale) on the x-axis of all plotted points.	1
1(c)(ii)	Line of best fit: 'Best fit' is judged by the balance of all points on the grid (at least 5 points) about the candidate's line. There must be an even distribution of points either side of the line along the full length. Lines must not be kinked or thicker than half a square. Some candidates may choose to identify an anomalous point. If they identify one point as anomalous (e.g. by circling or	1
	labelling) then this point is to be disregarded when judging the line of best fit. There must be at least 5 points left after the anomalous point is disregarded.	
1(c)(iii)	Gradient: The hypotenuse of the triangle used should be greater than half the length of the drawn line. Both read-offs must be accurate to half a small square in both <i>x</i> and <i>y</i> directions. The method of calculation must be correct, not $\Delta x / \Delta y$. The gradient sign on the answer line must be consistent with the graph drawn.	1
	<i>y</i> -intercept: Intercept read directly from the graph, with read-off at $x = 0$, accurate to half a small square in <i>y</i> direction. or Correct read-off from a point on the line and substituted correctly into $y = mx + c$ or an equivalent expression. Read-off is accurate to half a small square in both <i>x</i> and <i>y</i> directions.	1

May/June 2023

9702/32

Question	Answer	Marks
1(d)	Value of $a =$ candidate's gradient and value of $b =$ candidate's intercept. Values must not be written as fractions or given to only one significant figure.	1
	Units for <i>a</i> and <i>b</i> correct and consistent with readings (e.g. cm^{-1} for <i>a</i> and no unit for <i>b</i>).	1
1(e)	Correct calculation of S with unit (e.g. $N m^{-1}$ or $N cm^{-1}$).	1

9702/32

May/June 2	2023
------------	------

Question	Answer	Marks
2(a)(i)	Value for D_1 to nearest mm and in range 4.0 cm $\leq D_1 \leq 6.0$ cm.	1
	Correct calculation of C.	1
2(a)(ii)	Justification for significant figures in C linked to significant figures in M_1 and D_1 .	1
2(a)(iii)	All values of <i>T</i> to nearest 0.01 s or all to the nearest 0.1 s, with unit.	1
	Evidence of repeat readings of <i>T</i> .	1
2(b)(i)	Value for D_2 that is greater than D_1 .	1
2(b)(ii)	Absolute uncertainty in D_2 in the range 0.2–0.5 cm. Correct method of calculation to find percentage uncertainty in D_2 , e.g. (absolute uncertainty / value from 2(b)(i)) × 100. If repeated readings have been taken, then the absolute uncertainty can be half the range (but not zero) provided the working is clearly shown.	1
2(b)(iii)	Correct calculation of new value of C.	1
2(b)(iv)	Value for <i>T</i> .	1
	New value of T greater than first T.	1
2(c)	Two values of <i>k</i> calculated correctly. The final <i>k</i> values must not be written as fractions or given to only one significant figure.	1
2(d)	Calculation of percentage difference between candidate's two <i>k</i> values. Comparison of percentage difference with 15% leading to a consistent conclusion.	1

May/June 2023

9702/32

we readings are not enough to draw a (valid) conclusion (not "not enough for accurate results", "few readings"). If ficult to measure <i>T</i> or time with a reason e.g. difficult to judge when mass hanger reaches the floor/difficult to judge art of descent of mass hanger. The or <i>T</i> is short so uncertainty in <i>T</i> is large or percentage uncertainty in <i>T</i> is large. If icult to measure D_1 or D_2 or diameter with a reason e.g. plastic tube gets in way of ruler/parallax error. If icult with D_2 with a reason e.g. inconsistent thickness of clay layer, thickness of clay layer varies. If icult to exactly judge 16 turns of the flywheel/difficult to exactly judge number of turns of the flywheel. ass hanger does not fall smoothly/consistently/hanger stops and starts. <i>to reach point up to a maximum of 4.</i> ke more readings and plot a graph or take more readings and compare <i>k</i> values (not "repeat readings" on its own).	
art of descent of mass hanger. me or <i>T</i> is short so uncertainty in <i>T</i> is large or percentage uncertainty in <i>T</i> is large. fficult to measure D_1 or D_2 or diameter with a reason e.g. plastic tube gets in way of ruler/parallax error. fficulty with D_2 with a reason e.g. inconsistent thickness of clay layer, thickness of clay layer varies. fficult to exactly judge 16 turns of the flywheel/difficult to exactly judge number of turns of the flywheel. ass hanger does not fall smoothly/consistently/hanger stops and starts. <i>t</i> for each point up to a maximum of 4.	
fficult to measure D_1 or D_2 or diameter with a reason e.g. plastic tube gets in way of ruler/parallax error. fficulty with D_2 with a reason e.g. inconsistent thickness of clay layer, thickness of clay layer varies. fficult to exactly judge 16 turns of the flywheel/difficult to exactly judge number of turns of the flywheel. ass hanger does not fall smoothly/consistently/hanger stops and starts. <i>as for each point up to a maximum of 4.</i>	
fficulty with D_2 with a reason e.g. inconsistent thickness of clay layer, thickness of clay layer varies. fficult to exactly judge 16 turns of the flywheel/difficult to exactly judge number of turns of the flywheel. ass hanger does not fall smoothly/consistently/hanger stops and starts. as for each point up to a maximum of 4.	
fficult to exactly judge 16 turns of the flywheel/difficult to exactly judge number of turns of the flywheel. ass hanger does not fall smoothly/consistently/hanger stops and starts.	
ass hanger does not fall smoothly/consistently/hanger stops and starts.	
for each point up to a maximum of 4.	
ke more readings and plot a graph or take more readings and compare k values (not "repeat readings" on its own).	
e video/record/film (descent of mass hanger in view) and timer in view/view frame-by-frame.	
ethod to increase T or time e.g. use longer drop/decrease mass of mass hanger/increase number of turns.	
e (vernier) calipers.	
ld a roller on the modelling clay while flywheel is turned/use a preformed ring of clay/use a mould/flatten clay tween boards.	
e height change (preset height) instead of turns e fiducial mark and line up with slot on mass/mark on mass.	
proved method to allow hanger to fall smoothly e.g. support bamboo rod at both ends/use tube with circular cross-	
e e e	d a roller on the modelling clay while flywheel is turned/use a preformed ring of clay/use a mould/flatten clay veen boards. height change (preset height) instead of turns fiducial mark and line up with slot on mass/mark on mass.