

Cambridge International Examinations

Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS 9702/03

Paper 3 Advanced Practical Skills SPECIMEN MARK SCHEME For Examination from 2016

2 hours

MAXIMUM MARK: 40



2

1

(a)	Valu	ue of / recorded with consistent unit.	[1]		
(b)		sets of readings of <i>I</i> and <i>R</i> scores 5 marks; five sets scores 4 marks etc. or help from Supervisor –2 (setting up apparatus). Minor help from Supervisor –1.	[5]		
	Rar	nge of R includes 2.5 Ω and 40 Ω .	[1]		
	Eac The	umn headings: the column heading must contain a quantity and a unit. The presentation of quantity and unit must conform to accepted scientific convention, $1/I/A^{-1}$. Do not allow $1/I$ (A).	[1]		
		nsistency: values of / must be given to the same number of decimal places.	[1]		
	Sigi	nificant figures: nificant figures for every row of values of 1/I same as or one greater than I as orded in table. Accept three or four s.f. only.	[1]		
		Calculation: All values of 1/I calculated correctly.			
(c)	(i)	Axes: Sensible scales must be used, no awkward scales (e.g. 3:10). Scales must be chosen so that the plotted points occupy at least half the graph grid in both <i>x</i> and <i>y</i> directions Scales must be labelled with the quantity that is being plotted. Scale markings should be no more than three large squares apart.	[1]		
		Plotting of points: All observations in the table must be plotted. Diameter of points must be ≤ half a small square (no "blobs"). Work to an accuracy of half a small square.	[1]		
		Quality: All points in the table must be plotted (at least 5) for this mark to be awarded. Scatter of points must be less than 0.1 m ⁻¹ from a straight line on the 1/ <i>I</i> axis.	[1]		
	(ii)	Line of best fit: Judge by balance of all points on the grid about the candidate's line (at least 5 points). There must be an even distribution of points either side of the line along the full length. Allow one anomalous point only if clearly indicated (i.e. circled or labelled) by candidate.	h.		

Line must not be kinked or thicker than half a small square.

© UCLES 2014 9702/03/SM/16

		(iii)	Gradient: The hypotenuse of the triangle must be at least half the length of the drawn line. Both read-offs must be accurate to half a small square in both the <i>x</i> and <i>y</i> directions. The method of calculation must be correct.	[1]	
			<i>y</i> -intercept: Either: Correct read-off from a point on the line and substituted into $y = mx + c$. Read-off must be accurate to half a small square in both x and y directions. Or: Correct read-off of the intercept directly from the graph.	[1]	
	(d)	Valu	the of $E=1/(\text{candidate's gradient})$. The of $r=E\times(\text{candidate's intercept})$ or the of $r=(\text{candidate's intercept})$ or $r=(\text{candidate's intercept})$ or $r=(\text{candidate's intercept})$	[1] [1]	
	(e)	Line	e Z drawn with smaller gradient and same <i>y</i> -intercept.	[1]	
			[Total:	20]	
2	(a)	Mea Mea	asurement of mass of salt and container A. asurement of mass of salt and container B. asurement of mass of empty container. rect calculation of $m_{\rm A}$ and $m_{\rm B}$ by subtraction of mass of container.	[1] [1] [1]	
	(b)	(i)	Measurement of t_A .	[1]	
		(ii)	Measurement of $t_{\rm B}$.	[1]	
			Repeated measurements taken (here or in (i)). Quality: $t_{\rm B}=2t_{\rm A}\pm10\%$. (Do not allow this mark if the stopwatch has been misread.)	[1] [1]	
	(c)	Absolute uncertainty in t_A in the range 0.1–0.4 s. If repeated readings have been taker the absolute uncertainty can be half the range provided this is not zero. Correct method calculation to get percentage uncertainty.			
	(d)	(i)	One mass flow rate calculated correctly.	[1]	
			Second mass flow rate calculated correctly and a correct unit (g $\rm s^{-1}$ or kg $\rm s^{-1}$), consist with candidate's working.	tent [1]	
		(ii)	Sensible comment relating to the calculated mass flow rates, testing against a crite specified by the candidate.	rion [1]	

(e) (i) Relevant points might include:

[4]

Two readings are not enough to draw a valid conclusion.

Difficulty with removing finger and starting the stopwatch at the same time.

Length of pipe at bottom of funnel may affect results.

Salt may contain 'lumps' which affect the flow rate.

Moisture content of salt may affect flow rate.

Hard to see the point at which all the salt has passed out of the container.

Human error in starting/stopping the stopwatch.

Salt sticks to the sides of the funnel.

(ii) Relevant points might include:

[4]

Take many readings and plot a graph of the results.

Use greater masses of salt to increase t.

Greater masses reduce uncertainty in t.

Use mechanical method (joined to timer) to start the flow.

Use light gates to determine when salt ceases to pass out of the hole.

Use of a second person fully explained.

Do not allow "repeated readings".

Do not allow "use a computer to improve the experiment".

[Total: 20]

© UCLES 2014 9702/03/SM/16