

PHYSICS**9702/42**

Paper 4 A Level Structured Questions

May/June 2016

MARK SCHEME

Maximum Mark: 100

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2016 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42
1	(a) (i) gravitational force provides/is the centripetal force		B1
	same gravitational force (by Newton III)		B1 [2]
	(ii) $\omega = 2\pi/T$		C1
	$= 2\pi/(4.0 \times 365 \times 24 \times 3600)$		
	$= 5.0 (4.98) \times 10^{-8} \text{ rad s}^{-1}$		A1 [2]
	(b) (i) (centripetal force =) $M_A d \omega^2 = M_B (2.8 \times 10^8 - d) \omega^2$		
	or		
	$M_A d_A = M_B d_B$		C1
	$M_A/M_B = 3.0 = (2.8 \times 10^8 - d)/d$		C1
	$d = 7.0 \times 10^7 \text{ km}$		A1 [3]
	(ii) $GM_A M_B / (2.8 \times 10^{11})^2 = M_A d \omega^2$		B1
	$M_B = (2.8 \times 10^{11})^2 \times d \omega^2 / G$		
	$= (2.8 \times 10^{11})^2 \times (7.0 \times 10^{10}) \times (4.98 \times 10^{-8})^2 / (6.67 \times 10^{-11})$		C1
	$= 2.0 \times 10^{29} \text{ kg}$		A1 [3]
2	(a) (i) number of <u>atoms/nuclei</u> in 12 g of carbon-12		B1 [1]
	(ii) amount of substance		M1
	containing N_A (or 6.02×10^{23}) particles/molecules/atoms		
	or		
	which contains the same number of particles/atoms/molecules as there are atoms in 12 g of carbon-12		A1 [2]
	(b) $pV = nRT$		
	$2.0 \times 10^7 \times 1.8 \times 10^4 \times 10^{-6} = n \times 8.31 \times 290$, so $n = 149 \text{ mol}$ or 150 mol		A1 [1]
	(c) (i) V and T constant and so pressure reduced by 5.0%		
	pressure = $0.95 \times 2.0 \times 10^7$		C1
	or		
	calculation of new n (= 142.5 mol) and correct substitution into $pV = nRT$		(C1)
	pressure = $1.9 \times 10^7 \text{ Pa}$		A1 [2]

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42

- (ii) loss is $5/100 \times 150 \text{ mol} = 7.5 \text{ mol}$
or
 $\Delta N = 4.52 \times 10^{24}$ C1
- $t = (7.5 \times 6.02 \times 10^{23}) / 1.5 \times 10^{19}$
or
 $t = 4.52 \times 10^{24} / 1.5 \times 10^{19}$ C1
 $= 3.0 \times 10^5 \text{ s}$ A1 [3]
- 3 (a) no net energy transfer between the bodies
or
bodies are at the same temperature B1 [1]
- (b) (i) thermocouple, platinum/metal resistance thermometer, pyrometer B1 [1]
(ii) thermistor, thermocouple B1 [1]
- (c) (i) change = 11.5 K B1 [1]
(ii) final temperature = 311.2 K B1 [1]
- 4 (a) (i) $T = 0.60 \text{ s}$ and $\omega = 2\pi / T$ C1
 $\omega = 10(10.47) \text{ rad s}^{-1}$ A1 [2]
- (ii) energy = $\frac{1}{2}m\omega^2x_0^2$ or $\frac{1}{2}mv^2$ and $v = \omega x_0$ C1
 $= \frac{1}{2} \times 120 \times 10^{-3} \times (10.5)^2 \times (2.0 \times 10^{-2})^2$
 $= 2.6 \times 10^{-3} \text{ J}$ A1 [2]
- (b) sketch: smooth curve in correct directions B1
peak at f M1
amplitude never zero and line extends from $0.7f$ to $1.3f$ A1 [3]
- (c) sketch: peaked line always below a peaked line A M1
peak not as sharp and at (or slightly less than) frequency of peak in line A A1 [2]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42

- 5 (a) amplitude of the carrier wave varies M1
in synchrony with displacement of the information/audio signal A1 [2]
- (b) (i) 10 kHz A1 [1]
(ii) 5 kHz A1 [1]
- (c) (i) $24 = 10 \lg (P_{\text{MIN}} / \{5.0 \times 10^{-13}\})$ C1
 $P_{\text{MIN}} = 1.3 (1.26) \times 10^{-10} \text{ W}$ A1 [2]
- (ii) $45 \times 2 = 10 \lg (\{500 \times 10^{-3}\} / P)$
 $P = 5.0 \times 10^{-10} \text{ (W)}$ M1
 $P > P_{\text{MIN}}$ so yes A1
- or*
- maximum attenuation calculated to be 96 (dB) (M1)
96 dB > 2 × 45 dB so yes (A1)
- or*
- maximum length of wire calculated to be 48 (km) (M1)
actual length 45 km < 48 km so yes (A1)
- or*
- maximum attenuation per unit length calculated to be 2.2 dB km⁻¹ (M1)
2.2 dB km⁻¹ > 2.0 dB km⁻¹ so yes (A1) [2]
- 6 (a) lines perpendicular to surface
or
lines are radial M1
lines appear to come from centre A1 [2]
- (b) (i) $F_E = (1.6 \times 10^{-19})^2 / 4\pi\epsilon_0 x^2$ C1
 $F_G = G \times (1.67 \times 10^{-27})^2 / x^2$ C1
 $F_E / F_G = (1.6 \times 10^{-19})^2 \times (8.99 \times 10^9) / [(1.67 \times 10^{-27})^2 \times (6.67 \times 10^{-11})]$
= 1.2 (1.24) × 10³⁶ A1 [3]
- (ii) $F_E \gg F_G$ B1 [1]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42

- 7 (a) e.g. storing energy
blocking d.c.
in oscillator circuits
in tuning circuits
in timing circuits
- any two* B2 [2]
- (b) (i) $1/6 + 1/C + 1/C = 1/4$ C1
 $C = 24 \mu\text{F}$ A1 [2]
- (ii) $Q = CV$
 $= 4.0 \times 10^{-6} \times 12$ C1
 $= 48 \mu\text{C}$ A1 [2]
- (iii) 1. $48 \mu\text{C}$ A1
2. $24 \mu\text{C}$ A1 [2]
- 8 (a) (i) gain = voltage output / voltage input B1 [1]
- (ii) changes in V_{OUT}
occur immediately when V_{IN} changes M1
A1
- or*
- changes in V_{IN} (M1)
result in immediate changes to V_{OUT} (A1) [2]
- (b) $12 = 1 + R/(1.5 \times 10^3)$ C1
 $R = 16.5 \text{ k}\Omega$ A1 [2]
- (c) straight line from (0,0) to (0.75 t_1 , 9.0V) B1
horizontal line from endpoint of straight line to t_1 B1
+9V to -9V (or v.v.) at t_1 B1
correct line to t_2 B1 [4]

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42

- 9 (a) (i) number density of charge carriers/free electrons
or
number per unit volume of charge carriers/free electrons B1 [1]
- (ii) PX or QY or RZ B1 [1]
- (b) (i) V_H is inversely proportional to n B1
for semiconductors, n is (much) smaller than for metals B1 [2]
- (ii) magnetic field would deflect holes and electrons in same direction B1
(because) electrons are (-)ve, holes are (+)ve M1
so V_H has opposite polarity/opposite sign A1 [3]
- 10 (a) iron rod changes flux (density)/field B1
change of flux in coil Q causes induced e.m.f. B1 [2]
- (b) constant reading (either polarity) from time zero to near t_1 B1
spike in one direction near t_1 clearly showing a larger voltage M1
of opposite polarity A1
zero reading from near t_1 to t_2 B1 [4]
- 11 (a) point P shown at 'lower end' of load B1 [1]
- (b) $V_{r.m.s.} = 6.0/\sqrt{2} = 4.24\text{ V}$ C1
 $I_{r.m.s.} = 4.24/(2.4 \times 10^3)$
 $= 1.8 \times 10^{-3}\text{ A}$ A1 [2]
- (c) (i) capacitor in parallel with load B1 [1]
- (ii) line from peak to curve at 3.0V for either half- or full-wave rectified M1
correct curvature on line (gradient becoming more shallow) A1
line drawn as for full-wave rectified A1 [3]

Page 7	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9702	42

- 12 (a) (i)** (X-ray) photon produced when electron/charged particle is stopped/accelerated (suddenly) B1
- range of accelerations (in target) M1
- hence distribution of wavelengths A1 [3]
- (ii)** electron gives all its energy to one photon B1
- electron stopped in single collision B1 [2]
- (iii)** de-excitation of (orbital) electrons in target/anode/metal B1 [1]
- (b) (i)** aluminium sheet/filter/foil (placed in beam from tube) B1 [1]
- (ii)** (long wavelength X-rays) do not pass through the body B1 [1]
- 13 (a)** (photons of) electromagnetic radiation M1
- emitted from nuclei A1 [2]
- (b)** line of best fit drawn B1
- recognises μ as given by the gradient of best-fit line
- or*
- $\ln C = \ln C_0 - \mu x$ B1
- $\mu = 0.061 \text{ mm}^{-1}$ (within $\pm 0.004 \text{ mm}^{-1}$, 1 mark; within $\pm 0.002 \text{ mm}^{-1}$, 2 marks) A2 [4]
- (c)** aluminium is less absorbing (than lead)
- or*
- gradient of graph would be less M1
- so μ is smaller A1 [2]