MARK SCHEME for the October/November 2014 series

9702 PHYSICS

9702/41

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2014 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.



P	age 2	e 2 Mark Scheme Syllabus					
-		Cambridge International AS/A Level – October/November 2014	9702	Paper 41			
		Section A	·				
1	(a) g	$g = GM/R^{2}$ = (6.67 × 10 ⁻¹¹ × 6.4 × 10 ²³)/(3.4 × 10 ⁶) ² = 3.7 N kg ⁻¹		C1 A1	[2]		
	k Z	$\Delta E_{\rm P} = mg\Delta h$ because $\Delta h \ll R$ (or 1800 m $\ll 3.4 \times 10^6$ m) g is constant $\Delta E_{\rm P} = 2.4 \times 3.7 \times 1800$ = 1.6×10^4 J use of g = $9.8 m \text{s}^{-2}$ max. 1 for explanation)		B1 C1 A1	[3]		
	۱ ر	gravitational potential <u>energy</u> = (-) <i>GMm</i> /x $r^2 = 2GM/x$ $r = 4D = 4 \times 6.8 \times 10^6$ $r^2 = (2 \times 6.67 \times 10^{-11} \times 6.4 \times 10^{23})/(4 \times 6.8 \times 10^6)$		C1 C1 C1			
	-	= 3.14×10^{6} $\gamma = 1.8 \times 10^{3} \text{ m s}^{-1}$ use of 3.5D giving $1.9 \times 10^{3} \text{ m s}^{-1}$, allow max. 3)		A1	[4]		
2	(a) ((i) $F = R \cos \theta$ $W = R \sin \theta$ dividing, $W = F \tan \theta$ (max. 1 if derivation to final line not shown)		M1 M1 A0	[2]		
	(1	i) <u>provides</u> the centripetal force		B1	[1]		
	()	wither $F = mv^2/r$ and $W = mg$ for $v^2 = rg/\tan \theta$ $v^2 = (14 \times 10^{-2} \times 9.8)/\tan 28^\circ$ = 2.58 $v = 1.6 \mathrm{m s}^{-1}$		C1 C1 A1	[3]		
3		bbeys the equation pV/T = constant (accept $pV = nRT$)		B1	[1]		
	(b) ((i) $pV = nRT$ $5.0 \times 10^7 \times 3.0 \times 10^{-4} = n \times 8.31 \times 296$ giving $n = 6.1$ mol		C1 A1	[2]		
	(1	ii) pressure ∞ amount of substance loss = 0.40/100 × 6.1 mol = 0.0244 mol = 0.0244 × 6.02 × 10 ²³ (atoms) = 1.47 × 10 ²² atoms		C1 C1 C1			
		rate = $(1.47 \times 10^{22})/(35 \times 24 \times 60 \times 60)$ = $4.9 \times 10^{15} s^{-1}$		A1	[4]		

P	age 3	Mark Scheme	Syllabus	Раре	۲
	aye i	Cambridge International AS/A Level – October/November 2014	9702	<u>- rape</u> 41	71
4	(a)	acceleration / force proportional to displacement (from a fixed point) either acceleration and displacement in opposite directions		M1	[0]
	(b)	 <i>or</i> acceleration always directed towards a fixed point (i) <i>g</i> and <i>r</i> are constant so <i>a</i> is proportional to <i>x</i> 		A1 B1	[2]
		negative sign shows <i>a</i> and <i>x</i> are in opposite directions (ii) $\omega^2 = g/r \operatorname{and} \omega = 2\pi/T$		B1 C1	[2]
		$\omega^2 = 9.8/0.28$ = 35 $T = 2\pi/\sqrt{35} = 1.06 s$		C1	
		time interval $\tau = 0.53 \text{s}$		A1	[3]
	(c)	sketch: time period constant (or increases very slightly) drawn line always 'inside' given loops successive decrease in peak height		M1 A1 A1	[3]
5	(a)	work done in moving unit positive charge from infinity (to the point)		M1 A1	[2]
	(b)	(i) inside the sphere, the potential would be constant		B1	[1]
		(ii) for point charge, Vx is constant co-ordinates clear and determines two values of Vx at least 4 cm ap conclusion made clear	oart	B1 M1 A1	[3]
	(c)	$q = 4\pi\varepsilon_0 Vx$ $q = 4\pi \times 8.85 \times 10^{-12} \times 180 \times 1.0 \times 10^{-2}$ $= 2.0 \times 10^{-10} C$		M1 A1	[2]
6	(a)	$F = BIL \sin\theta$ = 2.6 × 10 ⁻³ × 5.4 × 4.7 × 10 ⁻² × sin 34°		C1	
		= 3.69×10^{-4} N (allow 1 mark for use of cos 34°)		A1	[2]
	(b)	peak current = $1.7 \times \sqrt{2}$ = 2.4 A		C1	
		max. force = $2.6 \times 10^{-3} \times 2.4 \times 4.7 \times 10^{-2} \times \sin 34^{\circ}$ = 1.64×10^{-4} N		C1	
		variation = $2 \times 1.64 \times 10^{-4}$ = 3.3×10^{-4} N		A1	[3]

Ρ	age 4		Mark Scheme	Syllabus	Pap	er
	-		Cambridge International AS/A Level – October/November 2014	9702	41	
7	(a)	(i)	<i>either</i> heating effect in a resistor ∞ (current) ² square of value of an alternating current is always positive so heating effect <i>or</i> current moves in opposite directions in resistor during half-cycle heating effect is independent of direction	S	B1 B1 A0 (B1) (B1)	[2]
		(ii)	that value of the direct current producing the same heating effect (as the alternating current) in a	resistor	M1 A1	[2]
	(b)	(i)	induced e.m.f. proportional to the rate of change of (magnetic) flux (linkage)		M1 A1	[2]
		(ii)	flux in core is in phase with current in the primary coil (induced) e.m.f. in secondary because coil cuts the flux flux and rate of change of flux are not in phase		B1 B1 B1	[3]
8	(a)	pho	oton 'absorbed' by electron oton has energy equal to difference in energy of two energy levels ctron de-excites emitting photon (of same energy) in any direction		B1 B1 B1	[3]
	(b)	(i)	$E = hc/\lambda$ = (6.63 × 10 ⁻³⁴ × 3 × 10 ⁸)/(435 × 10 ⁻⁹) = 4.57 × 10 ⁻¹⁹ J (allow 2 s.f.) = (4.57 × 10 ⁻¹⁹)/(1.6 × 10 ⁻¹⁹) (eV) = 2.86 eV (allow 2 s.f.)		C1 C1 C1 A1	[4]
		(ii)	arrow pointing in either direction between -3.41eV and -0.55eV		B1	[1]
9	(a)	ʻligl	nt' nuclei combine to form 'heavier' nuclei		B1	[1]
	(b)	(i)	either energy = $c^2 \Delta m$ or energy = $(3.00 \times 10^8)^2 \times 1.66 \times 10^{-27}$ energy = 1.494×10^{-10} J = $(1.494 \times 10^{-10})/(1.60 \times 10^{-13})$ = 934 MeV (3 s.f.)		C1 C1 A1	[3]
		(ii)	$\Delta m = (2.01356 + 3.01551) - (4.00151 + 1.00867)$ = 5.02907 - 5.01018 = 0.01889 u		C1	
			energy = 0.01889 × 934 = 17.6 MeV (<i>allow 2 s.f.</i>)		A1	[2]
		(iii)	high temperature means high speeds/ <u>kinetic</u> energy of nuclei D and T nuclei collide despite repelling one another		B1 B1	[2]

P	ige (5	Mark Scheme Syll	abus	Раре	۶r
Гс	iye .			/02	41	51
			Section B			
10	(a)	infi	. zero output resistance/impedance nite bandwidth			
			nite slew rate nark each, max. 3		B3	[3]
	(b)	(i)	at 1.0 °C, thermistor resistance is $3.7 \text{ k}\Omega$ amplifier gain = $-R/740 = -3700/740$ (negative sign essential) = -5.0		B1 C1 C1	
			potential = 1.0/-5.0 = -0.20 V		A1	[4]
		(ii)	at 15 °C, <i>R</i> = 2.15 kΩ (<i>allow ±0.05 kΩ</i>) reading = (2150/740) × 0.2		C1	
			$= 0.58 \text{ V} (0.59 \text{ V} \rightarrow 0.57 \text{ V})$		A1	[2]
	(c)	(i)	0.68 V		A1	[1]
		(ii)	resistance (of thermistor) does not change linearly with temperature		B1	[1]
11	(a)	alu	ay beam contains many wavelengths minium filter absorbs long wavelength X-ray radiation t would be absorbed by the body (and not contribute to the image)		B1 M1 A1	[3]
	(b)	ano X-r	scan consists of (many) X-ray <u>images</u> of a slice d there are many slices ay image is a single exposure much) greater exposure with CT scan		M1 A1 B1 B1	[4]
12	(a)	(i)	e.g. satellite communication, mobile phones, line of sight communication	n, wifi	B1	[1]
		(ii)	e.g. connection of TV to aerial, loudspeaker, microphone (if clearly ident	ified)	B1	[1]
		(iii)	e.g. a.f. amplifier to loudspeaker, landline for phone		B1	[1]
	(b)	(i)	attenuation/dB = $10 \log (P_2/P_1)$ -190 = $10 \log (P_2/3.1)$		C1	
			$P_2 = 3.1 \times 10^{-19} \text{kW}$		A1	[2]
		(ii)	signal is amplified frequency is changed to prevent swamping of up-link signal by down-link (signal)		M1 M1 A1	[3]

Page 6		Mark Scheme	Syllabus	Paper	
		Cambridge International AS/A Level – October/November 2014	9702	41	
13	(a)	<i>either</i> for transmission and reception of signal <i>or</i> switching between transmitted and received signals <i>either</i> so that one aerial may be used <i>or</i> so that transmission and reception can occur in quick succession		M1 A1	[2]
	(b)	gives large signal for one (input) frequency (and) rejects/very small signal for all other frequencies		M1 A1	[2]