



Cambridge International AS & A Level

PHYSICS**9702/52**

Paper 5 Planning, Analysis and Evaluation

October/November 2023

MARK SCHEME

Maximum Mark: 30

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2023 series for most Cambridge IGCSE, Cambridge International A and AS Level components, and some Cambridge O Level components.

This document consists of **11** printed pages.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently, e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

PUBLISHED**GENERIC MARKING PRINCIPLE 5:**

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Science-Specific Marking Principles

1 Examiners should consider the context and scientific use of any keywords when awarding marks. Although keywords may be present, marks should not be awarded if the keywords are used incorrectly.

2 The examiner should not choose between contradictory statements given in the same question part, and credit should not be awarded for any correct statement that is contradicted within the same question part. Wrong science that is irrelevant to the question should be ignored.

3 Although spellings do not have to be correct, spellings of syllabus terms must allow for clear and unambiguous separation from other syllabus terms with which they may be confused (e.g. ethane / ethene, glucagon / glycogen, refraction / reflection).

4 The error carried forward (ecf) principle should be applied, where appropriate. If an incorrect answer is subsequently used in a scientifically correct way, the candidate should be awarded these subsequent marking points. Further guidance will be included in the mark scheme where necessary and any exceptions to this general principle will be noted.

5 'List rule' guidance

For questions that require *n* responses (e.g. State **two** reasons ...):

- The response should be read as continuous prose, even when numbered answer spaces are provided.
- Any response marked *ignore* in the mark scheme should not count towards *n*.
- Incorrect responses should not be awarded credit but will still count towards *n*.
- Read the entire response to check for any responses that contradict those that would otherwise be credited. Credit should **not** be awarded for any responses that are contradicted within the rest of the response. Where two responses contradict one another, this should be treated as a single incorrect response.
- Non-contradictory responses after the first *n* responses may be ignored even if they include incorrect science.

6 Calculation specific guidance

Correct answers to calculations should be given full credit even if there is no working or incorrect working, **unless** the question states 'show your working'.

For questions in which the number of significant figures required is not stated, credit should be awarded for correct answers when rounded by the examiner to the number of significant figures given in the mark scheme. This may not apply to measured values.

For answers given in standard form (e.g. $a \times 10^n$) in which the convention of restricting the value of the coefficient (a) to a value between 1 and 10 is not followed, credit may still be awarded if the answer can be converted to the answer given in the mark scheme.

Unless a separate mark is given for a unit, a missing or incorrect unit will normally mean that the final calculation mark is not awarded. Exceptions to this general principle will be noted in the mark scheme.

7 Guidance for chemical equations

Multiples / fractions of coefficients used in chemical equations are acceptable unless stated otherwise in the mark scheme.

State symbols given in an equation should be ignored unless asked for in the question or stated otherwise in the mark scheme.

PUBLISHED

Question	Answer	Marks
1	Defining the problem	
	V is the independent variable and z is the dependent variable or vary V and measure z	1
	keep h <u>constant</u>	1
	Methods of data collection	
	labelled diagram of workable experiment including: <ul style="list-style-type: none"> • pulley supported by stand • stand placed on surface/bench/floor • minimum of two labels from stand, beaker, oil, surface/bench/floor, pulley, string 	1
	use (metre) rule to measure h or (metre) rule correctly positioned with h marked on diagram	1
	use measuring cylinder to measure V	1
	timing method to measure time t of fall of beaker to determine z e.g. use timer/stopwatch or use light gate(s) <u>connected to a timer/data logger</u>	1

PUBLISHED

Question	Answer	Marks
1	Method of Analysis	
	plot a graph of $\frac{1}{z^2}$ against $\frac{1}{V}$ or equivalent (e.g. $\frac{1}{V}$ against $\frac{1}{z^2}$) Do not accept logarithms.	1
	$b = \frac{1}{2h \times y\text{-intercept}}$ (for $\frac{1}{V}$ against $\frac{1}{z^2}$: $b = \frac{M \times \text{gradient}}{ah}$ or $b = -\frac{\text{gradient}}{2h \times y\text{-intercept}}$)	1
	$a = \frac{M}{bh \times \text{gradient}}$ or $a = \frac{2M \times y\text{-intercept}}{\text{gradient}}$ (for $\frac{1}{V}$ against $\frac{1}{z^2}$: $a = -2M \times y\text{-intercept}$)	1

PUBLISHED

Question	Answer	Marks
1	Additional detail including safety considerations	6
	D1 precaution linked to <u>oil spillage</u> , e.g. use of cushion/sand box/tray for falling beaker to land or use of bungs/lids on beakers or use foam on bench/floor or use foam to prevent rising beaker hitting pulley	
	D2 precaution linked to <u>oil contact with skin</u> e.g. use gloves to avoid contact with oil	
	D3 keep M constant	
	D4 use a (top-pan) balance to measure M	
	D5 method to keep h constant e.g. use a fiducial mark to release the beaker from the same position or release from the same position on the <u>clamped</u> rule each time	
	D6 equation to determine z for method used, e.g. for timing h , $z = 2h / t$ or for one light gate, $z = L / t$ where L is the length of the interrupted beam or for two light gates, $z = \text{distance between light gates} / t$ Do not accept h / t .	
	D7 additional detail on diagram to measure h , e.g. clamp (metre) rule with stand on surface or use of set squares positioned on the surface to side of rule or spirit level positioned to side of rule	
	D8 use large value of h to increase time of fall of beaker	
	D9 repeat measurements of z for the same V <u>and</u> average z	
	D10 relationship valid <u>if</u> a straight line is produced (passing through $\left(\frac{1}{2bh}\right)$) Do not accept line passing through the origin.	

PUBLISHED

Question	Answer	Marks														
2(a)	gradient = $-\frac{t}{R}$ y-intercept = $\ln I_0 R$	1														
2(b)	<table border="1" data-bbox="842 395 1435 855"> <thead> <tr> <th data-bbox="842 395 1137 461">$1/C/10^4 \text{ F}^{-1}$</th> <th data-bbox="1137 395 1435 461">$\ln (V/V)$</th> </tr> </thead> <tbody> <tr> <td data-bbox="842 461 1137 525">0.91 or 0.909</td> <td data-bbox="1137 461 1435 525">0.896 or 0.8961</td> </tr> <tr> <td data-bbox="842 525 1137 588">0.76 or 0.758</td> <td data-bbox="1137 525 1435 588">1.012 or 1.0116</td> </tr> <tr> <td data-bbox="842 588 1137 652">0.63 or 0.633</td> <td data-bbox="1137 588 1435 652">1.115 or 1.1151</td> </tr> <tr> <td data-bbox="842 652 1137 716">0.61 or 0.606</td> <td data-bbox="1137 652 1435 716">1.131 or 1.1314</td> </tr> <tr> <td data-bbox="842 716 1137 780">0.48 or 0.482</td> <td data-bbox="1137 716 1435 780">1.253 or 1.2528</td> </tr> <tr> <td data-bbox="842 780 1137 855">0.36 or 0.357</td> <td data-bbox="1137 780 1435 855">1.348 or 1.3481</td> </tr> </tbody> </table> <p data-bbox="322 890 757 922">Values correct as shown above.</p>	$1/C/10^4 \text{ F}^{-1}$	$\ln (V/V)$	0.91 or 0.909	0.896 or 0.8961	0.76 or 0.758	1.012 or 1.0116	0.63 or 0.633	1.115 or 1.1151	0.61 or 0.606	1.131 or 1.1314	0.48 or 0.482	1.253 or 1.2528	0.36 or 0.357	1.348 or 1.3481	1
$1/C/10^4 \text{ F}^{-1}$	$\ln (V/V)$															
0.91 or 0.909	0.896 or 0.8961															
0.76 or 0.758	1.012 or 1.0116															
0.63 or 0.633	1.115 or 1.1151															
0.61 or 0.606	1.131 or 1.1314															
0.48 or 0.482	1.253 or 1.2528															
0.36 or 0.357	1.348 or 1.3481															
	Uncertainties in $\ln (V/V)$ from ± 0.021 or ± 0.020 to ± 0.010 or ± 0.013	1														
2(c)(i)	Six points from (b) plotted correctly. Must be within half a small square. Diameter of points must be less than half a small square.	1														
	Error bars in $\ln (V/V)$ plotted correctly. All error bars to be plotted. Total length of bar must be accurate to less than half a small square and symmetrical.	1														

PUBLISHED

Question	Answer	Marks
2(c)(ii)	Straight line of best fit drawn. Do not accept line from top point to bottom point. Points must be balanced. Line must pass between (0.820, 0.95) and (0.845, 0.95) and between (0.400, 1.30) and (0.425, 1.30)	1
	Worst acceptable line drawn (steepest or shallowest possible line that passes through all the error bars). All error bars must be plotted.	1
2(c)(iii)	Gradient determined with clear substitution of data points into $\Delta y / \Delta x$. Distance between data points must be greater than half the length of the drawn line. Gradient must be negative.	1
	Gradient determined of worst acceptable line. uncertainty = (gradient of line of best fit – gradient of worst acceptable line) or uncertainty = $\frac{1}{2}$ (steepest worst line gradient – shallowest worst line gradient)	1
2(c)(iv)	y -intercept determined by substitution of correct point with consistent power of ten in m and x into $y = mx + c$.	1

PUBLISHED

Question	Answer	Marks
2(d)(i)	<p>R determined using gradient.</p> $R = -\frac{30.0}{\text{gradient}} = \frac{30.0}{\text{(c)(iii)}}$	1
	<p>I_0 determined using y-intercept with method shown.</p> $I_0 = \frac{e^{y\text{-intercept}}}{R} = \frac{e^{\text{(c)(iv)}}}{\text{(d)(i)}}$	1
	<p>R and I_0 determined correctly using gradient and y-intercept and R and I_0 given to 2 or 3 significant figures and R and I_0 given with SI units with appropriate powers of ten.</p> <p>Units: R: Ω or s F^{-1} I_0: A or V F s^{-1} or $\text{V } \Omega^{-1}$</p>	1
2(d)(ii)	<p>Percentage uncertainty in R with method shown.</p> $\text{percentage uncertainty in } R = \left(\frac{\Delta t}{t} + \frac{\Delta \text{gradient}}{\text{gradient}} \right) \times 100$ <p>or</p> <p>Correct substitution for max/min methods.</p>	1

PUBLISHED

Question	Answer	Marks
2(e)	<p>C determined to a minimum of 2 significant figures from (c)(iii) and (c)(iv) or (d)(i) with correct substitutions.</p> $C = \frac{\text{gradient}}{\ln V - y\text{-intercept}} \quad \text{or} \quad C = -\frac{\text{gradient}}{y\text{-intercept} - \ln V}$ <p>or</p> $C = -\frac{t}{R(\ln V - \ln I_0 R)} \quad \text{or} \quad C = \frac{t}{R(\ln I_0 R - \ln V)}$	1