



Mark Scheme (Results)

June 2019

Pearson Edexcel International Advanced Subsidiary Level In Physics (WPH12) Paper 01 Waves and Electricity Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at <u>www.edexcel.com</u> or <u>www.btec.co.uk</u>. Alternatively, you can get in touch with us using the details on our contact us page at <u>www.edexcel.com/contactus</u>.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

June 2019 Publications Code WPH12_01_MS_1906 All the material in this publication is copyright © Pearson Education Ltd 2019

PMT

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. **Examiners should also be prepared to award zero marks if the candidate's** response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a **candidate's** response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

PMT

Mark scheme notes

Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. It is not a set of model answers.

For example:

(iii) Horizontal force of hinge on table top

66.3 (N) or 66 (N) and correct indication of direction [no ue]
ISome examples of direction: acting from right (to left) / to the left / West
/ opposite direction to horizontal. May show direction by arrow. Do not accept a minus sign in front of number as direction.]

This has a clear statement of the principle for awarding the mark, supported by some examples illustrating acceptable boundaries.

- 1. Mark scheme format
 - 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the ms has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'
 - 1.2 Bold lower case will be used for emphasis.
 - 1.3 Round brackets () indicate words that are not essential e.g. "(hence) distance is increased".
 - 1.4 Square brackets [] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].
- 2. Unit error penalties
 - 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally mean that the final calculation mark will not be awarded.
 - 2.2 Incorrect use of case e.g. 'Watt' or 'w' will not be penalised.
 - 2.3 **There will be no unit penalty applied in 'show that' questions or in any other question** where the units to be used have been given, for example in a spreadsheet.
 - 2.4 The same missing or incorrect unit will not be penalised more than once within one question (one clip in epen).
 - 2.5 Occasionally, it may be decided not to penalise a missing or incorrect unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
 - 2.6 The mark scheme will indicate if no unit error penalty is to be applied by means of [no ue].
- 3. Significant figures
 - 3.1 Use of an inappropriate number of significant figures in the theory papers will **normally only be penalised in 'show that' questions where use of t**oo few significant figures has resulted in the candidate not demonstrating the validity of the given answer.
 - 3.2 The use of $g = 10 \text{ m s}^{-2}$ or 10 N kg⁻¹ instead of 9.81 m s⁻² or 9.81 N kg⁻¹ will be penalised by one mark (but not more than once per clip). Accept 9.8 m s⁻² or 9.8 N kg⁻¹

4. Calculations

- 4.1 Bald (i.e. no working shown) correct answers score full marks unless in a 'show that' question.
- 4.2 If a 'show that' question is worth 2 marks then both marks will be available for a reverse working; if it is worth 3 marks then only 2 will be available.
- 4.3 use of the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
- 4.4 recall of the correct formula will be awarded when the formula is seen or implied by substitution.
- 4.5 The mark scheme will show a correctly worked answer for illustration only.
- 4.6 Example of mark scheme for a calculation:

'Show that' calculation of weight

Use of L \times W \times H

Substitution into density equation with a volume and density

Correct answer [49.4 (N)] to at least 3 sig fig. [No ue] [If 5040 g rounded to 5000 g or 5 kg, do not give 3rd mark; if conversion to kg is omitted and then answer fudged, do not give 3rd mark] [Bald answer scores 0, reverse calculation 2/3]

Example of answer: $80 \text{ cm} \times 50 \text{ cm} \times 1.8 \text{ cm} = 7200 \text{ cm}^3$ $7200 \text{ cm}^3 \times 0.70 \text{ g cm}^{-3} = 5040 \text{ g}$ $5040 \times 10^{-3} \text{ kg} \times 9.81 \text{ N/kg}$ = 49.4 N

- 5. Quality of Written Communication
 - 5.1 Indicated by QoWC in mark scheme. QWC Work must be clear and organised in a logical manner using technical wording where appropriate.
 - 5.2 Usually it is part of a max mark, the final mark not being awarded unless the QoWC condition has been satisfied.

6. Graphs

- 6.1 A mark given for axes requires both axes to be labelled with quantities and units, and drawn the correct way round.
- 6.2 Sometimes a separate mark will be given for units or for each axis if the units are complex. This will be indicated on the mark scheme.
- 6.3 A mark given for choosing a scale requires that the chosen scale allows all points to be plotted, spreads plotted points over more than half of each axis and is not an awkward scale e.g. multiples of 3, 7 etc.
- 6.4 Points should be plotted to within 1 mm.
 - Check the two points furthest from the best line. If both OK award mark.
 - If either is 2 mm out do not award mark.
 - If both are 1 mm out do not award mark.
 - If either is 1 mm out then check another two and award mark if both of these OK, otherwise no mark.

For a line mark there must be a thin continuous line which is the best-fit line for the candidate's results.

3

Question Number	Answer	Mark
1	D is the correct answer	(1)
	A is not the correct answer as these are the units of charge	
	B is not the correct answer as these are the units of energy	
	C is not the correct answer as these are the units of force	
2	C is the correct answer	(1)
	A is not the correct answer as the intensity does not vary as the filter is rotated	
	B is not the correct answer as the intensity does not vary as the filter is rotated	
	D is not the correct answer as one filter will allow some oscillations to pass	
3	D is the correct answer	(1)
	A is not the correct answer as waves on a string are transverse	
	B is not the correct answer as waves on a string are transverse	
	C is not the correct answer as waves on a vibrating string are not progressive	
4	A is the correct answer (de Broglie wavelength = $2.43 \times 10^{-9} \text{ m}$)	(1)
	B is not the correct answer as the de Broglie wavelength = 1.82×10^{-9} m	
	C is not the correct answer as the de Broglie wavelength = $1.13 \times 10^{-12} \text{ m}$	
	D is not the correct answer as the de Broglie wavelength = $9.93 \times 10^{-13} \text{ m}$	
5	C is the correct answer	(1)
	A is not the correct answer as this is the graph for a fixed resistor	
	B is not the correct answer as this is the graph for a filament lamp	
	D is not the correct answer as this graph does not match any component	
6	A is the correct answer	(1)
	B is not the correct answer as it can be altered to change frequency (CP 5)	
	C is not the correct answer as it can be altered to change frequency (CP 5)	
	D is not the correct answer as it can be altered to change frequency (CP 5)	
7	B is the correct answer	(1)
	A is not the correct answer as distance has not been doubled	
	C is not the correct answer as time has been doubled, instead of halved	
	D is not the correct answer as distance has been doubled and time halved	
8	D is the correct answer	(1)
	A is not the correct answer as the two wires are both of the same material	
	B is not the correct answer as the current is the same in parallel	
	C is not the correct answer as the v is the same (if I , n , q and A are constant)	
)	A is the correct answer	(1)
	B is not the correct answer as it appears in neither of the definitions	
	C is not the correct answer as it only appears in the definition for current	
	D is not the correct answer as it only appears in the definition for p.d.	
10	B is the correct answer	(1)
	A is not the correct answer as X and Z are in antiphase	
	C is not the correct answer as Y and Z have the same frequency	
	D is not the correct answer as point Z is an antinode	

Question	Answer		Mark
Number			
11	Use of $A = \pi r^2$	(1)	
	Use of $R = \rho l/A$	(1)	
	Resistivity = $2.5 \times 10^{-8} (\Omega \text{ m})$ so aluminium	(1)	3
	(If candidates calculate A as 1.02×10^{-7} m ² they get $2.6 \times 10^{-8} \Omega$ m)		
	Example of calculation $A = \pi (0.18 \times 10^{-3})^2 = 1.0 \times 10^{-7} \text{ m}^2.$		
	$\rho = RA/l = (50 \times 10^{-3} \Omega) (1.0 \times 10^{-7} \mathrm{m^2}) / (0.200 \mathrm{m}) = 2.5 \times 10^{-8} \Omega \mathrm{m}$		
	Total for question 11		3

Question Number	Answer		Mark
12a	The average/mean velocity of the (free) electrons	(1)	1
	(allow "speed" for "velocity", and "charge carriers" for "electrons").		
12b	Use of $I = nqvA$ with $e = (-)1.60 \times 10^{-19}$ (C)	(1)	
	$v = (-) 3.65 \times 10^{-4} \text{ m s}^{-1}$	(1)	2
	Example of calculation $v = I/nqA = \frac{1.31 \text{ A}}{(8.49 \times 10^{28} \text{ m}^{-3})(1.60 \times 10^{-19} \text{ C})(2.64 \times 10^{-7} \text{ m}^2)}$		
	$v = 3.65 \times 10^{-4} \text{ m s}^{-1}$		
	Total for question 12		3

Question Number	Answer		Mark
13a	Use of $I = P/A$	(1)	
	Use of $A = 4\pi r^2$	(1)	
	$r = 1.47 \times 10^{11} \mathrm{m}$	(1)	3
	(MP3 can only be awarded if 1410 W m ⁻² has been used)		
	$\frac{\text{Example of calculation}}{4\pi r^2 = (3.83 \times 10^{26} \text{ W}) / 1410 \text{ W m}^{-2}$		
	$r = 1.47 \times 10^{11} m.$		
13b	Mars orbits at a greater distance from the Sun than the Earth as the intensity is lower	(1)	
	Mars has a more elliptical orbit than the Earth	(1)	
	The (relative) difference between the maximum and minimum intensity for Mars is greater.	(1)	3
	(All 3 marking points need to be comparisons)		
	Total for question 13		6

Question Number	Answer			Mark
*14		esses a student's ability to show		
	structured answer	with linkages and fully-sustain	ned reasoning.	
	Marks are awarde	d for indicative content and fo	r how the answer is structured	
	and shows lines of	f reasoning.		
	-	le shows how the marks shoul	d be awarded for indicative	
	content. Number of	Number of marks		
	indicative	awarded for		
	marking points	indicative		
	seen in answer	marking points		
	6	4		
	5–4	3		
	3–2	2		
	1	1		
	0	0		
			d be awarded for structure and	
	lines of reasoning.		Number of marks awarded for structure	
			of answer and sustained line of reasoning	
		erent and logical structure with stained lines of reasoning hout	2	
	Answer is partially s	tructured with some linkages	1	
	and lines of reasonin	g		
	Answer has no linka	ages between points and is	0	
	unstructured			
	Indicative conte	ent		
	Minimu	m / threshold frequency req	uired to release electrons.	
	• For wav	es, any frequency would be	able to release electrons.	
	• Release	of electrons is instantaneou	s.	
		ave model were correct, (en lectrons were released.	ergy) would take time to build up	
	• (Kinetic) energy of released electro	ns dependent on frequency.	
		ave model were correct, the s would be dependent on th	(kinetic) energy of the released e intensity.	
				6
	Total for questi	on 14		6

Question Number	Answer		Mark
15a	See $V_{\rm T} = V_1 + V_2$ See $IR_{\rm T} = IR_1 + IR_2$ (Divides by I to give) $R_{\rm T} = R_1 + R_2$	(1) (1) (1)	3
15b	Use of $V = IR$ with 7.0V and 0.5A Use of $\frac{1}{Rtot} = \frac{1}{R_1} + \frac{1}{R_2}$ $R = 12\Omega$	 (1) (1) (1) 	
	Or Use of $V = IR$ with 6Ω and $0.5A$ (to get 3V across 6Ω resistor) Second use of $V = IR$ with $V = 4V$ $R = 12\Omega$	(1) (1) (1)	3
	Example of calculation R for whole circuit = (7.0V/0.5A) = 14\Omega So R for parallel section = $14 - 6 = 8\Omega$ $1/8 = 1/24 + 1/R_2$ $R_2 = 12\Omega$		
15ci	Use of $V = IR$ to determine circuit current Use of $P = I^2 R$ or $P = V^2/R$ or $P = VI$ $P = 1.5 \times 10^{-2}$ W	(1) (1) (1)	
	Or Ratio of resistances used to calculate p.d. across R Use of $P = V^2/R$ $P = 1.5 \times 10^{-2}$ W	(1) (1) (1)	3
	$\frac{\text{Example of calculation}}{\text{I} = 12.0 \text{ V} / (8000 + 670 \Omega) = 1.38 \times 10^{-3} \text{ A}}$ $P = (1.38 \times 10^{-3} \text{ A})^2 \times 8000 = 0.015 \text{ W}$		
15cii	Decrease in the number of conduction/ free electrons	(1)	
	Greater resistance of LDR	(1)	
	Less p.d. across the fixed resistor (allow "voltage" for "p.d.")	(1)	
	Use of a suitable power equation to conclude that less power dissipated in the fixed resistor.	(1)	4
	(Converse argument not allowed for MP1 & MP2)		
	(For MP4, do not accept an answer that includes an incorrect statement about one of the variables)		
	Total for question 15		13

Question Number	Answer		Mark
16a	(Sodium) electrons/atoms gain/absorb energy	(1)	
10a	And electrons move to higher energy levels	(1) (1)	
		(1)	3
	(Solium) electrons drop to lower energy levels, releasing <u>photons</u>	(1)	U
	(For MP2 & MP3, allow excited and de-excited)		
	(For MP2 & MP3, do not allow "atoms" for "electrons")		
	(For "levels" accept shells, orbitals, states)		
16b	Use of $c = f\lambda$ and Use of $E=hf$	(1)	
	Converts J to eV	(1)	
	Energy = 2.11eV	(1)	3
	Example of calculation		
	$f = (3.00 \times 10^8 \text{ m s}^{-1}) / (589 \times 10^{-9} \text{ m}) = 5.09 \times 10^{14} \text{ Hz}$		
	$E = (6.63 \times 10^{-34} \text{ Js}) \times (5.09 \times 10^{14} \text{ Hz}) = 3.38 \times 10^{-19} \text{ J}$		
	$E (in eV) = (3.38 \times 10^{-19} \text{ J}) / (1.60 \times 10^{-19} \text{ J} eV^{-1}) = 2.11 \text{ eV}$		
16c		(1)	
		(1)	
	Grating has 301 lines / mm, so the label is correct.	(1)	
	OR		
	Uses $sin\theta = \frac{s}{\sqrt{(s^2 + D^2)}}$	(1)	
		(1)	
		(1) (1)	3
	Grating has 301 lines / mm, so the label is correct.	(1)	5
	(Use of double slit or single slit equations does not gain any credit)		
	(Allow reverse calculation to show that 300 lines per mm leads to a value of		
	λ that is close to the given value or that 300 lines per mm leads to a value of		
	d or θ that is close to a value calculated).		
	Example of calculation		
	$\tan\theta = 0.234 \text{ m} / 1.30 \text{ m} = 0.18$		
	$\theta = 10.2^{\circ}$		
	$n\lambda = d\sin\theta$, so d = 589 × 10 ⁻⁹ m / sin 10.2° = 3.33 × 10 ⁻⁶ m		
	lines per mm = $1 / 3.33 \times 10^{-3}$ m = 301.		
	Total for question 16		9

PMT

Question Number	Answer		Mark
17a	Path difference is zero Or both waves have travelled the same distance from the speakers to O	(1)	
	Waves are in phase	(1)	
	Constructive interference/superposition takes place	(1)	3
17bi	Use of Pythagoras with 1.66m and 3.00m		
	Or Use of Pythagoras with 3.34m and 3.00m	(1)	
	Path difference calculated	(1)	
	Uses wavelength = $2 \times$ their path difference	(1)	
	Use of $v = f\lambda$	(1)	
	Speed of sound = 340 ms^{-1} (dependent on correct calculation)	(1)	5
	Path length of waves from Speaker $1 = \sqrt{((3.00 \text{ m})^2 + (1.66 \text{ m})^2)} = 3.43 \text{m}$ Path length of waves from Speaker $2 = \sqrt{((3.00 \text{ m})^2 + (3.34 \text{ m})^2)} = 4.49 \text{m}$ Path difference = 1.06m, so $\lambda = 2.12 \text{m}$. $v = f\lambda = 160 \text{ Hz} \times 2.12 \text{ m} = 339 \text{ms}^{-1}$		
	3.00 m		
	3.43 m		
	4.49 m 3.34 m		
	3.00 m		

	Total for question 17		12
	Idea that more than two waves meet and interfere/superpose (at any point so maxima/minima less pronounced)	(1)	2
17c	Reflections/echoes from walls/ceiling (in the classroom) would occur	(1)	
	Or Microphone at same level as tape measure whereas ears are higher Distances measured will be different from true distance to ears	(1) (1)	2
	Distance between ears is greater than the size of the microphone receiver Less percentage uncertainty in distance measurement taken	(1)	
	Or	(1)	
1701	As the amplitude on the oscilloscope can be measured more <u>accurately</u> (For "amplitude" allow "maximum", "minimum", "displacement", "loudness" or "quietness")	(1) (1)	
17bii	Hard for a person to judge when sound is quietest/loudest	(1)	

Question Number	Answer		Mark
18 a	For light travelling in a more (optically) dense substance and meeting a less (optically) dense substance Or for light travelling a material with higher RI and meeting one with a lower RI	(1)	
	Angle of incidence is greater than (or equal to) the critical angle	(1)	2
18b	Wave slows down as it enters the glass	(1)	
	Part of the wave(front) meets the glass first, so wave direction changes	(1)	
	OR		
	Refractive index of glass is greater than that of air Or Density of glass is greater than that of air	(1)	
	So angle of incidence is greater than the angle of refraction (accept "bends towards the normal")	(1)	2
18c	Use of sin $C = 1/n$ for glass-air boundary Subtracts calculated critical angle from 90° Use of $n_1 \sin\theta_1 = n_2 \sin\theta_2$ for glass-water boundary $\theta = 59^\circ$	 (1) (1) (1) (1) 	4
	(For MP3, both 1.50 and 1.30 need to be seen in the calculation).		
	Example of calculation Critical angle for glass-air boundary = $\sin^{-1}(1.00 / 1.50) = 41.8^{\circ}$ Angle of incidence for glass-water boundary = $90^{\circ} - 41.8^{\circ} = 48.2^{\circ}$ $1.50 \times \sin (48.2^{\circ}) = 1.30 \times (\sin \theta)$ $\theta = 59.3^{\circ}$		
	Total for question 18		8

PMT

Question Number	Answer	Mark
19a	Ammeter in series with cell, voltmeter in parallel with cell(1)Variable resistor(1)	2
	(Voltmeter can be drawn in parallel with the (variable) resistor for MP1,as	
	long as there are no other components with resistance in the circuit).	
19b	Line of best fit drawn(1) $\varepsilon = 0.28 - 0.29 \mathrm{V}$ (1)(Magnitude of) gradient calculated using a best fit line(1) $r = 400 - 430 \Omega$ (1)	4
	(If no best fit line has been drawn, only MP2 and MP4 are available) <u>Example of calculation</u> Gradient = $\Delta V / \Delta I = -0.18 \text{ V} / (0.44 \text{ x } 10^{-3} \text{ A}) = -409 \Omega$ so $r = 409 \Omega$	

		(*)	4
	Terminal potential difference is greater in series/A	(1)	
	' R+r	(1)	
	$V = \frac{\varepsilon R}{R+r}$		
	as \mathcal{E} and r the same	(1)	
	In series/A there is a greater (combined) resistance than in parallel/B Or Resistance in series/A is 2R, resistance in parallel/B is R/2.	(1)	
	OR		
	Terminal potential difference is greater in series/A	(1)	
	As \mathcal{E} and r the same Or since $\mathcal{E} = V + Ir$ Or more lost volts in parallel/B	(1)	
	so greater current in paranetrib Or so less current in series/A	(1)	
	So greater current in parallel/B Or so less current in series/A		
	Or Resistance in series/A is 2R, resistance in parallel/B is R/2.	(1)	
9c	In series/A there is a greater (combined) resistance than in parallel/B		