



**GCE**

**Physics B**

Unit **H157/02**: Physics in depth

Advanced Subsidiary GCE

**Mark Scheme for June 2017**

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

OCR will not enter into any discussion or correspondence in connection with this mark scheme.















© OCR 2017

H157/02

Mark scheme

June 2017

Annotations available in RM Assessor

Annotation	Meaning
	Benefit of doubt given
	Contradiction
	Incorrect response
	Error carried forward
	Follow through
	Not answered question
	Benefit of doubt not given
	Power of 10 error
	Omission mark
	Rounding error
	Error in number of significant figures
	Correct response
	Arithmetic error
	Wrong physics or equation

H157/02




Mark scheme

June 2017

Abbreviations, annotations and conventions used in the detailed Mark Scheme (to include abbreviations and subject-specific conventions).

<b>Annotation</b>	<b>Meaning</b>
/	alternative and acceptable answers for the same marking point
(1)	Separates marking points
<b>reject</b>	Answers which are not worthy of credit
<b>not</b>	Answers which are not worthy of credit
<b>IGNORE</b>	Statements which are irrelevant
<b>ALLOW</b>	Answers that can be accepted
( )	Words which are not essential to gain credit
—	Underlined words must be present in answer to score a mark
<b>ecf</b>	Error carried forward
<b>AW</b>	Alternative wording
<b>ORA</b>	Or reverse argument
<b>(1)m</b>	a method mark, awarded if a correct method is used
<b>(1)e</b>	an evaluation mark, awarded for correct substitution and evaluation

The following questions should be annotated with ticks to show where marks have been awarded in the body of the text: 4(a)(ii) & 6(b) Ticks must NOT be used in 6(c) or 8(c).

Question	Answer	Marks	Guidance
<b>Section A</b>			
<b>1</b> (a)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> If answer = <b>667 (lines mm<sup>-1</sup>)</b> award 2 marks no. = $1.00 \times 10^{-3} \text{ m} / 1.50 \times 10^{-6} \text{ m} = 666.6\dots \checkmark$ = 667 (lines mm <sup>-1</sup> ) $\checkmark$	<b>2</b>	must be 3 s.f. for the second mark If number per metre calculated and then correctly rounded to $6.67 \times 10^5$ , give 1 mark
(b)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> If answer = <b>51.0 / 51 / 51.02 (°)</b> award 2 marks $2\lambda = d \sin \theta_2 \Rightarrow 2 \times 583 \times 10^{-9} \text{ m} = [1.50 \times 10^{-6} \text{ m}] \sin \theta_2 \checkmark \text{ m}$ $\theta_2 = \arcsin\{[2 \times 583 \times 10^{-9} \text{ m}] / [1.50 \times 10^{-6} \text{ m}]\} = 51^\circ \checkmark \text{ e}$	<b>2</b>	
(c)	$3\lambda/d = [3 \times 583 \times 10^{-9} \text{ m}] / [1.50 \times 10^{-6} \text{ m}] \checkmark = 1.166$ and so $\theta_3$ is impossible/there's no value of sine > 1 $\checkmark$	<b>2</b>	or $n_{\text{max}}$ for $\theta_n = 90^\circ \rightarrow 2.6 \checkmark$ and $2.6 < 3 \checkmark$ or maximum possible path difference = $1.50 \times 10^{-6} \text{ m} \checkmark$ and $3\lambda = 3 \times 583 \times 10^{-9} \text{ m} = 1.75 \times 10^{-6} \text{ m}$ which is greater $\checkmark$
<b>Total</b>		<b>6</b>	
<b>2</b> (a)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> If answer = <b><math>1.05 \times 10^{-5} / 1.1 \times 10^{-5}</math> (V)</b> award 3 marks $R = \rho L/A = [2.3 \times 10^{-8} \Omega \text{ m}] \times [3.2 \times 10^{-3} \text{ m}] / \{\pi \times [10 \times 10^{-6} \text{ m}]^2\}$ $= [7.36 \times 10^{-11} \Omega \text{ m}^2] / [3.14 \times 10^{-10} \text{ m}^2] \checkmark \text{ s} = 0.234 \Omega \checkmark \text{ e}$  $V_1 = IR = 4.5 \times 10^{-5} \text{ A} \times 0.234 \Omega = 1.05 \times 10^{-5} / 1.1 \times 10^{-5} \text{ V} \checkmark$	<b>3</b>	m.ps. 1 & 2 are $\checkmark$ m method of finding $R$ and $\checkmark$ e its evaluation.  Allow intermediate rounding e.g. $0.23 \Omega$ gives $1.0(35) \times 10^{-5}$ Ecf own $R$ /rounding error
(b)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> If answer = <b>0.026 / 0.0265 (V)</b> award 2 marks $V_2 = I/G = 4.5 \times 10^{-5} \text{ A} / 1.7 \times 10^{-3} \text{ S} \checkmark$ $= 0.026(5) \text{ V} / 26(.5) \text{ mV} \checkmark$	<b>2</b>	or $R = 1/G = 588/590 \Omega \checkmark$ followed by $V_2 = IR \checkmark$ Needs at least 2 sig figs. <b>NOT</b> 0.027. If $G = 1.7 \text{ S}$ , do not give mp1 allow e.c.f. for incorrect $G/R$ <b>or</b> $I$ , but not if <b>both</b> incorrect
<b>Total</b>		<b>5</b>	
<b>3</b> (a)		<b>2</b>	Same length and direction $\checkmark$ Resultant = sum of lengths, horizontal $\checkmark$ No ecf
(b)		<b>1</b>	Same length, head-to-tail closed loop
(c)	equal angles between the phasor components $\checkmark$ correct answer (up down up, maybe rotated) $\checkmark$ 	<b>2</b>	
<b>Total</b>		<b>5</b>	

H157/02

Mark scheme

June 2017

Question	Answer	Marks	Guidance
4 (a) (i)	(X is a ) dislocation ✓	1	
(a) (ii)	Any two points from: Shearing stress/stress applied perpendicular to dislocation ✓ individual atoms slip <b>OR</b> atoms move one at a time ✓ smaller force/less energy needed to deform metal ✓ dislocation moves ✓ whole layer of atoms moves ✓	2	Any of these may be obtained from clear additions to the figure.
(b)	Any two points from: Foreign atom different in size from the native atoms ✓ may occupy the gap in the dislocation ✓ 'pins' dislocation by preventing slip/ preventing movement /sliding of layers ✓	2	
<b>Total</b>		<b>5</b>	
5 (a)	<b>FIRST CHECK THE CANDIDATE'S CALCULATED ANSWER</b> If answer = $3.9 \times 10^{17}$ / $3.94 \times 10^{17}$ ( $s^{-1}$ ) award 3 marks  $f = c/\lambda = [3.0 \times 10^8 \text{ m s}^{-1}]/[520 \times 10^{-9} \text{ m}] = 5.77 \times 10^{14} \text{ Hz} \checkmark$ $E = hf = 6.6 \times 10^{-34} \text{ J s} \times 5.77 \times 10^{14} \text{ Hz} = 3.81 \times 10^{-19} \text{ J} \checkmark$ no. of photons/s = $[150 \times 10^{-3} \text{ W}]/[3.81 \times 10^{-19} \text{ J}]$ $= 3.94 \times 10^{17} \text{ s}^{-1} \checkmark$	3	Allow intermediate rounding to 2 s.f. so if answer is close but not as shown left, check the candidate's calculation ( $E = 3.8 \times 10^{-19} \text{ J}$ gives $3.95 \times 10^{17} \text{ s}^{-1}$ , $f = 5.8 \times 10^{14} \text{ Hz}$ gives $E = 3.83 \times 10^{-19} \text{ J}$ gives $3.92 \times 10^{17} \text{ s}^{-1}$ ) Or $E = hc/\lambda \checkmark$ Evaluation of $E \checkmark$
(b)	<b>FIRST CHECK THE CANDIDATE'S CALCULATED ANSWER</b> If answer = $1.27$ / $1.3 \times 10^{-27}$ ( $\text{km m s}^{-1}$ ) award 1 mark $p = h/\lambda = [6.6 \times 10^{-34} \text{ J s}]/[520 \times 10^{-9} \text{ m}] = 1.27/1.3 \times 10^{-27} \text{ N s} \checkmark$	1	
(c)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> If answer = $4.95$ / $5.0 \times 10^{-10} \text{ N}$ award 1 mark $F = \text{no. of photons/s} \times \text{momentum of 1 photon}$ $= 3.94 \times 10^{17} \text{ s}^{-1} \times 1.27 \times 10^{-27} \text{ N s} = 5.0 \times 10^{-10} \text{ N} \checkmark$	1	e.c.f. own answer to (b) and allow use of 'show that' value(s) from (a) $4 \times 10^{17} \text{ s}^{-1} \times 1.3 \times 10^{-27} \text{ N s} = 5.2 \times 10^{-10} \text{ N}$ or $4 \times 10^{17} \text{ s}^{-1} \times 1 \times 10^{-27} \text{ N s} = 4 \times 10^{-10} \text{ N}$
<b>Total</b>		<b>5</b>	
<b>Section A total</b>		<b>26</b>	

H157/02

Mark scheme

June 2017

Question	Answer	Marks	Guidance
<b>Section B</b>			
<b>6 (a) (i)</b>	choice of equation: $s = ut + \frac{1}{2} a t^2$ & $u = v \sin \theta$ and substitution for $s = 0$ ✓ rearrangement to $t = \frac{2v \sin \theta}{g}$ ✓	<b>2</b>	mp1 is for equation choice and setting boundary condition e.g. $s = 0$ , $v = -u$ , $g$ and $u$ have opposite signs alternative approaches possible, e.g. finding max height from $v^2 = u^2 + 2as$ where $u = v \sin \theta(1)$ ; then $v = u + at \Rightarrow 0 = v \sin \theta - gt(1)$ ; and doubling to get total time (1)
<b>(a) (ii)</b>	$t = \frac{2v \sin \theta}{g} = 2 \times 24 \text{ m s}^{-1} \sin(76^\circ) / (9.8 \text{ m s}^{-2}) = 4.75 \text{ s}$ ✓ $R = v \cos \theta t = 24 \text{ m s}^{-1} \cos(76^\circ) \times 4.75 \text{ s} = 27.6 \text{ m}$ ✓ plotted correctly from own tabulated value and maximum $> 58 \text{ m}$ & $< 62 \text{ m}$ read ✓	<b>3</b>	If there's no working but 27.6 is entered the in table, award both mp1 & mp2 mp3 needs the line to have been drawn: no line = no mark
<b>(b)</b>	Choose from the suggested differences and explanations in the guidance. Allow other reasonable responses. 'Difference' may be illustrated by sketch on the graph. For 3 marks, at least one must be an explanation of the difference stated. Annotate this question with ticks and crosses, so there will be three annotations in the question.	<b>3</b>	NB shape of curve is not the projectile trajectory Pairs of difference & explanation: all values of $R$ less for any given values of $\theta$ ✓ because air resistance opposes horizontal motion ✓ $R - \theta$ will become asymmetrical ✓ because air resistance changes with time as the projectile moves ✓ reduction in $R$ greater for larger $\theta$ ✓ because projectile in the air for longer ✓ Mean horizontal velocity will be less ✓ Because air resistance acts on the horizontal component of velocity, ✓

Question	Answer	Marks	Guidance
<p><b>6 (c)*</b></p>	<p><b>(Level 3) (5 – 6 marks)</b>  Discussion reveals understanding of the physics of at least two events. Relates initial velocity of projectile to impulse delivered / power developed during throw/ work done in throw/force applied and projectile mass. May relate range to factors such as impulse, angle of throw and projectile mass. Discusses differences in technique between different throwing methods (even if incorrect: candidate may have no experience of these sports)  <i>There is a well-developed line of reasoning which is clear and logically structured. The information presented is relevant and substantiated.</i></p> <p><b>(Level 2) (3 – 4 marks)</b>  Discussion reveals some understanding of the physics of at least one event, possibly with errors. Equates greater range to higher velocity. Relates initial velocity of projectile to force applied and projectile mass. Discusses differences in technique between two different throwing methods. <i>There is a line of reasoning presented with some structure. The information presented is in the most part relevant and supported by some evidence.</i></p> <p><b>(Level 1) (1 – 2 marks)</b>  No discussion of relevant physics – may use technical vocabulary in an everyday fashion. Makes simple comparison between masses of objects and ranges, relating these to force and acceleration, possibly loosely. Comments on differences between events in differences of throwing technique in a purely descriptive way.  <i>There is an attempt at a logical structure with a line of reasoning. The information is in the most part relevant.</i></p> <p><b>(0 marks)</b>  No response or no response worthy of credit.</p>	<p>[6]</p>	<p><b>Indicative scientific points may include:</b></p> <p><b>Difference between events:</b></p> <ul style="list-style-type: none"> <li>• masses not all the same</li> <li>• shot and hammer involve very different bodily movements</li> <li>• javelin allows a run-up to give the javelin greater initial momentum</li> <li>• javelin and discus streamlined to air progress through air</li> <li>• angle tilt of discus generates lift</li> <li>• angle of throw may be constrained by the particular projectile in the event</li> </ul> <p><b>Discussion of power and impulse</b></p> <ul style="list-style-type: none"> <li>• large range needs high velocity (in optimal direction)</li> <li>• great impulse means more momentum transferred to projectile</li> <li>• same momentum change/force will accelerate lighter projectile more</li> <li>• time of transfer depends on (relative) velocity of projectile during throw</li> <li>• greater power means more kinetic energy transferred to projectile during time of throw</li> </ul> <p><b>Discussion of range and angle</b></p> <ul style="list-style-type: none"> <li>• optimal angle is about 45°</li> <li>• but will be affected by interaction with the air</li> <li>• and object is not thrown from ground level</li> <li>• throwing action may not allow projectile to be thrown at optimal angle</li> </ul> <p><b>Use the L1, L2, L3 annotations in RM Assessor; do not use ticks.</b></p>
	<p><b>Total</b></p>	<p><b>14</b></p>	



H157/02

Mark scheme

June 2017

Question	Answer	Marks	Guidance
7 (a) (i)	( $2^8$ levels/shades of grey and) $2^8 = 256$ ✓ 0 to 255 is 256 (different values) ✓	2	or $\log_2 256 = 8$ NOT $\log_2 255$ as need to demonstrate knowledge that there are 256 levels mp2 needs to be explicit; mention of '256' by itself is not enough (8 bits is in question).
(a) (ii)	White/random/dark specks due to noise ✓ Some/many 'dots'/pixels are <b>very</b> different from surrounding ones (and unlikely to be realistic representations of surface) ✓	2	Mp1 = identify tiny dots as pixels (possibly implied) Mp2 = imply they are well off any reasonable value.
(b)	25 km $\approx$ 20 pixels ✓ so resolution = 25 km/20 = 1250 / 1300 m ✓	2	Allow range 15 – 25 pixels. accept answer in range 1000 – 1700 km from above No ecf from mp1
(c)	Advantage: suggestion ✓ explanation ✓ Disadvantage: suggestion ✓ explanation ✓	4	e.g. clearer/better quality/easy to interpret ✓ no distracting speckles/more like the actual surface of Mercury ✓ e.g. loss of detail/contrast ✓ genuine bright/dim areas smoothed out (at edges) ✓ need to process data ✓ need more computer time/power ✓
(d)	<b>FIRST CHECK THE ANSWER ON THE ANSWER LINE</b> <b>If answer = 48 (s), award 3 marks</b> <b>If answer = 47.8 (s), award 2 marks</b> quantity of data = $22 \times 31944 \times 8 = 5622144$ bits ✓ time = no. of bits/bit rate = $5622144/[117.6 \times 10^3 \text{ s}^{-1}]$ ✓m&s = 47.8 s = 48 s ✓e	3	e.c.f mp1 , e.g. $22 \times 31944$ gives 6 s would give mp2 & mp3 = 2 marks while 5.98 s would not get mp3 = 1 mark.
	<b>Total</b>	<b>13</b>	
	<b>Section B total</b>	<b>27</b>	

Question	Answer	Mark s	Guidance
<b>Section C</b>			
<b>8 (a) (i)</b>	percentage uncertainty in width = $[0.1/10] \times 100\% = 1\%$ ✓ and percentage uncertainty in $t < [4 \mu\text{s}/0.1 \text{ s}] \times 100\%$ (= 0.004 %) which is (very, very) much smaller ✓	<b>2</b>	Calculation of one percentage uncertainty = mp1; calculation of the other and comparison = mp2. Calculation can be implied by correct values 1% &/or 0.004%
<b>(a) (ii)</b>	mean = $[0.10 \text{ m}]/[0.1453 \text{ s}] = 0.6882 \text{ m s}^{-1}$ ✓  uncertainty $\Delta v = 1\%$ of own value of mean = $0.006882 / 6.882 \times 10^{-3} \text{ m s}^{-1}$ ✓  rounded $\Delta v$ to 1 s.f. and rounded $v$ to same no of d.p., = $[0.688 \pm 0.007] \text{ m s}^{-1}$ ✓	<b>3</b>	or: $\Delta v = v_{\text{max}} - 0.6882 \times 10^{-3} \text{ m s}^{-1}$ = $[0.101 \text{ m}]/[0.1453 \text{ s}] - 0.6882 \times 10^{-3} \text{ m s}^{-1}$ = $0.6951 \text{ m s}^{-1} - 0.6882 \times 10^{-3} \text{ m s}^{-1} = 0.0069 \text{ m s}^{-1}$  Allow $[0.69 \pm 0.01] \text{ m s}^{-1}$
<b>(b) (i)</b>	( $t$ is a scalar but) <b><u>v</u> and <u>p</u> are <u>vectors</u></b> and so can go in + or – direction.	<b>1</b>	not just 'are vectors' without linking to the movement in Fig. 8.1 e.g. '(Time is scalar but) velocity and momentum are vectors so can go in a negative direction' is a minimum for the mark
<b>(b) (ii)</b>	$\Delta p_1 = 0.649 \text{ N s} + [-0.761 \text{ N s}] = -0.112 \text{ N s}$ $\Delta p_2 = [-0.486] \text{ N s} + 0.377 \text{ N s} = -0.109 \text{ N s}$ ✓ The difference (= 0.003 N s) is negligible (about 3% of either value) ✓ because percentage uncertainty of 1% for each of 4 readings ( $\Rightarrow 4\%$ ) is more than this ✓	<b>3</b>	e.c.f own momenta providing values are not very different from each other
<b>(b) (iii)</b>	$E_k$ before: $\frac{1}{2} \times 0.800 \text{ kg} \times [0.811 \text{ m s}^{-1}]^2 + \frac{1}{2} \times 0.800 \text{ kg} \times [-0.951 \text{ m s}^{-1}]^2$ = 0.6249 J = 0.625 J ✓ $E_k$ after: $\frac{1}{2} \times 0.800 \text{ kg} \times [-0.608 \text{ m s}^{-1}]^2 + \frac{1}{2} \times 0.800 \text{ kg} \times 0.471 \text{ m s}^{-1}]^2$ = 0.2366 J = 0.237 J which (significantly) less than the initial kinetic energy so energy has been transferred to e.g. increased internal energy of trolleys ✓	<b>2</b>	Allow intermediate rounding to 2 s.f. in (b)(iii)  m.p.2 needs a repeat calculation and a reasoned comment that this is significantly less than the original kinetic energy.

Question	Answer	Marks	Guidance
8 (c)*	<p><b>(Level 3) (5 – 6 marks)</b> Comments on improvement obtained by more results in terms of better means and quantified uncertainty with consequences for analysis of momenta and energies. Suggests a reasonable and detailed method of producing similar initial velocity and suggests a plausible way to measure <math>v</math> with greater precision. <i>There is a line of reasoning presented with some structure. There is a well-developed line of reasoning which is clear and logically structured. The information presented is relevant and substantiated.</i></p> <p><b>(Level 2) (3 – 4 marks)</b> Comments on improvement obtained by more results in terms of better means and quantified uncertainty. Suggests a reasonable method, possibly incomplete, of producing similar initial velocity. Comments on accuracy of velocity measurements. <i>There is a line of reasoning presented with some structure. The information presented is in the most part relevant and supported by some evidence.</i></p> <p><b>(Level 1) (1 – 2 marks)</b> Suggests simple method of producing similar velocities without any physical justification. <i>There is an attempt at a logical structure with a line of reasoning. The information is in the most part relevant.</i></p> <p><b>(0 marks)</b> No response or no response worthy of credit.</p>	[6]	<p><b>Indicative scientific points may include:</b></p> <p><b>Repeatable set-up</b></p> <ul style="list-style-type: none"> <li>• catapult</li> <li>• weight/pulley with release</li> <li>• ramp</li> <li>• pull over marked distance with newton-meter at fixed setting</li> </ul> <p><b>Advantages of repeated similar velocities</b></p> <ul style="list-style-type: none"> <li>• allows calculation of mean and uncertainty in <math>v</math></li> <li>• can calculate uncertainty in <math>p</math>, <math>E_k</math></li> <li>• can quantify energy losses in the impact</li> <li>• can check on ‘lost’ <math>p</math> i.e. other unallowed-for forces</li> </ul> <p><b>Improving timing method</b></p> <ul style="list-style-type: none"> <li>• not a priority as current method is not the weakest link</li> <li>• cut card with greater precision</li> <li>• measure length with better resolution (e.g. travelling microscope)</li> <li>• longer card to reduce percentage error</li> <li>• ensure card cuts light-gate beam at right angles (e.g. by observing and discarding results where it doesn’t)</li> </ul> <p><b>Other suggestions</b></p> <ul style="list-style-type: none"> <li>• use of linear air track</li> <li>• use of motion sensors (NOT tickertape)</li> <li>• can investigate <math>p</math>, <math>E_k</math> losses in trolley running along surface without collision to allow for these</li> </ul> <p><b>Use the L1, L2, L3 annotations in RM Assessor ; do not use ticks.</b></p>
<b>Section C Total</b>		17	

**OCR (Oxford Cambridge and RSA Examinations)**  
**1 Hills Road**  
**Cambridge**  
**CB1 2EU**

**OCR Customer Contact Centre**

**Education and Learning**

Telephone: 01223 553998

Facsimile: 01223 552627

Email: [general.qualifications@ocr.org.uk](mailto:general.qualifications@ocr.org.uk)

**[www.ocr.org.uk](http://www.ocr.org.uk)**

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

**Oxford Cambridge and RSA Examinations**  
**is a Company Limited by Guarantee**  
**Registered in England**  
**Registered Office; 1 Hills Road, Cambridge, CB1 2EU**  
**Registered Company Number: 3484466**  
**OCR is an exempt Charity**

**OCR (Oxford Cambridge and RSA Examinations)**  
**Head office**  
**Telephone: 01223 552552**  
**Facsimile: 01223 552553**

© OCR 2017

