wjec cbac

GCE AS MARKING SCHEME

SUMMER 2017

AS (NEW) PHYSICS AS UNIT 2 2420U20-1 PMT

INTRODUCTION

This marking scheme was used by WJEC for the 2017 examination. It was finalised after detailed discussion at examiners' conferences by all the examiners involved in the assessment. The conference was held shortly after the paper was taken so that reference could be made to the full range of candidates' responses, with photocopied scripts forming the basis of discussion. The aim of the conference was to ensure that the marking scheme was interpreted and applied in the same way by all examiners.

It is hoped that this information will be of assistance to centres but it is recognised at the same time that, without the benefit of participation in the examiners' conference, teachers may have different views on certain matters of detail or interpretation.

WJEC regrets that it cannot enter into any discussion or correspondence about this marking scheme.

GENERAL INSTRUCTIONS

Recording of marks

Examiners must mark in red ink.

One tick must equate to one mark (except for the extended response question).

Question totals should be written in the box at the end of the question.

Question totals should be entered onto the grid on the front cover and these should be added to give the script total for each candidate.

Marking rules

All work should be seen to have been marked.

Marking schemes will indicate when explicit working is deemed to be a necessary part of a correct answer.

Crossed out responses not replaced should be marked.

Credit will be given for correct and relevant alternative responses which are not recorded in the mark scheme.

Extended response question

A level of response mark scheme is used. Before applying the mark scheme please read through the whole answer from start to finish. Firstly, decide which level descriptor matches best with the candidate's response: remember that you should be considering the overall quality of the response. Then decide which mark to award within the level. Award the higher mark in the level if there is a good match with both the content statements and the communication statement.

Marking abbreviations

The following may be used in marking schemes or in the marking of scripts to indicate reasons for the marks awarded.

cao = correct answer only ecf = error carried forward bod = benefit of doubt

0.00	stion	Marking details		Marks av	vailable			
Que	5000		AO1	AO2	AO3	Total	Maths	Prac
1	(a)	$v = \frac{1}{nAe} \text{ correct transposition at any stage or by implication(1)} A = 12.00 \times 10^{-3} \text{ m} \times 2.00 \times 10^{-3} \text{ m} [= 2.4 \times 10^{-5} \text{m}^2] (1) v = 2.45 \times 10^{-5} \text{ [m s}^{-1]} (1) \text{ Accept } 2.5 \times 10^{-5} \text{ [m s}^{-1]}$		3		3	3	
	(b)	Energy = I^2Rt or equivalent used (1) 192 J [or 190 J] UNIT (1) Collisions between [free] <u>electrons and ions</u> [or atoms or lattice] (1)	1	1 1		3	2	
		Question 1 total	1	5	0	6	5	0

	0				Marks a	vailable			
	Questic	on	Marking details	AO1	AO2	AO3	Total	Maths	Prac
2	(a)	(i)	$\rho = \frac{RA}{L}$ correct transposition at any stage or by implication (1)		1				
			$A = \pi \left(\frac{d}{2}\right)^2 \text{ or equivalent correctly used to give value in m2 or}$ by implication (1) $\rho = 4.9 \times 10^{-7} \Omega \text{m} [\text{accept } 4.90 \times 10^{-7} \Omega \text{m}] \text{UNIT} (1)$ Only one mark lost for $20 \times 10^{-7} \Omega \text{m}$ or $19.6 \times 10^{-7} \Omega \text{m}$ No sig fig penalty	1	1		3	3	3
		(ii)	One mark penalty for working with uncertainties of half the resolutions without comment. No penalty if reasonable justification given. This applies to both methods below. <i>Fractional or percentage uncertainties method</i> In <i>r</i> : 0.02[1] or 2[.1]%. In <i>R</i> : 0.04 5 or 4.5% In <i>L</i> : 0 or 0.1% (1) Correct composition of individual fractional or percentage uncertainties (0.087 (8.7%) and 0.09 (9%)) (1) So 0.4 or 0.5 × 10 ⁻⁷ [Ω m] if 4.9 × 10 ⁻⁷ [Ω m] given in (i) or 0.39 to 0.44 × 10 ⁻⁷ [Ω m] if 4.90 × 10 ⁻⁷ [Ω m] given in (i) ecf (1) Only one mark penalty for omitting 10 ⁻⁷ in this part. <i>Maximum value method</i> $\frac{2.3 \times \pi \times (0.245 \times 10^{-3})^2}{0.811}$ or by implication (1) 5.34 or 5.35 × 10 ⁻⁷ [Ω m]], or 5.3 or 5.4 × 10 ⁻⁷ [Ω m] (1) So ± 0.4 or 0.5 × 10 ⁻⁷ [Ω m] if 4.90 × 10 ⁻⁷ [Ω m] given in (i) or 0.43, 0.44 or 0.45 × 10 ⁻⁷ [Ω m] if 4.90 × 10 ⁻⁷ [Ω m] in (i) (1) Answer to 1 or 2 sig figs only		3		3	3	3

Question	Marking dataila		Marks av	/ailable			
Question	Marking details	AO1	AO2	AO3	Total	Maths 6	Prac
(b)	 Longer wire (1) Don't accept more repeat readings Less percentage or fractional uncertainty in resistance (1) Don't accept less percentage or fractional uncertainty in length Or winding wire or equivalent to measure across several diameters at once (1) Less percentage error in diameter (1) 			2	2		2
	Question 2 total	1	5	2	8	6	8

	Oursetien	Marking dataila		Marks a	vailable			
	Question	Marking details	AO1	AO2	AO3	Total	Maths	Prac
3	(a)	$I = \frac{12.0 V}{450 \Omega + 150 \Omega} [= 0.020 \text{ A}] \text{ or equivalent or } \frac{V_{\text{out}}}{V_{\text{in}}} = \frac{150 \Omega}{450 \Omega + 150 \Omega} \text{ or}$ equivalent (1) Give mark if included in single equation (as below) $V_{\text{out}} = 0.020 A \times 150 \Omega$ or $\frac{150 \Omega}{450 \Omega + 150 \Omega} \times 12.0 \text{ V}$ and = 3[.0 V] [as required] (1)		1	1	2	2	
	(b)	Any valid power calculation i.e. $\frac{3^2}{150}$ or $\frac{9^2}{450}$ or $\frac{12^2}{600}$ (1) For 2nd mark: - If used $\frac{9^2}{450}$ power in R_1 is 0.18 W which is < 0.5 W or which meets requirement - If used $\frac{12^2}{600}$ total power is 0.24 W and therefore power in R_1 is < 0.5 W (1) If $\frac{3^2}{150}$ don't award 2 nd mark ecf on current and V_{out} from part (a)		1	1	2	2	
	(C)	$\frac{1}{R} = \frac{1}{150} + \frac{1}{600}$ or equivalent or by implication (1) $R = 120 [\Omega]$ (the modified R_2) (1) $V_{out} = 2.5 [V]$ or 2.53 [V] (1) So drop of > 0.4 V [therefore requirement not met] (give mark only if whole argument valid) (1) ecf on V_{out} from part (a)		1 1 1	1	4	2	
		Question 3 total	0	5	3	8	6	0

	0		Merking details		Marks a	vailable			
	Quest	ion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
4	(a)	(i)	$\lambda = 0.20 \text{ [m]}$ (or by implication) (1)						
			$v = \frac{0.20 [\text{m}]}{0.040 [\text{s}]}$ or 0.20 [m] × 25 [Hz] or 5.0 [m s ⁻¹]						
			or $d = 0.20 \text{ [m]} \times \frac{0.34 \text{ [s]}}{0.04 \text{ [s]}}$ (1)						
			d = 1.7 [m] (1)		3		3	2	
			Award 1 mark only if λ wrong but all else right						
		(ii)	Upside down, roughly same amplitude at least one complete cycle shown		1		1		
	(b)	(i)	[Point] that doesn't move or of no oscillation or of zero						
			(minimum) amplitude or of destructive interference or equiv (1)	-					
			0.10 [m] ecf (1) Don't accept $\frac{\lambda}{2}$	2			2		
		(ii)	Points between [successive] nodes in phase or points a						
			wavelength apart are in phase (1) Phase reversals at each node or equivalent (1)	2			2		
		(iii)	[Progressive] waves reflect [at clamp] (1)						
			[Progressive] waves travelling in opposite directions [reflected						
			covers this] and interfere or superpose (1) Accept specific case, e.g. waves travelling in opposite directions	2			2		
			and interfere destructively at nodes						
		(iv)	Nodes closer together or shorter wavelength		1		1		
			Accept more nodes or more antinodes						
			Question 4 total	6	5	0	11	2	0

PMT

Oursetien	Marking dataila					Marks available		
Question	Marking details	AO1	AO2	AO3	Total	Maths	Prac	
5 (a)	 Placing of laser slits, screen or travelling microscope or transverse ruler in words or diagram even if no suggested distances. Distance between slits and screen measured: stated with metre ruler or tape measure . Fringe separation/spacing measured with ruler [or travelling microscope] with details included e.g. between centres of fringes or across several fringes or repeat readings taken or use of magnifying glass or large slit-screen distance Slit-screen distance, slit separation / fringe separation 'put into formula' stated: λ = slit separation × fringe separation 'put guantities. No penalty for swapping <i>a</i> and <i>y</i>. 5-6 marks Comprehensive description of how to set up the apparatus, the measurements to be taken (including details of instruments / techniques) and how to determine the wavelength with the equation clearly stated. There is a sustained line of reasoning which is coherent, relevant, substantiated and logically structured. 3-4 marks Description of how to set up the apparatus, the measurement / technique and how to determine the wavelength with the equation stated. There is a line of reasoning which is partially coherent, largely relevant, supported by some evidence and with some structure. 	6			6		6	

Ques	tion	Marking dataila		Marks a	vailable			
Ques	tion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
		 1-2 marks Some correct attempt at either how to set up the apparatus, which measurements are taken and / or how the wavelength is determined. There is a basic line of reasoning which is not coherent, largely irrelevant, supported by limited evidence and with very little structure. 0 marks No attempt made or no response worthy of credit.						
(b)	(i)	Right angled triangle drawn and labelled with 0.6[00] on the correct side (1) adj side \approx hypot or sin $\theta_1 \approx \tan \theta_1$ (accept calculations) or equivalent (1)		2		2	2	
	(ii)	Correct insertion of values of d , $\sin \theta_1$ and $n = 1$ in equation or correct use of Youngs slits equation (1) $\lambda = 510 \text{ n[m]}$ (1)		2		2	2	
	(iii)	39 orders (1) ecf accept 39.2 orders Slit separation is very large [compared with λ] (1) Accept λ <u>much</u> less than slit separation		1	1	2	1	
		Question 5 total	6	5	1	12	5	6

	2	lan	Merking details		Marks a	vailable			
Ċ	Quest	ion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
6	(a)	(i)	Total internal reflection	1			1		
			Don't accept TIR						
		(ii)	$1.52 \sin \theta_{\rm C} = 1.33 [\sin 90^\circ]$ (1)						
			$\theta_{\rm C} = 61^{\circ} (1)$						
			45° (or angle of inc) < 61° (or $\theta_{\rm C}$) so won't work properly or no						
			TIR ecf (1)						
			Alternative: $1.52 \sin 45^\circ = 1.33 \sin \theta_w (1)$						
			$\theta_{\rm w} = 54^{\circ} \text{ or } \sin \theta_{\rm w} < 1 \text{ (1)}$						
			Light escapes or not TIR so won't work properly ecf (1)			3	3	3	
	(b)	(i)	$t = \frac{d}{n}$ in this transposed form, or by implication – ignore units and						
			accept omission of n (1)						
			$v = \frac{c}{n}$ or equivalents used or by implication (1)						
			n		3		3	3	
			7.6 μ[s] (1)						
		(ii)	Monomode fibre allow only one route/path for light [whereas						
			multimode fibres allow many] (1)						
			[Therefore] any one pulse arrives without spreading [over time]						
			(smearing) in a monomode fibre. Accept all light takes the same						
			time to travel through fibre. Accept converse point for thicker (1)	3			3		
			Hence likelihood of pulses overlapping [muddling] (1)	Ŭ			Ĵ		
			Question 6 total	4	3	3	10	6	0

	2		Mouling dataile		Marks a	vailable			
	Quest	ion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
7	(a)	(i)	Increase pd until microammeter reads zero. Or decrease pd until microammeter just starts to read a current (1) Reading of voltmeter <u>gives the energy value needed</u> or equivalent statement (1) Accept $E_k = eV_{stop}$	2			2		2
		(ii)	$\phi = \frac{6.63 \times 10^{-34} \times 3.00 \times 10^8}{405 \times 10^{-9}} [J](1) - 0.480 \times 1.60 \times 10^{-19} [J](1)$ $[4.91 \times 10^{-19}] \qquad [-7.68 \times 10^{-20}]$ or $\phi = \frac{6.63 \times 10^{-34} \times 3.00 \times 10^8}{405 \times 10^{-9} \times 1.60 \times 10^{-19}} [eV](1) - 0.480 [eV](1)$ $[3.07]$ even if not transposed $4.1 \times 10^{-19} [J] \text{ or } 2.6 [eV] (1)$		3		3	3	3
		(iii)	For 650 nm, photon energy = 3.1×10^{-19} J or 1.9 eV (1) Photon energy not enough to knock out electron or photon energy < ϕ (1) More photons [per second] won't help or increasing intensity doesn't increase photon energy (1) Accept only gives more photons at the same energy or doesn't change frequency Alternative Calculation of f_0 = 6.2×10^{14} [Hz] ecf or calculation of λ_0 = 4.8×10^{-7} [m] ecf (1) 4.6×10^{14} [Hz] < 6.2×10^{14} [Hz] or 650 nm is > 480 nm so no emission occurs (1) More photons [per second] won't help or increasing intensity doesn't increase photon energy (1) Accept only gives more photons at the same energy or doesn't change frequency - Subtract 1 mark if no useful reference made to photons			3	3		3

Questi	ion	Marking dataila		Marks a	vailable			
Luest	ion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
(b)	(i)	$v = \frac{h}{m\lambda}$ transposed and used (1) $v = 1.5 \times 10^7 \text{ [m s}^{-1]}$ (1)		2		2	2	
	(ii)	Electrons are wavelike or diffract or interfere (1) Accept reference to wave-particle duality Graphite crystals act as diffraction gratings or electrons diffract <u>between (around) atom</u> [s] (through lattice) or λ comparable with gaps between atoms (1)	2			2		
		Question 7 total	4	5	3	12	5	8

	Quest	ion	Marking dataila		Marks a	vailable			
	Quest	ion	Marking details	AO1	AO2	AO3	Total	Maths	Prac
8	(a)	(i)	Use of $\lambda = \frac{hc}{\Delta E}$ including wrong transition or equivalent (1) 1.55 µ[m] (1)		2		2	2	
		(ii)	Absorption: photon disappears or is absorbed or has its energy transferred (1)Electron promoted from L accept if state going to PStimulated em: [passing] photon demotes electron from U [to L] 	4			4		
		(iii)	Stimulated emission because more electrons <u>in U</u> [than L] Accept population inversion		1		1		
		(iv)	So P stays relatively empty to receive [pumped] electrons or so as not to impede pumping or equivalent or so as to keep the population of U high (1) To maintain high population in U or to maintain population inversion or equivalent (1)	2			2		

Ouestien	Marking details	Marks available					
Question		AO1	AO2	AO3	Total	Maths	Prac
(b)	 At least 1 from: no power loss in wires high power lasers very inefficient laser beam only travels in straight lines / wires are flexible less use of raw materials (e.g. copper) for laser beams no danger of electrocution with laser beams light isn't versatile needs to be transferred into other more useful forms reference to beam spreading and absorption Maximum of 3 from the following: no visual pollution cheaper because less raw materials used replacement cost very large danger to birds / aeroplanes, possibly to humans accept to anything getting in the way if intercepted cuts power 			4	4		
	Question 8 total	6	3	4	13	2	0

AS UNIT 2: ELECTRICITY AND LIGHT

SUMMARY OF MARKS ALLOCATED TO ASSESSMENT OBJECTIVES

Question	AO1	AO2	AO3	TOTAL MARK	MATHS	PRAC
1	1	5	0	6	5	0
2	1	5	2	8	6	8
3	0	5	3	8	6	0
4	6	5	0	11	2	0
5	6	5	1	12	5	6
6	4	3	3	10	6	0
7	4	5	3	12	5	8
8	6	3	4	13	2	0
TOTAL	28	36	16	80	37	22

WJEC GCE AS Physics Unit 2 MS/Summer 2017/ED

© WJEC CBAC Ltd.

PMT