

Q1.

3 (a)	f_0 is at natural frequency of spring (system) B1 this is at the driver frequency B1 (allow 1 mark for recognition that this is resonance)	[2]
(b)	line: amplitude less at all frequencies B1 peak flatter B1 peak at f_0 or slightly below f_0 B1	[3]
(c)	(aluminium) sheet cuts the magnetic flux/field B1 (so) currents/e.m.f. <u>induced</u> in the (metal) sheet B1 these currents dissipate energy M1 less energy available for the oscillations A1 so amplitude smaller A0 (‘current opposes motion of sheet’ scores one of the last two marks)	[4]

Q2.

4 (a)	e.g. amplitude is not constant or wave is damped B1 <i>do not allow ‘displacement constant’</i> should be $(-)\cos$, (not \sin) B1	[2]
(b)	$T = 0.60$ s C1 $\omega = 2\pi/T = 10.5 \text{ rad s}^{-1}$ (allow $10.4 \rightarrow 10.6$) A1	[2]
(c)	same period B1 displacement always less M1 amplitude reducing appropriately A1 <i>for 2nd and 3rd marks, ignore the first quarter period</i>	[3]
	Total	[7]

Q3.

4 (a)	acceleration proportional to displacement (from a fixed point) M1 <u>or</u> $a = -\omega^2 x$ with a , ω and x explained A1 and directed towards a fixed point A1 <u>or</u> negative sign explained	[2]
(b)	for s.h.m., $a = (-)\omega^2 x$ B1 identifies ω^2 as $A\rho g/M$ and therefore s.h.m. (may be implied) B1 $2\pi f = \omega$ B1 hence $f = \frac{1}{2\pi} \sqrt{\frac{A\rho g}{M}}$ A0	[3]
(c) (i)	$T = 0.60$ s <u>or</u> $f = 1.7$ Hz C1 $0.60 = (2\pi\sqrt{M})/\sqrt{(\pi \times \{1.2 \times 10^{-2}\}^2 \times 950 \times 9.81)}$ C1 $M = 0.0384$ kg A1	[3]
(ii)	<u>decreasing</u> peak height/amplitude B1	[1]

Q4.

- 4 (a) (i) 1.0 B1 [1]
 (ii) 40 Hz B1 [1]
- (b) (i) speed = $2\pi fa$ C1
 $= 2\pi \times 40 \times 42 \times 10^{-3}$
 $= 10.6 \text{ m s}^{-1}$ A1 [2]
- (ii) acceleration = $4\pi^2 f^2 a$ C1
 $= (80\pi)^2 \times 42 \times 10^{-3}$
 $= 2650 \text{ m s}^{-2}$ A1 [2]
- (c) (i) S marked correctly (on 'horizontal line through centre of wheel') B1
 (ii) A marked correctly (on 'vertical line' through centre of wheel) B1 [2]

Q5.

- 7 (a) (i) oscillations are damped/amplitude decreases B1
 as magnet moves, flux is cut by coil B1
 e.m.f./current is induced in the coil B1
 causing energy loss in load OR force on magnet B1
 energy is derived from oscillations of magnet
 OR force opposes motion of magnet B1 [5]
- (ii) $T = 0.60 \text{ s}$ C1
 $\omega_0 (= 2\pi/T) = 10.5 \text{ rad s}^{-1}$ A1 [2]
- (b) sketch: sinusoidal wave with period unchanged or slightly smaller M1
 same initial displacement, less damping A1 [2]
- (c) (i) sketch: general shape – peaked curve M1
 peak at ω_0 and amplitude never zero A1 [2]
- (ii) resonance B1 [1]
- (iii) useful: e.g. child on swing, microwave oven heating B1
 avoid: e.g. vibrating panels, vibrating bridges B1 [2]
 (for credit, stated example must be put in context)

Q6.

- 3 (a) (i) amplitude = 0.5 cm A1 [1]
 (ii) period = 0.8 s A1 [1]
- (b) (i) $\omega = 2\pi / T$ C1
 $= 7.85 \text{ rad s}^{-1}$
 correct use of $v = \omega \sqrt{(x_0^2 - x^2)}$ B1
 $= 7.85 \times \sqrt{\{(0.5 \times 10^{-2})^2 - (0.2 \times 10^{-2})^2\}}$
 $= 3.6 \text{ cm s}^{-1}$ A1 [3]
(if tangent drawn or clearly implied (B1)
 $3.6 \pm 0.3 \text{ cm s}^{-1}$ (A2)
but allow 1 mark for $> \pm 0.3$ but $\leq \pm 0.6 \text{ cm s}^{-1}$)
- (ii) $d = 15.8 \text{ cm}$ A1 [1]
- (c) (i) (continuous) loss of energy / reduction in
 amplitude (from the oscillating system)
 caused by force acting in opposite direction to the motion / friction /
 viscous forces B1
B1 [2]
- (ii) same period / small increase in period B1
 line displacement always less than that on Fig.3.2 (*ignore first T/4*) M1
 peak progressively smaller A1 [3]

Q7.

- 3 (a) (i) to-and-fro / backward and forward motion (between two limits) B1 [1]
 (ii) no energy loss or gain / no external force acting / constant energy / constant amplitude B1 [1]
 (iii) acceleration directed towards a fixed point B1
 acceleration proportional to distance from the fixed point / displacement B1 [2]
- (b) acceleration is constant (magnitude) M1
 so cannot be s.h.m. A1 [2]

Q8.

- 2 (a) (i) reduction in energy (of the oscillations) (B1)
 reduction in amplitude / energy of oscillations (B1)
 due to force (always) opposing motion / resistive forces (B1) [2]
 any two of the above, max 2
- (ii) amplitude is decreasing (very) gradually / oscillations would
 continue (for a long time) / many oscillations M1
 light damping A1 [2]
- (b) (i) frequency = $1 / 0.3$
 = 3.3 Hz A1 [1]
 allow points taken from time axis giving $f = 3.45$ Hz
- (ii) energy = $\frac{1}{2} mv^2$ and $v = \omega a$ C1
 = $\frac{1}{2} \times 0.065 \times (2\pi/0.3)^2 \times (1.5 \times 10^{-2})^2$ M1
 = 3.2 mJ A0 [2]
- (c) amplitude reduces exponentially / does not decrease linearly M1
 so will be not be 0.7 cm A1 [2]

Q9.

- 3 (a) acceleration / force proportional to displacement from a fixed point M1
 acceleration / force (always) directed towards that fixed point / in opposite
 direction to displacement A1 [2]
- (b) (i) $A\rho g / m$ is a constant and so acceleration proportional to x B1
 negative sign shows acceleration towards a fixed point / in opposite
 direction to displacement B1 [2]
- (ii) $\omega^2 = (A\rho g / m)$ C1
 $\omega = 2\pi f$ C1
 $(2 \times \pi \times 1.5)^2 = \{(4.5 \times 10^{-4} \times 1.0 \times 10^3 \times 9.81) / m\}$ C1
 $m = 50$ g A1 [4]

Q10.

- 4 (a) $a = (-)\omega^2 x$ and $\omega = 2\pi/T$ C1
 $T = 0.60$ s C1
 $a = (4\pi^2 \times 2.0 \times 10^{-2}) / (0.6)^2$
 = 2.2 ms^{-2} A1 [3]
- (b) sinusoidal wave with all values positive B1
 all values positive, all peaks at E_k and energy = 0 at $t = 0$ B1
 period = 0.30 s B1 [3]

Q11.

- 2 (a) energy = $\frac{1}{2}m\omega^2a^2$ and $\omega = 2\pi f$ C1
 $= \frac{1}{2} \times 37 \times 10^{-3} \times (2\pi \times 3.5)^2 \times (2.8 \times 10^{-2})^2$ M1
 $= 7.0 \times 10^{-3} \text{ J}$ A0 [2]
 (allow $2\pi \times 3.5$ shown as 7π)
 Energy = $\frac{1}{2}mv^2$ and $v = r\omega$ (C1)
 Correct substitution (M1)
 Energy = $7.0 \times 10^{-3} \text{ J}$ (A0)
- (b) $E_K = E_P$ C1
 $\frac{1}{2}m\omega^2(a^2 - x^2) = \frac{1}{2}m\omega^2x^2$ or E_K or $E_P = 3.5 \text{ mJ}$ C1
 $x = a/\sqrt{2} = 2.8/\sqrt{2}$ or $E_K = \frac{1}{2}m\omega^2(a^2 - x^2)$ or $E_P = \frac{1}{2}m\omega^2x^2$ A1 [3]
 $= 2.0 \text{ cm}$
 (E_K or $E_P = 7.0 \text{ mJ}$ scores 0/3)
 Allow: $k = 17.9$ (C1)
 $E = \frac{1}{2}kx^2$ (C1)
 $x = 2.0 \text{ cm}$ (A1)
- (c) (i) graph: horizontal line, y-intercept = 7.0 mJ with end-points of line at +2.8 cm and -2.8 cm B1 [1]
 (ii) graph: reasonable curve B1
 with maximum at (0, 7.0) end-points of line at (-2.8, 0) B1 [2]
 and (+2.8, 0)
 (iii) graph: inverted version of (ii) M1
 with intersections at (-2.0, 3.5) and (+2.0, 3.5) A1 [2]
 (Allow marks in (iii), but not in (ii), if graphs K & P are not labelled)
- (d) gravitational potential energy B1 [1]

Q12.

- 3 (a) (i) 1. amplitude = 1.7 cm A1 [1]
2. period = 0.36 cm C1
 frequency = $1/0.36$ A1 [2]
 = 2.8 Hz
- (ii) $a = (-)\omega^2 x$ and $\omega = 2\pi/T$ C1
 acceleration = $(2\pi/0.36)^2 \times 1.7 \times 10^{-2}$ M1
 = 5.2 ms^{-2} A0 [2]
- (b) graph: straight line, through origin, with negative gradient M1
 from $(-1.7 \times 10^{-2}, 5.2)$ to $(1.7 \times 10^{-2}, -5.2)$ A1 [2]
(if scale not reasonable, do not allow second mark)
- (c) either kinetic energy = $\frac{1}{2}m\omega^2(x_0^2 - x^2)$ B1
 or potential energy = $\frac{1}{2}m\omega^2 x^2$ and potential energy = kinetic energy C1
 $\frac{1}{2}m\omega^2(x_0^2 - x^2) = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$ or $\frac{1}{2}m\omega^2 x^2 = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$
 $x_0^2 = 2x^2$
 $x = x_0 / \sqrt{2} = 1.7 / \sqrt{2}$ A1 [3]
 = 1.2 cm

Q13.

- 3 (a) (i) $\omega = 2\pi / T$ C1
 = $2\pi / 0.69$ A1 [2]
 = 9.1 rad s^{-1}
 (allow use of $f = 1.5 \text{ Hz}$ to give $\omega = 9.4 \text{ rad s}^{-1}$)
- (ii) 1. $x = 2.1 \cos 9.1t$ B1
 2.1 and 9.1 numerical values B1 [2]
 use of cos
2. $v_0 = 2.1 \times 10^{-2} \times 9.1$ (allow ecf of value of x_0 from (ii)1.) B1
 = 0.19 m s^{-1} B1 [2]
 $v = v_0 \sin 9.1t$ (allow cos 9.1t if sin used in (ii)1.)
- (b) energy = either $\frac{1}{2}mv_0^2$ or $\frac{1}{2}m\omega^2 x_0^2$ C1
 = either $\frac{1}{2} \times 0.078 \times 0.19^2$ or $\frac{1}{2} \times 0.078 \times 9.1^2 \times (2.1 \times 10^{-2})^2$ A1 [2]
 = $1.4 \times 10^{-3} \text{ J}$

Q14.

- 3 (a) (i) constant amplitude B1
 (ii) period = 0.75 s ... (allow ± 0.2 s) C1
 $\omega = 2\pi/T$ C1
 $\omega = 8.4 \text{ rad s}^{-1}$... (-1 for 1 sf) A1
 (iii) either use of gradient or $v = \omega y_0$ C1
 $v = 0.168 \text{ m s}^{-1}$ A1 [6]
 (allow ± 0.02 for construction: gradient drawn at wrong place 0/2)
- (b) (i) 1.3 Hz B1
 (ii) at $\frac{1}{2}f_0$, 'pulse' provided to mass on alternate/some oscillations M1
 so 'pulses' build up the amplitude A1 [3]

Q15.

- 2 (a) (i) a, ω and x identified (-1 each error or omission) B2
 (ii) (-)ve because a and x in opposite directions
 OR a directed towards mean position/centre B1 [3]
- (b) (i) forces in springs are $k(e + x)$ and $k(e - x)$ C1
 resultant = $k(e + x) - k(e - x)$ M1
 $= 2kx$ A0 [2]
- (ii) $F = ma$ B1
 $a = -2kx/m$ A0
 (-)ve sign explained B1 [2]
- (iii) $\omega^2 = 2k/m$ C1
 $(2\pi f)^2 = (2 \times 120)/0.90$ C1
 $f = 2.6 \text{ Hz}$ A1 [3]
- (c) atom held in position by attractive forces
 atom oscillates,
 not just two forces OR 3D not 1D
 force not proportional to x
 any two relevant points, 1 each, max 2 B2 [2]

Q16.

3	(a)	(i)	reasonable shape as 'inverse' of k.e. line	1	
		(ii)	straight line, parallel to x-axis at 15 mJ	1	[2]
	(b)	either	(max) kinetic energy ($= \frac{1}{2}mv^2$) $= \frac{1}{2}m\omega^2a_0^2$	1	
			$15 \times 10^{-3} = \frac{1}{2} \times 0.15 \times \omega^2 \times (5.0 \times 10^{-2})^2$	1	
			$\omega = 8.9(4) \text{ rad s}^{-1}$	1	
		or	(k.e. $= \frac{1}{2}mv^2$), $v = 0.44(7) \text{ m s}^{-1}$	1	
			$\omega = v/a = (0.447)/(5.0 \times 10^{-2})$	1	
			$\omega = 8.9(4) \text{ rad s}^{-1}$	1	[3]
	(c)	(i)	either loss of energy (from the system) or amplitude decreases or additional force acting (on the mass)	1	
			either continuous/gradual loss or force always opposing motion	1	[2]
		(ii)	either (now has 80% of its) p.e./k.e. = 12 mJ or loss in k.e. = 3 mJ	1	
			new amplitude = 4.5 cm (allow $\pm 0.1 \text{ cm}$)	1	[2]

Q17.

4	(a)(i)	$\omega = 2\pi f$	C1	
		$= 2\pi \times 1400$		
		$= 8800 \text{ rad s}^{-1}$	A1	[2]
	(ii)	$a_0 = (-)\omega^2 x_0$	C1	
		$= (8800)^2 \times 0.080 \times 10^{-3}$		
		$= 6200 \text{ m s}^{-2}$	A1	[2]
	(b)	straight line through origin with negative gradient	M1	
		end points of line correctly labelled	A1	[2]
	(c)(i)	zero displacement	B1	[1]
	(ii)	$v = \omega x_0$	C1	
		$= 8800 \times 0.080 \times 10^{-3}$		
		$= 0.70 \text{ m s}^{-1}$	A1	[2]

Q18.

3	(a)	use of $a = -\omega^2 x$ clear	C1	
		either $\omega = \sqrt{(2k/m)}$ or $\omega^2 = (2k/m)$	B1	
		$\omega = 2\pi f$	C1	
		$f = (1/2\pi)\sqrt{(2 \times 300)/0.240}$	B1	
		$= 7.96 \approx 8 \text{ Hz}$	A0	[4]
	(b)	(i) resonance	B1	[1]
		(ii) 8 Hz	B1	[1]
	(c)	(increase amount of) damping	B1	
		without altering (k or) m ... (some indirect reference is acceptable)	B1	
		sensible suggestion	B1	[3]

Q19.

- 3 (a) (i) 0.8 cmB1 [1]
- (ii) (max.) kinetic energy = 2.56 mJC1
 $v_{(MAX)} = \omega a$ C1
 (max.) kinetic energy = $\frac{1}{2}m\omega^2 a^2$ or $\frac{1}{2}m\omega^2 (a^2 - x^2)$ C1
 $2.56 \times 10^{-3} = \frac{1}{2} \times 0.130 \times \omega^2 \times (0.8 \times 10^{-2})^2$ M1
 $\omega = 24.8 \text{ rad s}^{-1}$ C1
 $f = \omega/2\pi$ M1
 = 4.0 Hz (3.95 Hz)A0 [6]
- (b) (i) line parallel to x-axis at 2.56 mJB1 [1]
- (ii) 1 4.0 HzB1
 2 0.50 cm (allow ± 0.03 cm)B1 [2]

Q20.

- 3 (a) acceleration / force (directly) proportional to displacement M1
 and either directed towards fixed point
 or acceleration & displacement in opposite directions A1 [2]
- (b) (i) maximum / minimum height / 8 mm above cloth / 14 mm below cloth B1 [1]
- (ii) 1. $a = 11 \text{ mm}$ A1 [1]
 2. $\omega = 2\pi f$ C1
 $= 2\pi \times 4.5$
 $= 28.3 \text{ rad s}^{-1}$ (do not allow 1 s.f.) A1 [2]

© UCLES 2008

Page 3	Mark Scheme	Syllabus	Paper
	GCE A/AS LEVEL – October/November 2008	9702	04

- (c) (i) $v = \omega a$ C1
 $= 28.3 \times 11 \times 10^{-3}$
 $= 0.31 \text{ m s}^{-1}$ (do not allow 1 s.f.) A1 [2]
- (ii) $v = \omega \sqrt{(a^2 - y^2)}$
 $y = 3 \text{ mm}$ C1
 $= 28.3 \times 10^{-3} \sqrt{(11^2 - 3^2)}$ C1
 $= 0.30 \text{ m s}^{-1}$ (allow 1 s.f.) A1 [3]

Q21.

- 4 (a) (i) amplitude = 0.2 mm A1 [1]
 (ii) period = 1.2 ms C1
 frequency = 830 Hz A1 [2]
- (b) (i) any two of zero, 0.6 ms and 1.2 ms A1 [1]
 (ii) any two of 0.3 ms, 0.9 ms, 1.5 ms A1 [1]
- (c) either $v = \omega x_0 = 2\pi f x_0$
 $= 2\pi \times 830 \times 0.2 \times 10^{-3} = 1.05 \text{ m s}^{-1}$
 or slope of graph = 1.0 m s^{-1} (allow $\pm 0.1 \text{ m s}^{-1}$) C1
 $E_k = \frac{1}{2}mv^2$
 $= \frac{1}{2} \times 2.5 \times 10^{-3} \times 1.05^2$ C1
 $= 1.4 \times 10^{-3} \text{ J}$ A1 [3]
- (d) (i) large / maximum amplitude of vibration B1
 when impressed frequency equals natural frequency of vibration B1 [2]
- (ii) e.g. metal panels on machinery vibrate / oscillate (M1)
 motor in machine impresses frequency on panel (A1)
 e.g. car suspension system vibrates / oscillates (M1)
 going over bumps would give large amplitude vibrations (A1)
 any feasible example, M1 + A1 [2]

[Total: 12]

Q22.

- 3 (a) straight line through origin B1
 negative gradient B1 [2]
- (b) $a = -\omega^2 x$ and $\omega = 2\pi f$ C1
 $750 = (2\pi f)^2 \times 0.3 \times 10^{-3}$ C1
 $f = 250 \text{ Hz}$ A1 [3]
- (c) straight line between (-0.3,+190) and (+0.3,-190) A2 [2]
 (allow 1 mark for end of line incorrect by one grid square or line does not extend to +/- 0.3 mm)

[Total: 7]

Q23.

- 3 (a) (i) resonance B1 [1]
(ii) amplitude 16 mm and frequency 4.6 Hz A1 [1]
- (b) (i) $a = (-)\omega^2 x$ and $\omega = 2\pi f$ C1
 $a = 4\pi^2 \times 4.6^2 \times 16 \times 10^{-3}$ C1
 $= 13.4 \text{ m s}^{-2}$ A1 [3]
- (ii) $F = ma$ C1
 $= 150 \times 10^{-3} \times 13.4$
 $= 2.0 \text{ N}$ A1 [2]
- (c) line always 'below' given line and never zero M1
peak is at 4.6 Hz (or slightly less) and flatter A1 [2]

Q24.

- 3 (a) (i) 8.0 cm A1 [1]
- (ii) $2\pi f = 220$ C1
 $f = 35$ (condone unit) A1 [2]
- (iii) line drawn mid-way between AB and CD (allow $\pm 2 \text{ mm}$) B1 [1]
- (iv) $v = \omega a$ C1
 $= 220 \times 4.0$
 $= 880 \text{ cm s}^{-1}$ A1 [2]
- (b) (i) 1. line drawn 3 cm above AB (allow $\pm 2 \text{ mm}$) B1 [1]
2. arrow pointing upwards B1 [1]
- (ii) 1. line drawn 3 cm above AB (allow $\pm 2 \text{ mm}$) B1 [1]
2. arrow pointing downwards B1 [1]
- (iii) $v = \omega \sqrt{a^2 - x^2}$ C1
 $= 220 \times \sqrt{4.0^2 - 2.0^2}$
 $= 760 \text{ cm s}^{-1}$ A1 [2]
(incorrect value for x , 0/2 marks)

Q25.

- 3 (a) (i) amplitude remains constant B1 [1]
- (ii) amplitude decreases gradually M1
light damping A1 [2]
- (iii) period = 0.80 s C1
frequency = 1.25 Hz (period not 0.8 s, then 0/2) A1 [2]

Q26.

- 3 (a) acceleration proportional to displacement/distance from fixed point and in opposite directions/directed towards fixed point M1
A1 [2]
- (b) energy = $\frac{1}{2}m\omega^2x_0^2$ and $\omega = 2\pi f$ C1
 $= \frac{1}{2} \times 5.8 \times 10^{-3} \times (2\pi \times 4.5)^2 \times (3.0 \times 10^{-3})^2$ C1
 $= 2.1 \times 10^{-5} \text{ J}$ A1 [3]
- (c) (i) at maximum displacement above rest position M1
A1 [2]
- (ii) acceleration = $(-)\omega^2x_0$ and acceleration = 9.81 or g C1
 $9.81 = (2\pi \times 4.5)^2 \times x_0$
 $x_0 = 1.2 \times 10^{-2} \text{ m}$ A1 [2]

Q27.

- 4 (a) straight line through origin M1
shows acceleration proportional to displacement A1
negative gradient M1
shows acceleration and displacement in opposite directions A1 [4]

© Cambridge International Examinations 2012

Page 3	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	41

- (b) (i) 2.8 cm A1 [1]
- (ii) either gradient = ω^2 and $\omega = 2\pi f$ or $a = -\omega^2x$ and $\omega = 2\pi f$ C1
gradient = $13.5 / (2.8 \times 10^{-2}) = 482$
 $\omega = 22 \text{ rad s}^{-1}$ C1
frequency = $(22/2\pi) = 3.5 \text{ Hz}$ A1 [3]
- (c) e.g. lower spring may not be extended
e.g. upper spring may exceed limit of proportionality / elastic limit
(any sensible suggestion) B1 [1]

Q28.

- 2 (a) (i) 1. 0.1 s, 0.3 s, 0.5 s, etc (*any two*) A1 [1]
 2. either 0, 0.4 s, 0.8 s, 1.2 s
 or
 0.2 s, 0.6 s, 1.0 s (*any two*) A1 [1]
- (ii) period = 0.4 s C1
 frequency = $(1/0.4) = 2.5\text{ Hz}$ A1 [2]
- (iii) phase difference = 90° or $\frac{1}{2}\pi$ rad B1 [1]
- (b) frequency = 2.4 – 2.5 Hz B1 [1]
- (c) e.g. attach sheet of card to trolley M1
 increases damping / frictional force A1
 e.g. reduce oscillator amplitude (M1)
 reduces power/energy input to system (A1) [2]

Q29.

- 3 (a) (i) any two from 0.3(0) s, 0.9(0) s, 1.50 s (*allow 2.1 s etc.*) B1 [1]
- (ii) either $v = \omega x$ and $\omega = 2\pi/T$ C1
 $v = (2\pi/1.2) \times 1.5 \times 10^{-2}$ M1
 $= 0.079\text{ ms}^{-1}$ A0 [2]
 or gradient drawn clearly at a correct position (C1)
 working clear (M1)
 to give $(0.08 \pm 0.01)\text{ m s}^{-1}$ (A0)

Page 3	Mark Scheme	Syllabus	Paper
	GCE A LEVEL – October/November 2013	9702	41

- (b) (i) sketch: curve from $(\pm 1.5, 0)$ passing through $(0, 25)$ M1
 reasonable shape (*curved with both intersections between*
 $y = 12.0 \rightarrow 13.0$) A1 [2]
- (ii) at max. amplitude potential energy is total energy B1
 total energy = 4.0 mJ B1 [2]

Q30.

- 4 (a) kinetic (energy)/KE/ E_k B1 [1]
- (b) *either* change in energy = 0.60 mJ
 or max E proportional to (amplitude)²/equivalent numerical working B1
 new amplitude is 1.3 cm B1
 change in amplitude = 0.2 cm B1 [3]

Q31.

- 4 (a) acceleration/force proportional to displacement (from a fixed point) M1
either acceleration and displacement in opposite directions A1 [2]
 or acceleration always directed towards a fixed point
- (b) (i) g and r are constant so a is proportional to x B1
 negative sign shows a and x are in opposite directions B1 [2]
- (ii) $\omega^2 = g/r$ and $\omega = 2\pi/T$ C1
 $\omega^2 = 9.8/0.28$
 $= 35$ C1
 $T = 2\pi/\sqrt{35} = 1.06$ s
 time interval $\tau = 0.53$ s A1 [3]
- (c) sketch: time period constant (or increases very slightly) M1
 drawn line always 'inside' given loops A1
 successive decrease in peak height A1 [3]

Q32.

- 1 (a) (i) *either* $\omega = 2\pi/T$ or $\omega = 2\pi f$ and $f = 1/T$ C1
 $\omega = 2\pi/0.30$
 $= 20.9$ rad s⁻¹ (accept 2 s.f.) A1 [2]
- (ii) kinetic energy = $\frac{1}{2}m\omega^2x_0^2$ or $v = \omega x_0$ and $\frac{1}{2}mv^2$ C1
 $= \frac{1}{2} \times 0.130 \times 20.9^2 \times (1.5 \times 10^{-2})^2 = 6.4 \times 10^{-3}$ J A1 [2]
- (b) (i) as magnet moves, flux is cut by cup/aluminium giving rise to induced e.m.f. (in cup) B1
 induced e.m.f. gives rise to currents and heating of the cup B1
 thermal energy derived from oscillations of magnet so amplitude decreases B1
 or
 induced e.m.f. gives rise to currents which generate a magnetic field (B1)
 the magnetic field opposes the motion of the magnet so amplitude decreases (B1) [3]
- (ii) *either* use of $\frac{1}{2}m\omega^2x_0^2$ and $x_0 = 0.75$ cm or x_0 is halved so $\frac{1}{4}$ energy C1
 to give new energy = 1.6 mJ
either loss in energy = $6.4 - 1.6$ or loss = $\frac{3}{4} \times 6.4$ giving loss = 4.8 mJ A1 [2]
- (c) $q = mc\Delta\theta$
 $4.8 \times 10^{-3} = 6.2 \times 10^{-3} \times 910 \times \Delta\theta$ C1
 $\Delta\theta = 8.5 \times 10^{-4}$ K A1 [2]

Q33.

- 4 (a) acceleration/force proportional to displacement (from a fixed point) M1
either acceleration and displacement in opposite directions A1 [2]
or acceleration always directed towards a fixed point
- (b) (i) zero & 0.625 s *or* 0.625 s & 1.25 s *or* 1.25 s & 1.875 s *or* 1.875 s & 2.5 s A1 [1]
- (ii) 1. $\omega = 2\pi/T$ *and* $v_0 = \omega x_0$ C1
 $\omega = 2\pi/1.25$ C1
 $= 5.03 \text{ rad s}^{-1}$
- $v_0 = 5.03 \times 3.2$
 $= 16.1 \text{ cm s}^{-1}$ (allow 2 s.f.) A1 [3]
2. $v = \omega\sqrt{(x_0^2 - x^2)}$
either $\frac{1}{2}\omega a = \omega\sqrt{(x_0^2 - x^2)}$ *or* $\frac{1}{2} \times 16.1 = 5.03\sqrt{(3.2^2 - x^2)}$ C1
 $x_0^2/4 = x_0^2 - x^2$ 2.58 = 3.2^2 - x^2
 $x = 2.8 \text{ cm}$ x = 2.8 cm A1 [2]
- (c) sketch: loop with origin at its centre M1
correct intercepts & shape based on (b)(ii) A1 [2]

