

Definitions and Concepts for WJEC (Eduqas) Physics GCSE

Topic 8: Magnetism and Electromagnetism

*Definitions in **bold** are for higher tier only*

Definitions marked by '' are for separate sciences only*

Alternating Current: Current flow consisting of charges that continually change direction. These oscillations usually occur at a set frequency.

Alternator: A device that makes use of the generator effect to generate alternating current.

Current-Carrying Wires: When current flows through a wire, a magnetic field is generated around it. The strength of the field depends on the magnitude of the current and the distance from the wire.

Dynamo: A device that makes use of the generator effect to generate direct current.

Electric Motor: A current-carrying coil of wire in a magnetic field. The two sides of the coil that are perpendicular to the magnetic field experience forces in opposite directions, causing rotation.

Electromagnet: A solenoid with an iron core.

Fleming's Left-Hand Rule: A rule used to determine the orientation of the force (thumb), current (second finger) and magnetic field (first finger) when a current-carrying wire is placed in a magnetic field (motor effect).

Force on a Wire: When a current-carrying wire is placed perpendicular to a magnetic field, a force is exerted on it. The force is proportional to the magnetic flux density of the field and proportional to the current and length of the wire.

Generator Effect: When there is relative motion between an electrical conductor and a magnetic field, a potential difference will be induced across the ends of the conductor. A current will flow if this conductor is part of a complete circuit.

This work by [PMT Education](https://www.pmt.education) is licensed under [CC BY-NC-ND 4.0](https://creativecommons.org/licenses/by-nc-nd/4.0/)



Induced Magnet: A material that becomes a magnet when it is placed in an existing magnetic field, but loses its magnetism quickly once it is removed. Induced magnetism always produces attractive forces.

Like Magnetic Poles: When matching poles of a magnet are brought near each other they repel each other.

Loudspeaker: A device that converts variations in current into vibrations of a diaphragm to produce corresponding sound waves.

Magnetic Field Lines: Lines that show the strength and direction of a magnetic field. The lines point from North to South and their concentration represents the magnitude of the field.

Magnetic Field: The region around a magnet in which another magnet or magnetic material will experience a non-contact force.

Magnetic Materials: Iron, steel, cobalt and nickel.

Magnetic Poles: The regions of a magnet where the magnetic forces are at their strongest.

Microphone: A device that converts the pressure variations in sound into corresponding current variations.

Permanent Magnet: A magnet that produces its own magnetic field.

Power Cables: Metal wires that are part of the National Grid. Electricity is transported along them at very high voltages to reduce the energy loss and make the transportation more efficient.

Solenoid: A wire wrapped into the shape of a coil, that has a strong and uniform magnetic field inside of it. The solenoid's magnetic field strength can be increased by adding an iron core.

Step-Down Transformer: A transformer that has a smaller potential difference in the secondary coil than in the primary coil. This is a result of the secondary coil having fewer turns.

Step-Up Transformer: A transformer that has a larger potential difference in the secondary coil than in the primary coil. This is a result of the secondary coil having more turns.

Transformer: An iron core with a primary and secondary coil of wire wound around opposite ends. Transformers can change the magnitude of an alternating voltage.



Turns Ratio: The number of turns in the primary coil of a transformer over the number of turns in the secondary coil. This is equal to the voltage ratio for a 100% efficient transformer.

Unlike Magnetic Poles: When opposite poles of a magnet are brought near each other they attract each other.

Voltage Ratio: The potential difference across the primary coil of a transformer over the potential difference across the secondary coil.

