1	(a		uid evaporates) at any temperature/below the boiling point/over a range of eratures/below 100°C/at different temperatures/not at a fixed temperature	B1	
		(during evaporation) vapour forms at/escapes from the surface of the liquid			
			out a supply of thermal energy,) evaporation continues/occurs/doesn't stop auses liquid to cool/is slower/reduces		
	(b)		(Q =) <i>mL</i> OR 0.075 × 2.25 × 10 <sup>6</sup>	C1	
			1.7 × 10 <sup>5</sup> J	A1	
		• •	( <i>E</i> =) <i>VIt</i> OR 240 × 0.65 × (20 × 60) OR <i>P</i> = <i>IV</i> <u>and</u> <i>P</i> = <i>E</i> / <i>t</i> OR energy/time	C1	
			1.9 × 10 <sup>5</sup> J	A1	
	(		energy is transferred <u>to the surroundings</u> OR in heating the surroundings/air/atmosphere/h <b>ot-</b> plate		
				otal: 8]	
2	(8	<ul> <li>molecules OR atoms OR particles speed OR velocity OR kinetic energy molecules OR atoms OR particles (Surface) area any four correct gains 2 marks, two or three correct gains 1 mark</li> </ul>		B2	
	(k	o) (i)	<ul> <li>(i) (when cap is screwed on) at top of mountain: pressure of air in bottle = the low pressure of the air outside OR is less than pressure at bottom of mountain OR is low</li> </ul>	B1	
			(at bottom of mountain) bottle collapses because pressure outside (bottle) is greater than pressure inside	B1	
		(ii)	Boyle's law applies OR $PV$ = constant OR $P_1V_1 = P_2V_2$ 9.2 × 10 <sup>4</sup> × V = 4.8 × 10 <sup>4</sup> × 250 130 cm <sup>3</sup>	C1 C1 A1	
				[Total: 7]	

1

3	(a)	(	smaller because <u>area</u> smaller	B1	
		(ii)	smaller because depth/height smaller	B1	
	(b)	(	h ho g OR 12 × 1000 × 10 1.2 × 10 <sup>5</sup> Pa OR 1.1772 × 10 <sup>5</sup> Pa OR 1.176 × 10 <sup>5</sup> Pa accept N/m <sup>2</sup>	C1 A1	
		(ii)	candidate's (i) + 1.0 × $10^5$ Pa correctly evaluated with unit (correct value 2.2 × $10^5$ )	в	
		(iii)	$p_1V_1 = p_2V_2$ in any form 1.1 cm <sup>3</sup>	C1	
			OR 0.5 × candidate's (ii)/10 <sup>5</sup> correctly evaluated	A1	
	(	(iv)	value in (iii) too small OR volume larger o.w.t.t.e.	B1	[8]

(a	(i)	increases	B1
	(ii)	pV = const_in any form 1.05 (× 10 <sup>5</sup> ) × 860 (× 10 <sup>-6</sup> ) = p × 645 (× 10 <sup>-6</sup> ) 1.4 × 10 <sup>5</sup> Pa	C1 C A1

(iii)	F = pA	A in any form accept weight for F	C1
	EITHE		C1
		$0.35 \times 10^5 \times 5.0 \times 10^3$	C1
		175 N (minimum 2 s.f.) c.a.o.	A1
	OR	$1.05 \times 10^5 \times 5.0 \times 10^{3}$ or 525 N or $1.4 \times 10^5 \times 5.0 \times 10^{3}$ or 700 N	(C1)
		700 – 525 N e.c.f. from (a) (ii)	(C1)
		175 N (minimum 2 s.f.) c.a.o.	(A1)

(b)	increases	B1
(ii)	no change	B1
(iii)	extra weight (on tray/piston)	B1
(iv)	increases	B1

[12]

4

5	(a	increase surface area of tank blow air over surface/put in windy place			2
	(b)	(i)	capillary tube longer or liquid with lower expansivity	B1	
		(ii)	capillary tube thinner/finer or liquid with higher expansivity or bigger bulb	B1	2
	(c)	p <sub>1</sub> v <sub>1</sub> p <sub>2</sub> =	= p <sub>2</sub> v <sub>2</sub> or 1 x 10 <sup>5</sup> x 150 = p <sub>2</sub> x50 3 x 10 <sup>5</sup> (Pa)	C1 A1	2 [6]