

GCE

Mathematics

Advanced GCE

Unit 4730: Mechanics 3

Mark Scheme for June 2013

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

OCR will not enter into any discussion or correspondence in connection with this mark scheme.

© OCR 2013

Annotations and abbreviations

Annotation in scoris	Meaning
√and x	
BOD	Benefit of doubt
FT	Follow through
ISW	Ignore subsequent working
M0, M1	Method mark awarded 0, 1
A0, A1	Accuracy mark awarded 0, 1
B0, B1	Independent mark awarded 0, 1
SC	Special case
۸	Omission sign
MR	Misread
Highlighting	
Other abbreviations in	Meaning
mark scheme	
E1	Mark for explaining
U1	Mark for correct units
G1	Mark for a correct feature on a graph
M1 dep*	Method mark dependent on a previous mark, indicated by *
cao	Correct answer only
oe	Or equivalent
rot	Rounded or truncated
soi	Seen or implied
www	Without wrong working

Subject-specific Marking Instructions for GCE Mathematics (OCR) Mechanics strand

a Annotations should be used whenever appropriate during your marking.

The A, M and B annotations must be used on your standardisation scripts for responses that are not awarded either 0 or full marks. It is vital that you annotate standardisation scripts fully to show how the marks have been awarded.

For subsequent marking you must make it clear how you have arrived at the mark you have awarded.

An element of professional judgement is required in the marking of any written paper. Remember that the mark scheme is designed to assist in marking incorrect solutions. Correct solutions leading to correct answers are awarded full marks but work must not be judged on the answer alone, and answers that are given in the question, especially, must be validly obtained; key steps in the working must always be looked at and anything unfamiliar must be investigated thoroughly.

Correct but unfamiliar or unexpected methods are often signalled by a correct result following an *apparently* incorrect method. Such work must be carefully assessed. When a candidate adopts a method which does not correspond to the mark scheme, award marks according to the spirit of the basic scheme; if you are in any doubt whatsoever (especially if several marks or candidates are involved) you should contact your Team Leader.

c The following types of marks are available.

M

A suitable method has been selected and *applied* in a manner which shows that the method is essentially understood. Method marks are not usually lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, eg by substituting the relevant quantities into the formula. In some cases the nature of the errors allowed for the award of an M mark may be specified.

Α

Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated Method mark is earned (or implied). Therefore M0 A1 cannot ever be awarded.

В

Mark for a correct result or statement independent of Method marks.

Ε

A given result is to be established or a result has to be explained. This usually requires more working or explanation than the establishment of an unknown result.

Unless otherwise indicated, marks once gained cannot subsequently be lost, eg wrong working following a correct form of answer is ignored. Sometimes this is reinforced in the mark scheme by the abbreviation isw. However, this would not apply to a case where a candidate passes through the correct answer as part of a wrong argument.

- When a part of a question has two or more 'method' steps, the M marks are in principle independent unless the scheme specifically says otherwise; and similarly where there are several B marks allocated. (The notation 'dep *' is used to indicate that a particular mark is dependent on an earlier, asterisked, mark in the scheme.) Of course, in practice it may happen that when a candidate has once gone wrong in a part of a question, the work from there on is worthless so that no more marks can sensibly be given. On the other hand, when two or more steps are successfully run together by the candidate, the earlier marks are implied and full credit must be given.
- e The abbreviation ft implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A and B marks are given for correct work only differences in notation are of course permitted. A (accuracy) marks are not given for answers obtained from incorrect working. When A or B marks are awarded for work at an intermediate stage of a solution, there may be various alternatives that are equally acceptable. In such cases, exactly what is acceptable will be detailed in the mark scheme rationale. If this is not the case please consult your Team Leader.

Sometimes the answer to one part of a question is used in a later part of the same question. In this case, A marks will often be 'follow through'. In such cases you must ensure that you refer back to the answer of the previous part question even if this is not shown within the image zone. You may find it easier to mark follow through questions candidate-by-candidate rather than question-by-question.

f Unless units are specifically requested, there is no penalty for wrong or missing units as long as the answer is numerically correct and expressed either in SI or in the units of the question. (e.g. lengths will be assumed to be in metres unless in a particular question all the lengths are in km, when this would be assumed to be the unspecified unit.)

We are usually quite flexible about the accuracy to which the final answer is expressed and we do not penalise over-specification.

When a value is given in the paper

Only accept an answer correct to at least as many significant figures as the given value. This rule should be applied to each case.

When a value is not given in the paper

Accept any answer that agrees with the correct value to 2 s.f.

ft should be used so that only one mark is lost for each distinct accuracy error, except for errors due to premature approximation which should be penalised only once in the examination.

There is no penalty for using a wrong value for g. E marks will be lost except when results agree to the accuracy required in the question.

g Rules for replaced work

If a candidate attempts a question more than once, and indicates which attempt he/she wishes to be marked, then examiners should do as the candidate requests.

If there are two or more attempts at a question which have not been crossed out, examiners should mark what appears to be the last (complete) attempt and ignore the others.

NB Follow these maths-specific instructions rather than those in the assessor handbook.

For a *genuine* misreading (of numbers or symbols) which is such that the object and the difficulty of the question remain unaltered, mark according to the scheme but following through from the candidate's data. A penalty is then applied; 1 mark is generally appropriate, though this may differ for some units. This is achieved by withholding one A mark in the question.

Marks designated as cao may be awarded as long as there are no other errors. E marks are lost unless, by chance, the given results are established by equivalent working.

'Fresh starts' will not affect an earlier decision about a misread.

Note that a miscopy of the candidate's own working is not a misread but an accuracy error.

- If a graphical calculator is used, some answers may be obtained with little or no working visible. Allow full marks for correct answers (provided, of course, that there is nothing in the wording of the question specifying that analytical methods are required). Where an answer is wrong but there is some evidence of method, allow appropriate method marks. Wrong answers with no supporting method score zero. If in doubt, consult your Team Leader.
- j If in any case the scheme operates with considerable unfairness consult your Team Leader.

C	Question	n Answer	Marks	Guida	nce
1		Use of $T = \frac{\lambda e}{l}$	M1	Attempt at one tension; allow use of <i>x</i>	allow 2 <i>l</i> for M1
			A1	$\frac{20(d-0.4)}{0.4}$ or $\frac{30(d-0.6)}{0.6}$	either term seen, accept in terms of x
		Weight = tension 1 + tension 2	M 1		condone Wg and W/g
			A 1	100 = 50d - 20 + 50d - 30	fractions and brackets removed
		(AW =) 1.5 (m)	A1		
			[5]		
2	(i)	Use of correct formula	M1	$v^2 = 0^2 + 2 \times 9.8 \times 0.4$	or by energy
		Vert speed imm before bounce = $2.8 \text{ (m s}^{-1})$	A1		
		Time between bounces = 0.286 (s) (2/7)	B1		
			[3]		
2	(ii)	Use of their t in a correct formula	M1	$0 = u + 9.8 \times 0.5(t)$ Allow their value of t	or -u = u - 9.8t
		Vert speed imm after bounce = $1.4 \text{ (m s}^{-1})$	A1		
		Coeff of rest = 0.5	B1ft	Their values for v after/ v before	must be worked out to fraction or decimal; $0 \le e \le 1$
			[3]		
2	(iii)	Imp = change of mom	M1	$I = 0.3 \times (v) + 0.3 \times (u)$ Allow their u, v	allow sign errors for M1, allow if answer implies use of their values
		I = 1.26 (N s)	A 1	CAO	-
			[2]		
3	(i)	Use of $F = ma$	M1	$\frac{3}{2}t - 1 = 0.2\frac{\mathrm{d}v}{\mathrm{d}t}$	allow sign errors or <i>m</i> omitted
		Integrate correctly	A1	$v = \frac{15}{4}t^2 - 5t(+c)$	allow if c missing or wrong
		$v = \frac{15}{4}t^2 - 5t + 0.8$	A1		oe
			[3]		

C	Questio	n	Answer	Marks	Guida	nce
3	(ii)		Use $vel = 0.8$	M1	$\frac{15}{4}t^2 - 5t + 0.8 = 0.8$	ft their (i)
			t = 1.33 (s) or 1 1/3 (s)	A1	must come from correct equation for v	Accept 4/3
				[2]		
3	(iii)		Integrate to find <i>x</i>	M1*	At least 2 terms with powers increased by 1	
			$x = \frac{15}{12}t^3 - \frac{5}{2}t^2 + 0.8t$	A1	Need to state $c = 0$, or use limits	
			Solve for $x = 0$	*M1		
			t = 1.6 (s) or 0.4 (s)	A1	Both answers needed; must be from correct work to find equation	Ignore $t = 0$
				[4]		
3	(iv)		x(3) - x(2)	M1	Allow for $x(2)$ or $x(3)$ worked out from (iii)	13.65 or 1.6
			Distance is 12.05 (m)	A1		Accept 12 or 12.1
				[2]		_
4	(i)		Conservation of momentum	*M1	Must have 4 terms	allow sign errors, $\cos\theta$ omitted
				A1	$0.1 \times 3 + 0.2 \times 1 \times \cos \theta = 0.1 \times a + 0.2 \times b$	a and b are vel components of A and B to right, respectively, after collision
			Newton's experimental law	*M1	Must have 4 terms and 0.8	allow sign errors, $\cos\theta$ omitted
				A1	$b - a = -0.8(1 \times \cos \theta - 3)$	
			Attempt to solve their 2 sim eqns	M1*	Dep both previous M marks	allow 1 slip
			0.12 in same direction as before	A1	Direction may be implied by working	withhold if direction stated to left
				[6]		
4	(ii)		b = 2.04	B1	Must be seen/used in (ii)	
			vel of B perp to line of centres = 0.8	B1	$(1 \times \sin \theta)$	
			Direction of B after collision makes angle	M1	$\tan \varphi = 0.8/2.04;$	Allow with their 0.8 and 2.04 (<i>b</i> from
			21.4° with line of centres	A1	or 0.374 rads	(i)); allow $\tan \varphi = 2.04/0.8$, if angle clear, leading to 68.4° for A1
			Angle turned through by B is 31.7°	A1ft [5]	or 0.554 rads; allow +/-	$53.1(3) - \varphi$, $0.927 - 0.374$ rads

Q	Question	Answer	Marks	Guid	lance
5	(i)	Use of energy equation at A and B	M1	3 terms needed $mg0.6\cos\frac{\pi}{6} = mg0.6\cos\theta + \frac{1}{2}mv^2$	allow sign error, missing $m / g / r$
		F = ma radially	A1 M1 A1	$mg\cos\theta - R = \frac{mv^2}{0.6}$	allow if θ replaced by $\varphi + \pi/6$ allow sign error, missing m / g
		Use of $R = 0$ $\cos TOB = \frac{\sqrt{3}}{3} AG$	M1 A1	May be incorporated in previous step Completely correct	not given if decimals used for angle.
		,	[6]		
5	(ii)	Use of $\sqrt{3}/3$ in 'correct' equation in (i)	M1	$mg0.6\cos\frac{\pi}{6} = mg0.6 \times \frac{\sqrt{3}}{3} + \frac{1}{2}mv^{2}$ or $mg\frac{\sqrt{3}}{3} = \frac{mv^{2}}{0.6}$	equation must have gained M1 in (i) but allow restart here
		1.84 (m s ⁻¹)	A1 [2]	3 0.6	
5	(iii)	Use of $F = ma$ tangentially	M1	$mg\sin\theta = ma$ seen	allow missing m/g , – sign; allow M1
		$8.00 (\text{m s}^{-2})$	A1 [2]		if angular accel found
6	(i)	Moments about B for equilibrium of BC	M1	$2Wl\cos 60^{\circ} + F2l\sin 60^{\circ} = R2l\cos 60^{\circ}$	3 moment terms, condone sin/cos errors and missing <i>l</i> . Need trig terms for M1
		$W + \sqrt{3} F = R \qquad AG$	A1	Must be formula for <i>R</i>	correct, with sin/cos evaluated
			[2]		

	Questio	n	Answer	Marks	Guida	nce
6	(ii)		Moments about A for equilibrium of whole system	M1	At least one of <i>F</i> and <i>R</i> terms must involve lengths of both rods	At least 3 moment terms, condone sin/cos errors, sign errors and <i>l/2l</i> confusion/missing. Wrong use of forces at <i>B</i> gets M0
				A1	$Wl\cos 30 + 2W(2l\cos 30 + l\cos 60) + F(2l\sin 60 + 2l\sin 30) = R(2l\cos 30 + 2l\cos 60)$	4 terms, accept sin/cos errors and <i>l/2l</i> confusion/missing and sign errors for A1
				A1	sin/cos left in, but correct	
			$W\left(\frac{5\sqrt{3}}{2}+1\right)+F\left(\sqrt{3}+1\right)=R\left(\sqrt{3}+1\right)$	A1	fully correct, oe. Mark final answer	accept $5.33W + 2.73F = 2.73R$, $W\left(\frac{13}{4} - \frac{3\sqrt{3}}{4}\right) + F = R$
					Allow full credit for candidates who work out internal forces at B and work correctly from there.	$Eg 3R = \sqrt{3}F + 7.5W$
				[4]		
6	(iii)		Solving 2 sim equations to eliminate F or R	M1	Both equations must involve W , F and R	allow slips in working
				A1	$F = \frac{3\sqrt{3}}{4}W$	$F = 1.299 \ W$
				A1	$R = \frac{13}{4}W$	R = 3.25 W
			Use $F = \mu R$ to find μ	M1	At any point	
			$(\mu =)\frac{3\sqrt{3}}{13} (0.39970)$	A1		Accept 0.4 if with correct working $5.33(R - 1.73F) + 2.73F = 2.73R$ $2.6R = 6.52F$
					Or eliminate W M1A1A1	2.01 - 0.321
					Use $F = \mu R$ M1	
					cao A1	
				[5]		

C	Questio	n	Answer	Marks	Guida	nce
7	(i)		Use of $F = ma$ when string stretched	M1	Must have mg – tension term (involving 39.2 m , 0.8 and x) = ma	allow if sign errors; x could be length or ext of string, or from eq ^m pos.
					$mg - \frac{39.2m(x - 0.8)}{0.8} = m\ddot{x}$	$mg - \frac{39.2mx}{0.8} = m\ddot{x} \text{ leads to}$
				A1	$\ddot{x} = -49(x-1)$	$\ddot{x} = -49(x - 0.2)$
						$mg - \frac{39.2(x+0.2)}{0.8} = m\ddot{x}$ leads to
						$\ddot{x} = -49x$
			Show $x = 1$ is centre of SHM or that $x = 1$ is equilibrium position.	B1	and state about $x = 1$	Convincingly
				[3]		
7	(ii)		By energy	M1	Must be PE term and EE term	Allow for missing '2', wrong 'g' or inconsistent lengths
				A1	$mg(0.8+e) = \frac{39.2me^2}{2 \times 0.8}$	Or $mgh = \frac{39.2m(h-0.8)^2}{2 \times 0.8}$ and
						h = 0.8 + e
						$2.5e^2 - e - 0.8 = 0$
			e = 0.8 satisfies this equation AG	A1	Or by solving quadratic in e	Convincingly
					Allow full credit if done correctly from $v^2 = \omega^2(a^2 - x^2)$	Allow integration of $v \frac{dv}{dx} = g - 49x$
				[3]		

	Question	Answer	Marks	Guidance	
7	(iii)	For SHM, $\omega = 7$	B1		To be awarded if seen in (i) or (iv)
		a = 0.6	B1		or seen or used here
		Correct use of appropriate SHM distance equation	M1	$-0.2 = 0.6 \cos(7t) \text{ or } -0.2 = 0.6 \sin(7t)$	Allow +0.2, allow their a and ω
		t = 0.272(9476) from bottom ($x = 1.6$) to $x = 0.8$	A1	Could be 0.0485 + 0.224	
		t = 0.404(061) from O to $x = 0.8$	B1	Or $\frac{2\sqrt{2}}{7}$	May be seen first
		Time to reach lowest point = 0.677 s	A1ft	('0.273' + '0.404')	
			[6]		
7	(iv)	Use of $v = -a\omega\sin\omega t$ or $a\omega\cos\omega t$	M1	Must ft from their 'x' equation in (iii), or shown here	Allow use of their a and ω , sign error
		$v = -0.6 \times 7\sin 7t$	A1	or $0.6 \times 7\cos 7t$	
		Use of $t = 0.8 - 0.677 = 0.123$ after bottom point	B1ft	Or use of $t = 0.3475$ in 'cos' version	Must be between 0 and 0.8
		v = 3.19 (3.185677)	A1	(-)3.187	Do not allow if direction stated to be down.
			[4]		

OCR (Oxford Cambridge and RSA Examinations) 1 Hills Road Cambridge **CB1 2EU**

OCR Customer Contact Centre

Education and Learning

Telephone: 01223 553998 Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

Oxford Cambridge and RSA Examinations is a Company Limited by Guarantee Registered in England Registered Office; 1 Hills Road, Cambridge, CB1 2EU Registered Company Number: 3484466 **OCR** is an exempt Charity

OCR (Oxford Cambridge and RSA Examinations) Head office

Telephone: 01223 552552 Facsimile: 01223 552553



