## **CAMBRIDGE INTERNATIONAL EXAMINATIONS**

Cambridge International Advanced Subsidiary and Advanced Level

## MARK SCHEME for the May/June 2015 series

## 9702 PHYSICS

9702/22

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2015 series for most Cambridge IGCSE<sup>®</sup>, Cambridge International A and AS Level components and some Cambridge O Level components.

 ${\small \circledR}$  IGCSE is the registered trademark of Cambridge International Examinations.



Page 2	2 Mark Scheme		Paper	
	Cambridge International AS/A Level – May/June 2015	9702	22	

1 (a) (work =) force 
$$\times$$
 distance or force  $\times$  displacement or ( $W =$ )  $F \times d$  M1

units of work: 
$$kg m s^{-2} \times m = kg m^2 s^{-2}$$
 A1 [2]

(c) 
$$R = V/I$$
 units of  $V$ : kg m<sup>2</sup> s<sup>-2</sup>/As **and** units of  $I$ : A

$$R = P/I^2$$
 [or  $P = VI$  and  $V = IR$ ] (B1)  
units of  $P$ : kg m<sup>2</sup> s<sup>-3</sup> and units of  $I$ : A (C1)

or  

$$R = V^2/P$$
 (B1)  
units of V: kg m<sup>2</sup> s<sup>-2</sup>/As **and** units of P: kg m<sup>2</sup> s<sup>-3</sup> (C1)

units of 
$$R$$
:  $(kg m^2 s^{-2}/A^2 s =) kg m^2 s^{-3} A^{-2}$  A1 [3]

(b) (i) 
$$v = u + at$$
 (or  $s = ut + \frac{1}{2}at^2$  and  $v^2 = u^2 + 2as$ )
$$= 0 + (3.00 - 1.25) \times 9.81$$
C1

$$= 17.2 (17.17) \,\mathrm{m \, s^{-1}}$$
 A1 [3]

(ii) 
$$s = ut + \frac{1}{2}at^2$$

$$s = \frac{1}{2} \times 9.81 \times (1.25)^2 = 7.66$$
 C1  
 $s = \frac{1}{2} \times 9.81 \times (1.75)^2 = 15.02$  C1

$$(distance = 7.66 + 15.02)$$

$$[v = u + at = 0 + 9.81 \times (2.50 - 1.25) = 12.26 \,\mathrm{m \, s^{-1}}]$$

or

$$s = \frac{1}{2} \times 9.81 \times (1.25)^2 [= 7.66]$$
 (C1)

$$s = 12.26 \times 0.50 + \frac{1}{2} \times 9.81 \times (3.00 - 2.50)^{2} [= 7.36]$$
 (C1)

 $(distance = 2 \times 7.66 + 7.36)$ 

Example alternative method:

$$s = (v^2 - u^2)/2a = (12.26^2 - 0)/2 \times 9.81 [= 7.66]$$
 (C1)

$$s = (v^2 - u^2)/2a = (17.17^2 - 12.26^2)/2 \times 9.81 [= 7.36]$$
 (C1)

 $(distance = 2 \times 7.66 + 7.36)$ 

Page 3		3	Mark Scheme		Paper	
			Cambridge International AS/A Level – May/June 2015	9702	22	
			22.7 (22.69 or 23) m		A1	[3]
	(	iii)	(s = 15.02 – 7.66 =) 7.4 (7.36) m (ignore sign in answer)		A1	
			down		A1	[2]
	(c)	stra	aight line from positive value of $v$ to $t$ axis		M1	
		sar	ne straight line <u>crosses</u> $t$ axis at $t = 1.25$ s		A1	
		sar	me straight line continues with same gradient to $t = 3.0 \mathrm{s}$		A1	[3]
3	(a)	(i)	(vertical component = 44 sin 30° =) 22 N		A1	[1]
		(ii)	(horizontal component = 44 cos 30° =) 38(.1) N		A1	[1]
	(b)	W:	× 0.64 = 22 × 1.60		C1	
		(W	=) 55 N		A1	[2]
	(c)	or I	as a horizontal component (not balanced by <i>W</i> )  has 38 N acting horizontally  N acts on wall			
			vertical component of <i>F</i> does not balance <i>W</i> F and <i>W</i> do not make a closed triangle of forces		B1	[1]
	(d)	line	from P in direction towards point on wire vertically above $W$ and direc	tion up	B1	[1]
4	(a)	(p =	=) mv		C1	
		Δρ	$(= -6.64 \times 10^{-27} \times 1250 - 6.64 \times 10^{-27} \times 1250) = 1.66 \times 10^{-23} \text{ Ns}$		A1	[2]
	(b)	(i)	molecule collides with wall/container and there is a change in momen	itum	B1	
			change in momentum / time is force or $\Delta p = Ft$		B1	
			many/all/sum of molecular collisions over surface/area of container propressure	oduces	B1	[3]
		(ii)	more collisions per unit time so greater pressure		B1	[1]
5	(a)	cur	ved line showing decreasing gradient with temperature rise		M1	
		sm	ooth line not touching temperature axis, not horizontal or vertical anywh	nere	A1	[2]
	(b)	(i)	(no energy lost in battery because) no/negligible internal resistance		B1	[1]

Page 4	age 4 Mark Scheme		Paper
	Cambridge International AS/A Level – May/June 2015	9702	22

(ii) 
$$I = V/R$$

$$= 8/15 \times 10^{3} \text{ or } 1.6/3.0 \times 10^{3} \text{ or } 2.4/4.5 \times 10^{3} \text{ or } 12/22.5 \times 10^{3}$$

$$= 0.53 \times 10^{-3} \text{ A}$$

$$A1 \quad [2]$$
(iii)  $\text{ p.d. across } X = 12 - 8.0 - 3.0 \times 10^{3} \times 0.53 \times 10^{-3} (= 2.4 \text{V})$ 

$$R_{X} = 2.4/(0.53 \times 10^{-3})$$

$$C1$$

$$R_{X} = 2.4/(0.53 \times 10^{-3})$$

$$C1$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$C1$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$C1$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.0 - 3.0) \times 10^{3}$$

$$R_{X} = (22.5 - 15.$$

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	22

(c) 
$$v = f\lambda$$
 C1  
 $f = 3.0 \times 10^8 / (2.8 \times 10^{-2}) [= 1.07 \times 10^{10} \text{Hz}]$  C1  
11 (10.7) GHz A1 [3]

7 (a) 92 protons and 143 neutrons

B1 [1]

(b)

	value		
а	1		
b	0	(a and b both required)	B1
С	141		B1
d	55		B1 [3]

(c) kinetic energy (of products) or gamma/ $\gamma$  (radiation or photon) B1 [1]

(d) (total) mass on left-hand side/reactants is greater than (total) mass on right-hand side/products

M1

difference in mass is (converted to) energy

A1 [2]